

Original Research Article

Design and Performance Evaluation of Photovoltaic systems with Automatic Dust Wiper in a Natural Dusty Environment

ABSTRACT

The accumulation of dust on solar panels affects the transmittance of solar panel glazing which leads to the degradation of its efficiency due to low levels of irradiance reaching the cells. In this work, the response of polycrystalline silicon solar panels toward dust in a natural dusty environment was experimentally investigated at a location in Calabar close to the Calabar river. The experimental measurements were carried out in real-time outdoor conditions where human activities take place. An automatic dust wiping/cleaning mechanism to ensure the panel surface was kept clean was deployed in the study. An intelligent maximum power point (MPP) trackers for tracking the maximum power points of the panels were also utilized for this work. Results obtained revealed that the accumulation of dust on polycrystalline solar panel adversely affects its power output and efficiency. From the results, it was also revealed that the average panel temperature of the photovoltaic system with the automatic dust wiping mechanism was 5.30°C lower than the other system without the mechanism. This lower panel temperature led to an increase of 16%, 32.5%, 43.40% and 43.37% in average voltage, average current, average power and average efficiency respectively over the dusty panel. It was demonstrated that solar panel efficiency plummets as panel temperature rises due to heat dissipation caused by the accumulation of dust.

Keywords: Dust, shade, automatic dust-wiping mechanism, maximum power point, solar panel, efficiency

1. INTRODUCTION

The photovoltaic (PV) cell is one of the most amazing mechanisms developed by man for the generation of electricity. Connecting the PV cells in series and parallel make up a solar panel which can be carefully assembled with other components to make up a photovoltaic system. The birth of the PV system for the generation of electricity was made possible through the PV effect which was discovered by Alexandre E. Becquerel in 1839 [1-3]. At present, PV systems are ranked as the most favourable and reliable source of energy in the middle east and Africa due to the abundant solar irradiation of the regions [4]. Due to the remarkable and steady improvements in PV technology, PV systems are no more confined to street lighting or household applications since it has been shown that they can be used to generate power on large scales in the range of mega and gigawatt [5]. PV systems possess many advantages (long-lasting, almost maintenance-free, minimum operational control and generating maximum electricity during periods of peak load demand) which makes them eye-catching for both small and large-scale investments [6-7].

The working principle of the PV system envelops features including charge controller topology, battery technology, solar panel technology and inverter design. Regardless of these remarkable features, PV systems are constantly influenced by atmospheric factors including temperature variations, ageing, wind, shading and dust [8-10]. The emergence of solar tracking technology enabled solar panels and PV systems in capturing maximum solar radiation which enhance the power output and efficiency [11-12]. Notwithstanding the enormous benefits and improvements that solar tracking technology adds to PV systems, temperature, dust and shade still affect their performance efficiency [13-15].

Particles with sizes less than 500 μm are classified as dust, and their deposition, composition and morphology depends on the characteristics of the location [16-18]. Dust is normally measured in micrometers and comprises of minute particles of various elements and sizes, which are transported by air currents and formed by the disintegration of solids into tiny pieces through crushing, grinding or impact among other ways [19-20]. Some particles cause crowding in the dust layer which results in adhesion to surfaces due to ionic charges, which inevitably causes significant increase in effort required to remove dust particles from surfaces [21-22]. The size of particles and the density of dust on the surface of solar panel influences the plummet in the performance of solar panels [23]. The accumulation of dust on the surface of a solar panel tends to trigger a significant rise in temperature due to the affected cell heating up while acting as a barrier to the generated photocurrent [24]. This phenomenon can lead to the birthing of hot spot that have the potential to cause severe damage to the solar panel [25]. The performance and conversion efficiency of

solar panels is related to the size of the dust particles deposited on it. Dust made of very fine particles have minimum interparticle separation between them which makes it very difficult for light to pass through to reach the solar panel [26]; this cause a higher drop in performance efficiency of a solar panel when compared with dust of larger particle and larger interparticle separation [27].

The output power of a solar panel has been ascertained to drop by 85% due to sand, dust, algae-like substance and even small stones that accumulate on their surface, which means regular cleaning is a must if maximum performance from the panel is desired [28]. The shading, masking and coating due to deposition, accumulation and contamination can be classified into two categories: soft shade and hard shade [29]. Soft shades can be formed due to smoke, dust particles in the air hovering over the surface of the solar panel or a distant obstruction such as the diffused or dispersed shadow of a tree, adjacent building, towers, telephone poles or clouds which significantly reduces the amount of radiation reaching the solar cells. While hard shade is an obstruction such as fallen leaves, stones, bird droppings or a tree branch laying on the panel surface that can completely obstruct light from reaching the solar cells. [30].

Gholami et al. [31] carried out an experimental study about the impact of dust accumulation on a solar panel surface after 70 days without rainfall. Their findings revealed that the surface density of the accumulated dust increased up to 6.0986 g/m², which triggered a 21.47% decrease in the output power. Said and Walwil [32] researched a dusty solar panel for 5 weeks without cleaning in Dhahran, Saudi Arabia. They realized that the short circuit current and output power dropped by 13% and 6% respectively. Kaldellis and Kapsali [33] studied how PV system outputs are affected by different air pollutants. They disclosed that the output parameters of PV systems are severely affected by dust deposition and accumulation on PV surfaces. While Sulaiman et al. [34] researched the impact of dust on the performance of a 50 W solar panel using artificial dust (mud and talcum) and clear plastic under constant radiation sources in a laboratory. Their results portrayed a massive drop of 50% and 18% for efficiency and maximum power respectively. Furthermore, their results show just a slight difference in the performance of the panel covered with mud and talcum. However, Darwish et al. [35] using different types of dust pollutants studied the impact of each pollutant on the performance of PV systems. They concluded that ash, silica and limestone are the pollutants that mostly influence the performance of PV systems. Mustafa et al. [36] investigated the impact of dust accumulation, bird dropping, shading effects and water drops on the performance of PV systems. From their analysis, it was revealed that dust accumulation caused the output power and efficiency to drop by 8.80% and 11.86% respectively. While about a 7.40% reduction in the output power was observed when the panel was covered with bird droppings. When the surface of the PV panels was exposed to water droplets, an improvement of at least 5.9% in the output power was observed. Jiang et al. [37] researched on the impact of airborne dust deposition on PV module performance. Data was obtained when the density of the accumulated dust reached 22 g/m². Analysis of the obtained data revealed a 22% decrease in the short circuit current and a 6% reduction in the open circuit voltage. Andrea et al. [38] studied the effect of industrial dust deposition on PV module performance in Arusha Tanzania. Dust utilized in the study was obtained from fertilizer, gypsum, aggregate crusher and coal mine industries. Maximum module efficiency loss was observed to be 64%, 42%, 30%, and 29% for coal, aggregate, gypsum, and organic fertilizer dust, respectively. Their results also show that PV module performance depreciated with the increase in temperature owing to heat dissipation triggered by dust accumulation.

The effect of various types of shade, dirt and dust accumulation on solar panel surfaces have been investigated. As a matter of fact, there is a plethora of obtainable literatures on the effect of dust on the performance of photovoltaics, but a huge amount of the obtainable information is only valid to for a specific location or region and does not apply to PV systems with automatic cleaning/wiping mechanism. Generally, there is a shortage of pertinent information on how the performance of PV modules are hindered by dust deposition for a specific location in Nigeria that can be employed by engineers in the design and sizing of PV systems.

Deposition and accumulation of dust on PV module surface is inevitable. Solar panels were designed and manufactured to be optimally efficient in outdoor environments with their surface free from shade, dust and dirt. Since there is difficulty that comes with the regular cleaning of solar panels especially when they are installed on roof tops. Then the solution is to create and design a photovoltaic system that will always be free from dust and dirt irrespective of how dusty the environment might be. Thus the introduction of an automatic cleaning/wiping mechanism will not only ensure that the module surface is kept clean but also ensure that the system remains optimally efficient. The polysilicon technology is the dominant technology in the Nigerian market and is widely utilized for backup power in households and small business premises. Hence the need to

develop a means so that its surface can be kept clean. Investigation on the performance of polysilicon PV systems with automatic cleaning/wiping mechanism is not yet investigated in the Nigeria's prospect.

The aim of this study is to experimentally investigate the degradation in performance efficiency of PV systems caused by the natural accumulation of dust and dirt. In achieving the objectives, an intelligent water timer coupled with relays that is linked to the dust wipers was employed. The intelligent water timer triggers the wiping mechanism once the preset times (6:30 and 13:00) for the PV module surface to be cleaned is reached. Once the preset time is reached, the cleaning/wiping mechanism activates and remains active for 90 seconds before shutting down automatically and reactivating again once the next preset times is reached. This study provides information that will enlighten user of how much energy their PV system will lost as dust and dirt keeps accumulating on solar panel surface.

2. MATERIALS AND METHODS

This section is about the materials used in the study, how they were connected and the steps followed in the course of measurement.

2.1 Materials Utilized in the Study

Two exact 130-watt polysilicon solar panels of the model AF-130W produced by Africell solar were utilized in this study: the output electrical characteristics of the module are revealed in table 1. A digital high-precision intelligent photovoltaic panel maximum power point tracker (MPPT) (model WS400A) manufactured by Elejoy was used to track and determine the maximum power generated by the photovoltaic modules as shown in figure 1a. An intelligent digital programmable water timer (model ZG004) manufactured by Zhigarden and a digital relay timer (model THC-15A) manufactured by Gangbei were also deployed and can be seen in figures 1b and 1c respectively. Water hose, water sprinklers (figure 1d) and wipers were also employed. Solar batteries (Gel battery: 12 V, 100 A) and a digital charge controller were also utilized. A digital hygrometer (model KT-908 shown in figure 1e), a digital solar power meter (model SM206) manufactured by RZ (figure 1f) and a digital non-contact infrared gun thermometer (model GM320) manufactured by Aneng (figure 1g) were deployed for the tracking of the relative humidity, irradiance and temperature respectively at the surface of the solar panel. The range and accuracy of all the measuring instruments are displayed in table 2.

TABLE 1: PV module technical characteristics

Electrical Specification	Value
Maximum Power	130W
Current at Maximum Power	7.18A
Voltage at Maximum Power	18.10V
Short Circuit Current	7.91A
Open-circuit Voltage	21.72V
Number of cells	36
Module dimension	1480mm*670mm*35mm

TABLE 2: Description of instrument

Instrument	Company	Model	Accuracy	Range
MPP Tracker	Elejoy	WS400A	±0.1 Watt ±0.1 Volt ±0.1 Amps	0-400 W 0-60 V 0-20 A
Solar Power Meter	RZ	SM206	0.1 W/m ² 0.1 Btu	0.1-1999.9 W/m ² 0.1-1999.9 Btu
Hygrometer	KT	KT-908	±5% RH ±1°C	0-100% -50.0-70.0°C
Non-Contact Infrared Gun Thermometer	Aneng	GM320	±1.5°C	-50.0 to 400.0°C
Water Timer	Zhigarden	ZG004	1s	1s-99min 59s.
Relay Timer	Gangbei	THC-15A	1s	0-15 A



Figure 1: materials used for the experimental setup

2.2 Experimental setup

The experiment was done in an outdoor environment in Calabar at a location close to the Calabar river (latitude 4°57'38.6161" N and Longitude 8°18'58.482"). The solar panels were installed at an angle of 5° facing the north on a platform of one metre above sea level. One solar panel was installed with the cleaning/wiping mechanism and served as the control, while the other was left unattended for dust to accumulate.

For the dusty solar panel, connecting cables were connected from its output to the input of the intelligent MPP tracker from which its maximum power points were tracked and determined as displayed in figure 2. For the panel installed with the cleaning/wiping mechanism, connecting cables were connected from its output into a two-way switch. One output of the two-way switch leads to the intelligent MPP tracker from which its maximum power points were precisely tracked and **determined**, while the other output enters the

input of the charge controller for smooth charging of the battery as shown in figure 3. The input of the programmable timer relay was connected to the battery while the output powers the wiper which wipes the surface of the solar panel. The input of the intelligent water timer was connected to a tap from a water tank, while the output led to the water sprinkler via a hose. Through the water sprinkler, water was directed to the surface of the solar panel.




Figure 2: The experimental setup for the dusty panel




Figure 3: The experimental setup for the clean panel

2.3 Measurement procedure

Data was acquired from the solar panels at 30 minutes' interval from 6:00 to 18:00 for 16 weeks. During data acquisition, data were taken from both panels simultaneously. The time of day was noted, while the power, current and voltage from the panels were ascertained with the aid of the intelligent MPP tracker. The humidity level, the surface temperature and the level of irradiance at the surface of the panels were measured through the digital hygrometer, digital infrared gun thermometer and digital solar power meter respectively.

2.4 Data processing and measurements

This study was carried out in real-time outdoor conditions with varying atmospheric parameters. With the aid of the intelligent MPP tracker, the maximum power at maximum power point P_{mp} , the open circuit voltage V_{oc} , the instantaneous current I_{mp} and voltage V_{mp} at maximum power under a particular real-time

atmospheric condition were measured. The efficiency of a solar panel is significantly influenced by the current and voltage it can generate which is affected by maintenance and atmospheric parameters. The V_{mp} and the V_{oc} are immensely influenced by temperature (T) which can be ascertained by (1) as revealed by [39]. Also the I_{mp} and the short circuit current I_{sc} are immensely influenced by irradiance (H) and can be ascertained via (2) also revealed by [39]. In contrast, from the data obtained, the normalized power output efficiency was computed with (3) while the solar panel efficiency at STC was confirmed with (4) as shown by [40-41].

Open circuit voltage:

$$V_{oc} = \frac{KT}{Q} \ln \frac{I_{sc}}{I_0} \quad (1)$$

Short circuit current:

$$I_{sc} = bH \quad (2)$$

Normalized power output efficiency:

$$\eta_p = \frac{P_{mea}}{P_{max}} \times 100\% \quad (3)$$

Module Efficiency:

$$\eta_{Mod} = \frac{\text{Power of photovoltaic module} \times 100\%}{\text{Area of photovoltaic module} \times 1000W/m^2} \quad (4)$$

where K and Q are Boltzmann constant and electronic charge respectively. i_0 is the saturation current while b is a constant which is influenced by the semiconductor junction properties. P_{mea} and P_{max} are measured power and power at STC respectively.

2.5 Study Area




Figure 4: Map of study area

Calabar lies on Latitude 4°57'06"N and longitude 8°19'19"E. It has an elevation of 32m above sea level and is the capital of Cross River State located in southern Nigeria. The dominant climate is the tropical monsoon climate and it experiences precipitations almost throughout the entire year excluding the core

months of the dry season which occurs in two short periods of January to March and October to December [42]. Rainfall is substantial in most months with the short dry season having little effect. In Calabar, it is hot and oppressive throughout the year, the rainy season is overcast, while the dry season is mostly cloudy. Throughout the year, the temperature ranges between 64°F (17.78°C) to 92°F (33.33°C) and rarely go above 96°F (35.56°C) or below 58°F (14.44°C) [43].

The average percentage of the sky covered by clouds varies throughout the year. The part of the year with clear skies starts around November 25 and ends around February 15 with December being the clearest. While the part of the year with cloudier (unclear) skies starts around February 15 to November 25 with April being the cloudiest; in which 89% of the time the sky is cloudiest [43]. The length of daytime in Calabar varies very little throughout the year, staying within 24 minutes of 12 hours throughout. The longest day is June 21, with 12 hours, 25 minutes of daylight, while the shortest day is December 21 with 11 hours, 50 minutes of daylight [43].

Calabar experiences significant seasonal variation in its average hourly wind speed. From May 23 to October 15 (4.7 months) is the windier part of the year with an average wind speed of more than 5.8 miles per hour, with August as the windiest month having an average hourly speed of 7.5 miles per hour. The calmer part of the year begins from October 15 to May 23 (7.3 months) with an average wind speed of less than 5.8 miles per hour, with December as the calmest month having an average hourly wind speed of 4.2 miles per hour [43].

The hottest month in Calabar is January, with a mean high temperature of 95.4°F (35.2°C) and a mean low temperature of 74.8°F (23.8°C), while the coldest month is August, with a mean high temperature of 82.9°F (28.3°C). However, the highest and lowest recorded temperature so far is 102°F (38.9°C) and 66°F (18.9°C) which were recorded in the months of January and April respectively [44].

The least humid month is January with a mean relative humidity of 69%, while July through September are the most humid months with a mean relative humidity of 87%. In regard to rainfall, December and July are the months having the least (13.5 days) and most rainfall (29.9 days) respectively [45]. In regard to sunshine hours, December (9.5 hours) is the month with the most sunshine, while August (4 hours) is the month with the least sunshine [45]. The location for this study is on Latitude 4°57'38.6161" N and Longitude 8°18'58.482" E which is less than 400 metre away from the Calabar river as displayed in figure 4.

3. RESULTS AND DISCUSSION

This section presents the results acquired from experimental measurement and analysis, it is divided into four parts. The first part discusses the variations in the atmospheric condition during data acquisition in the study area. The second part presents the analysis of the performance of the solar panels with respect to ambient temperature. In the third and fourth part, analysis is given on how both solar panels responds to varying levels of relative humidity and irradiance respectively. It should be noted that the voltage, current and power used in the analysis of the results are the maximum voltage, current and power respectively that the modules produces instantly under a particular atmospheric condition.

Table 3 displays the summary of the atmospheric data obtained at the site, while table 4 displays the summary of the output electrical parameters of both solar panels under study.

Table 3: Uncertainty analysis of atmospheric data obtained from in-situ measurement

	Relative Humidity (%)	Irradiance (W/m ²)	Ambient Temp (°C)
Statistic			
Minimum	65.53	0.00	25.27
Maximum	93.13	665.9	32.01
Mean	76.24	298.11	29.01
Median	73.07	331.3	29.31
Variance	85.74	41205	4.88
Standard Deviation	9.26	202.99	2.21
Standard Error	1.85	40.6	0.44

Table 4: Uncertainty analysis of solar panel data obtained from in-situ measurement

Statistic	Panel Temp (°C)		Voltage (V)		Current (A)		Power (W)		Efficiency (%)	
	Clean	Dusty	Clean	Dusty	Clean	Dusty	Clean	Dusty	Clean	Dusty
Minimum	24.61	28.35	1.87	1.57	0	0	0	0	0%	0%
Maximum	44.95	51.78	18.35	15.41	4.81	3.24	87.70	49.65	67.46%	38.20%
Mean	34.80	40.08	17.00	14.28	2.12	1.43	38.53	21.81	29.63%	16.78%
Median	34.89	40.19	18.14	15.23	2.46	1.66	44.33	25.10	34.10%	19.31%
Variance	43.05	57.12	11.55	8.15	2.12	0.96	712.10	228.26	4.21%	1.35%
Standard Deviation	6.56	7.56	3.40	2.86	1.46	0.98	26.66	15.11	20.53%	11.62%
Standard Error	1.31	1.51	0.68	0.57	0.29	0.20	5.34	3.02	4.10%	2.32%

3.1. Variation of atmospheric parameters at the site

As displayed in figure 5a, there was constant fluctuation in the atmospheric parameters (temperature, relative humidity and irradiance) at the location of study. A constant rise in irradiance was observed in the morning which peaked at 11:00. Between 11:00 to 13:00 a decrease was observed, between 13:00 to 14:00 another increase was observed, beyond 14:00 there was constant decrease in irradiance. As for the ambient temperature of the location, it increased gradually from morning to 11:30, then attained fair stability until 16:00, then begin to decrease gradually. Also, the relative humidity was high in the morning, an increase in relative humidity was observed between 6:00 to 7:00, then begin to decrease beyond noon time to 14:30, beyond 14:30 an increase in relative humidity was experienced again; this shows that as irradiance increased, relative humidity decreased. Transient variations of atmospheric parameters are triggered by turbulences within the atmosphere.

The impact of dust on solar panel temperature is revealed in figure 5b. the figure shows that dust accumulation on solar panels enhances its operating temperatures which is undesired. This observation was made in the process of acquiring data from both panels which revealed an average panel temperature difference between the clean and dusty panel to be 5.30°C as evident in table 3. Furthermore, the rise and fall in panel temperature also depends on the level of solar irradiance at the surface of the solar panel which is clearly evident in figure 5a. Our observation about the impact of dust on the solar panel operating temperature corresponds with earlier studies by [38] which reported that the operating temperature of the clean module was observed to be lower than that of the dusty one.




Figure 5: Climatic condition at site and panel temperatures with respect to ambient temperature

3.2. Analysis of electrical performance of both solar panel with varying temperature

The impact of dust on the output electrical parameters of the solar panels with respect to ambient temperature is displayed in figure 6. Figure 6a and figure 6b reveals a higher voltage and current performance from the clean solar panel over the dusty one respectively. The low voltage and current performance from the dusty panel is linked to its higher panel temperature (as revealed in figure 5) which is as a result of the dust on its surface absorbing heat and also obstructing air from reaching its surface to enhance cooling. The poor voltage and current performance from the dusty panel is translated to poor output power and efficiency which is evident in figure 6c and figure 6d respectively. These figures reveals that temperature rise in solar panel which is triggered by dust deposition hinders the performance efficiency of solar panels. Our results in figure 6 is in agreement with earlier researches by [13-15] which revealed that temperature, dust and shade affect the performance efficiency of solar panel.




Figure 6: impact of ambient temperature on operating voltage, current, power and efficiency for clean and clean and dusty panels

3.3. Analysis of electrical performance of both solar panel with varying levels of relative humidity

The effect of relative humidity on the clean and dusty solar panel performances is shown in figure 7. From figure 7a and figure 7b respectively, it is revealed that high levels of relative humidity adversely affect the voltage and current performance of both panels. An increase in voltage was observed for both panels as the relative humidity decrease to 80%, below 80% stability in voltage was achieved while a linear increase in current was observed as the humidity level decreases. The figure further shows the dusty panel generating lower voltage and current. High level of humidity hinders solar radiation from reaching the surface of the panels, while the dust on the surface of the dusty panel further hinders the available solar radiation at its surface from going through to reach the cells, which further causes a degradation in its voltage and current performance. Figure 7c and figure 7d which displays the power output and efficiency of both panel respectively is as a result of the voltage and current performances from both panels. **It shows that high levels of relative humidity negatively affect the power output and efficiency of solar panel regardless of the mechanism employed for dust wiping.** It depicts that for the same level of relative humidity around both

panels, the lost in power by the dusty panel was up to 43.40% which is a massive lost. Our observation about the impact of dust on the solar panel output power corresponds with earlier studies by [31] which reported that dust accumulation on solar panels up to 6.0986 g/m^2 triggered a 21.47% decrease in the output power.




Figure 7: impact of relative humidity on operating voltage, current, power and efficiency for clean and clean and dusty panels

3.4. Analysis of electrical performance of both solar panel with varying levels of irradiance

The impact of dust on the output electrical parameters of the solar panels under the same level of irradiance is displayed in figure 8. The figure reveals an increase in voltage from both panels from 0 to 200 W/m^2 , above 200 W/m^2 stability in voltage was attained, while the current, power and efficiency of both panels increases linearly as irradiance increases which conforms to earlier work by [4]. Furthermore, the figure shows low performance in voltage, current, power and efficiency from the dusty solar panel as displayed in figure 8a to figure 8d respectively which is as a result of the obstruction towards solar radiation

caused by dust deposition and accumulation on the panel surface. Solar radiation is one of the most important parameter necessary for the effective operation and functionality of a solar panel. Once it is hindered from reaching the cells of a solar panel, the efficiency of the panel is drastically reduced as evident from figure 8d. The difference between the average maximum efficiency attained by the clean panel and the dusty one is 29.26% which is more than 50% efficiency lost as displayed in table 3, and this shows that for solar panel to keep functioning at its best it must be free from dust and shade at all time. Our observations about the impact of dust on solar panel output electrical parameters corresponds with earlier studies by [38] which reported they observed maximum panel efficiency loss to be 64%, 42%, 30%, and 29% for coal, aggregate, gypsum, and organic fertilizer dust, respectively.




Figure 8: impact of irradiance on operating voltage, current, power and efficiency for clean and clean and dusty panels

4. CONCLUSION

A photovoltaic system with an automatic dust wiping/cleaning mechanism was designed and its impact was evaluated. Loss in performance efficiency of a polycrystalline solar panel due to dust accumulation was investigated in real-time outdoor conditions in an environment where human activity takes place. The impact of dust deposition was ascertained by subjecting both panels to the same environmental and atmospheric conditions. One panel was installed with the automatic dust-wiping mechanism while the other panel was left unattended for the dust to accumulate on it. It was observed that the photovoltaic system with the automatic dust-wiping mechanism performed better in voltage and current performance and efficiency over the dusty

panel. The average panel temperature of the photovoltaic system with the automatic dust-wiping mechanism was 5.30°C lower than the panel without the mechanism. This lower panel temperature led to an increase of 16%, 32.5%, 43.40% and 43.37% in average voltage, average current, average power and average efficiency respectively over the dusty panel. Plummet in voltage and current output due to dust accumulation leads to a loss in power output and efficiency and consequently, huge economic loss to photovoltaic power with concern towards large-scale photovoltaic power generating plants. Solar radiation is one of the most essential parameters necessary for the effective operation and functionality of a solar panel. Once it is hindered from reaching the cells of a solar panel, the efficiency of the panel will immensely decrease. From this study, it is advisable not to mount photovoltaic systems just one metre above the ground in a dusty environment. The study reveals that just 16 weeks after the mounting of any photovoltaic system more than 40% efficiency can be lost due to dust. If a photovoltaic system must be mounted one metre above the ground it must be given considerable care and attention or an automatic dust-wiping mechanism must be installed with it, especially for large-scale photovoltaic power generating plants.

ABBREVIATIONS

I_{sc} : Short circuit current

V_{oc} : Open circuit voltage

V_{mp} : Voltage at maximum power

I_{mp} : Current at maximum power

P_{max} : Maximum power of solar panel at STC

MPP: Maximum power point

STC: Standard test condition

LCD: Liquid crystal display

References

- [1] A. O. Njok, I. O. Ewona and N. A. Akonjom, "The effect of relative humidity on photovoltaics enhanced with automatic cooling mechanism," *Unicross Journal of Science and Technology*, vol. 1, no. 1, pp. 172-183, 2022.
- [2] F. Obeidat, "A comprehensive review of future photovoltaic systems," *Solar Energy*, vol. 163, pp. 545-551, 2018.
- [3] J. Khan and M. H. Arsalan, "Solar power technologies for sustainable electricity generation - a review," *Renewable and Sustainable Energy Reviews*, vol. 55, pp. 414-425, 2016.
- [4] A. O. Njok, F. A. Kamgba, M. K. Panjwani and F. H. Mangi, "The influence of solar power and solar flux on the efficiency of polycrystalline photovoltaics installed close to a river," *Indonesian Journal of Electrical Engineering and Computer Science*, vol. 17, no. 2, pp. 988-996, 2020.
- [5] M. Saidan, A. G. Albaali, E. Alasis and J. K. Kaldellis, "Experimental study on the effect of dust deposition on solar photovoltaic panels in desert environment," *Renewable Energy*, vol. 92, pp. 499-505, 2016.
- [6] S. Mekhilef, R. Saidur and M. Kamalisarvestani, "Effect of dust, humidity and air velocity of photovoltaic cells," *Renewable and Sustainable Energy Review*, vol. 16, pp. 2920-2925, 2012.
- [7] T. Sarver, R. Al Qaraghuli and L. Kazmersky, "A comprehensive review of the impact of dust on the use of solar energy: history, investigations, results, literature and mitigation approaches," *Renewable and Sustainable Energy Review*, vol. 22, pp. 698-733, 2013.
- [8] E. Adıgüzel, E. Özer, A. Akgündoğdu, and A. Ersoy Yılmaz, "Prediction of dust particle size effect on efficiency of photovoltaic modules with ANFIS: an experimental study in Aegean region, Turkey," *Solar Energy*, vol. 177, pp. 690-702, 2019.
- [9] R. S. Anjos, R. Melício, V. M. Mendes, and H. M. Pousinho, "Crystalline silicon PV module under effect of shading simulation of the hot-spot condition," in *Doctoral Conference on Computing, Electrical and Industrial Systems*, L. Camarinha- Matos, M. Parreira-Rocha, and J. Ramezani, Eds., pp. 479- 487, Springer, Cham, 2017.
- [10] Z. A. Darwish, H. A. Kazem, K. Sopian, M. A. Alghoul, and H. Alawadhi, "Experimental investigation of dust pollutants and the impact of environmental parameters on PV performance: an experimental study," *Environment, Development and Sustainability*, vol. 20, no. 1, pp. 155-174, 2018.

- [11] A. O. Njok, and I. O. Ewona, "Diurnal analysis of enhanced solar photovoltaic systems using automatic cooling mechanism," *World Journal of Advanced Engineering Technology and Sciences*, vol. 5, no. 2, pp. 16-23, 2022.
- [12] A. E. Hammoumi, S. Motahhir, A. E. Ghzizal, A. Chalh, and A. Derouich, "A simple and low-cost active dual-axis solar tracker," *Energy Science & Engineering*, vol. 6, no. 5, pp. 607-620, 2018.
- [13] D. S. Rajput and K. Sudhakar, "Effect of dust on the performance of solar PV panel," *International Journal of ChemTech Research*, vol. 5, no. 2, pp. 1083-1086, 2013.
- [14] B. R. Paudyal and S. R. Shakya, "Dust accumulation effects on efficiency of solar PV modules for off grid purpose: a case study of Kathmandu," *Solar Energy*, vol. 135, pp. 103-110, 2016.
- [15] J. C. Ogbulezie, A. O. Njok, M. K. Panjwani and S. K. Panjwani, "The impact of high temperature and irradiance source on the efficiency of polycrystalline photovoltaic (PV) panels in a controlled environment," *International Journal of Electrical and Computer Engineering*, vol. 10, no. 4, pp. 3942-3947, 2020.
- [16] B. Aïssa, R. J. Isaifan, V. E. Madhavan, and A. A. Abdallah, "Structural and physical properties of the dust particles in Qatar and their influence on the PV panel performance," *Scientific Reports*, vol. 6, no. 1, pp. 1-12, 2016.
- [17] A. Pan, H. Lu, and L.-Z. Zhang, "Experimental investigation of dust deposition reduction on solar cell covering glass by different self-cleaning coatings," *Energy*, vol. 181, pp. 645-653, 2019.
- [18] J. Tanesab, D. Parlevliet, J. Whale, and T. Urmee, "The effect of dust with different morphologies on the performance degradation of photovoltaic modules," *Sustainable Energy Technologies and Assessments*, vol. 31, pp. 347-354, 2019.
- [19] Md. M. Rahman, Md. A. Islam, A. H. M. Z. Karim and A. H. Ronee, "Effects of natural dust on the performance of PV panels in Bangladesh," *International Journal of Modern Education and Computer Science*, vol. 10, pp. 26-32, 2012.
- [20] M. Altintas, and S. Arslan, "Analysis of Atmospheric Transported Particulate Matter and Investigation of Its Effects on Solar Panel," In Proceedings of the 9th European Conference on Renewable Energy Systems, Istanbul, Turkey, pp. 712-718, 2021.
- [21] B. S. Yilbas, H. Al-Qahtani, A. Al-Sharafi, S. Bahattab, G. Hassan, N. Al-Aqeeli and M. Kassas, "Environmental dust particles repelling from a hydrophobic surface under electrostatic influence," *Scientific Reports*, vol. 9, pp. 8703, 2019.
- [22] M. Altintas and S. Arslan, "The study of dust removal using electrostatic cleaning system for solar panels," *Sustainability*, vol. 13, pp. 1-18, 2021.
- [23] K. Styszko, M. Jaszczur, J. Teneta, Q. Hassan, P. Burzynska, E. Marcinek, N. Lopian and L. Samek "An analysis of the dust deposition on solar photovoltaic modules," *Environmental Science and Pollution Research*, vol. 26, no. 9, pp. 8393-8401, 2019.
- [24] A. K. Tripathi, M. Aruna, and C. S. N. Murthy, "Performance of a PV panel under different shading strengths," *International Journal of Ambient Energy*, vol. 40, no. 3, pp. 248-253, 2017.
- [25] W. He, F. Liu, J. Ji, S. Zhang, and H. Chen, "Safety analysis of solar module under partial shading," *International Journal of Photoenergy*, vol. 2015, Article ID 907282, 8 pages, 2015.
- [26] H. Lu and W. Zhao, "Effects of particle sizes and tilt angles on dust deposition characteristics of a ground-mounted solar photovoltaic system," *Applied Energy*, vol. 220, pp. 514-526, 2018.
- [27] A. A. Hachicha, I. Al-Sawafta, and Z. Said, "Impact of dust on the performance of solar photovoltaic (PV) systems under United Arab Emirates weather conditions," *Renewable Energy*, vol. 141, pp. 287-297, 2019.
- [28] S. A. Sulaiman, A. K. Singh, M. M. M. Mokhtar and M. A. Bou-Rabee, "Influence of Dirt Accumulation on Performance of PV Panels," *Energy Procedia*, vol. 50, pp. 50-56, 2014.
- [29] M. R. Maghami, H. Hizam, C. Gomes, M. A. Radzi, M. I. Rezadad and S. Hajjghorbani, "Power loss due to soiling on solar panel: A review," *Renewable and Sustainable Energy Review*, vol. 59, pp. 1307-1316, 2016.
- [30] M. Boxwell, "Solar Electricity Handbook: A simple, practical guide to solar energy - designing and installing photovoltaic solar electric systems (6th ed.)," *United Kingdom: Greenstream Publishing*, pp. 409, 2012.
- [31] A. Gholami, I. Khazaei, S. Eslami, M. Zandi and E. Akrami, "Experimental investigation of dust deposition effects on photo-voltaic output performance," *Solar Energy*, vol. 159, pp. 346-352, 2018.

- [32] S. A. Said and H. M. Walwil, "Fundamental studies on dust fouling effects on PV module performance," *Solar Energy*, vol. 107, pp. 328, 2014.
- [33] J. Kaldellis and M. Kapsali, "Simulating the dust effect on the energy performance of photovoltaic generators based on experimental measurements," *Energy*, vol. 36, pp. 5154–5161, 2011.
- [34] S. A. Sulaiman, H. H. Hussain, N. Leh and M. S. Razali, "Effects of dust on the performance of PV panels," *World Acad. Sci. Eng. Technol*, vol. 58, pp. 588–593, 2011.
- [35] Z. A. Darwish, H. A. Kazem, K. Sopian, M. Al-Goul and H. Alawadhi, "Effect of dust pollutant type on photovoltaic performance," *Renewable and Sustainable Energy Review*, vol. 41, pp. 735–744, 2015.
- [36] R. J. Mustafa, M. R. Goma, M. Al-Dhaifallah and H. Rezk, "Environmental impacts on the performance of solar Photovoltaic Systems," *Sustainability*, vol. 12, 1-17, 2020.
- [37] H. Jiang, L. Lu and K. Sun, "Experimental investigation of the impact of airborne dust deposition on the performance of solar photovoltaic (PV) modules," *Atmospheric Environment*, vol. 45, pp. 4299, 2011.
- [38] Y. Andrea, T. Pogrebnya and B. Kichonge, "Effect of industrial dust deposition on photovoltaic module performance: experimental measurement in the tropical region," *International Journal of Photoenergy*, Vol. 2019, Article ID 1892148, 10 pages, 2019.
- [39] A. O. Njok, J. I. Iloke, M. K. Panjwani and F. H. Mangi, "The impact of coloured filters on the performance of polycrystalline photovoltaic (PV) panel in an uncontrolled environment," *International Journal of Electrical and Computer Engineering*, vol. 10, no. 4, pp. 4436-4446, 2020.
- [40] A. O. Njok, J. C. Ogbulezie and N. A. Akonjom, "Evaluation of the performance of photovoltaic system under different wavelengths from artificial light in a controlled environment," *Journal of Applied Science and Environmental management*, vol. 26, no. 6, pp. 1015-1020, 2022.
- [41] N. A. Akonjom and A. O. Njok, "Effect of meteorological parameters on the performance of photovoltaics installed under the guinea savannah atmosphere in cross river state, Nigeria," *Journal of Applied Science and Environmental management*, vol. 26, no. 7, pp. 1299-1306, 2022.
- [42] F. A. Kamgba, C. O. Edet and A. O. Njok, "Effects of some meteorological parameters on wind energy potential in Calabar, Nigeria," *Asian journal of physical and chemical sciences*, vol. 4, no. 1, pp. 1-7, 2017.
- [43] Weatherspark. "Calabar, Nigeria". <https://weatherspark.com/y/58500/Average-Weather-in-Calabar-Nigeria-Year-Round>. Retrieved October 15, 2022.
- [44] Weatherbase. "Calabar, Nigeria". <https://www.weatherbase.com/weather/weather-summary.php?s=46256&cityname=Calabar,+Nigeria>. Retrieved October 15, 2022.
- [45] Weather-atlas. "Calabar, Nigeria". <https://www.weather-atlas.com/en/nigeria/calabar-climate>. Retrieved October 15, 2022.