

TREATMENT AND SLIP EFFECT ON MHD BLOOD FLOW THROUGH A STENOTIC ARTERY: A MATHEMATICAL MODEL

Abstract

Theoretical study of the treatment and slip effect on Magneto-hydrodynamic (MHD) blood flow through a stenotic artery where the porous wall and the boundary slip at the wall of the artery have a significant effect on the blood flow was investigated. The magnetic field is applied radially on the stenotic region of the artery with blood flowing axially. Dimensionless governing equations was solved using Frobenius series method to obtain a solution for the velocity of the blood flow, blood concentration, wall shear stress, fluid acceleration and the volumetric flow rate. The Results showed that, an increase in the chemical reaction increased the blood viscosity causing a decrease in the blood velocity, acceleration and shear stress at the wall but increases the volumetric flow rate of the blood. Increased slip at the wall with stenosis decreases the blood velocity, acceleration and volumetric flow rate but causes an increase in the wall shear stress.

Keywords: Magneto-hydrodynamic (MHD), Slip at the Wall, Chemical Reaction, Pulsatile Pressure, Permeability of Porous Wall.

Nomenclature

P_s Steady State Pressure Gradient	
P_p Pulsatile State Pressure Gradient	
W_h Amplitude of Frequency Pulse Rate	t Time
W_b Amplitude of Frequency of the Body	C Concentration of Blood
f_h Frequency of the Heart Pulse	θ Temperature of Blood
f_b Frequency of Body Acceleration	B_m Applied Magnetic field
G_b Body Acceleration	g Acceleration due to gravity
$G(t)$ Time Dependent Body acceleration	D Coefficient of Mass Diffusivity
\emptyset Inclination of stenosed artery	K Coefficient of Porosity
Φ Phase Difference Angle	Re Reynolds number

C_p Heat capacity
 Q Heat source term
 Pe Peclet number
 Sc Schmidt number
 μ Coefficient of Blood viscosity
 ρ Density of the Blood
 K_r Chemical Reaction
 M Magnetic Parameter
 σ Electrical Conductivity of Blood
 C_w Concentration of the Artery wall
 T_w Temperature of the Artery wall
 Gr Grashof Temperature number
 G_c Grashof Diffusion number
 β_T Coefficient of Volume expansion by temperature
 β_c Coefficient of Volume expansion by concentration
 δ Height of Stenosis
 l_0 Length of Stenosis
 $R(z)$ Stenotic Vessel Radius
 R_0 Normal Artery Radius
 s Shape of Stenosis
 ξ Tapering
 d Position of Stenosis
 z Axial Direction for Flow of Blood
 r Radial Direction for Flow of Blood
 \vec{J} Current Density

1. Introduction.

This theoretical work considers the flow of blood through an inclined artery having stenosis at the artery walls with the effect of heat source and body acceleration which has immense significance and importance in the growth of tumor and cardiovascular disease. Certain factors can affect the viscosity of the blood where the shear stress could reduce its viscosity. Pulsatile blood flow past an artery has caught the attention from researchers because of the relevant applicability in the biotechnological, biomedical and medical sciences. Blood circulation takes place when blood is pumped from the heart to different muscles of the body through the arteries which transports the blood with the pressure gradient creating a pulsatile flow of the blood. The application of induced chemical reaction to the areas where the stenosis is present due to plaques of cholesterols, could help to increase blood flow and treat diseases resulting to hypotension and cardiac failure. Furthermore the application of induced chemicals, drugs and slip at the wall can help treat ailments such as cancer and tumor growth.

Stenosis in the artery affects blood flowing from the heart through the artery Rabbi et al. [1] and Ellahi et al. [2]. Pralhad et al. [3] studied the blood flow through the artery with stenosis with the wall shear stress and the resistance at the wall while Ellahi et al. [4] did a mathematical model explaining the

blood flow through an artery with a composite stenosis. Magnetic field applied on bio fluids have effect on the dynamics of the fluid hence this fluids are bio magnetic fluids with rich application in medical sciences and biomedical engineering. Haik et al. [5] gave a clear distinction between bio magnetic fluid (BFD) and hydro magnetic fluid (MHD). Abdullah et al. [6] studied the effect of magneto-hydrodynamic on the flow of blood through a stenosis that is irregular with the results obtained from the study showing that, the rate of flow of blood reduced as a result of magnetic field applied to the arterial segment.

Srivastava [8] did an analysis of the blood flow motion that is steady through an artery inclined with applied magnetic field with the conclusion that velocity of the blood flow decreases as a result of the increase in the magnetic field.

Sinha et al. [11] did a study on the slip and periodic body acceleration effect on pulsatile flow of blood passing through a segmented stenosed artery. Tripathi and Sharma [13] did a study on heat and mass transfer effects of a blood flow two phases which is pulsatile past a stenosed artery that is narrow with chemical reaction and radiation. Karthikeyan and Jeevitha [14] did a study analysis on the effect of heat and mass transfer on a model in two phases for unsteady blood flow that is pulsatile past an artery with stenosis having a wall that is permeable with

radiation and chemical reaction effects. Amos and Ogulu [16] studied the magnetic field effect on Pulsatile Blood Flow through an axis-symmetric channel that is constricted. Bunonyo and Amos [17] studied the effect of lipid concentration on the blood that flows through an artery channel inclined with magnetic field present.

Thermal radiation had a mixed effect on the blood flow and heat source increase increased the blood flow which was helpful in treating tumor and low blood pressure as discussed by Omamoke et al. [18]. The adoption of Frobenius method and effects of pertinent parameters on the behavior of flow was considered in the research done by Omamoke and Amos [19], Amos et al. [20], Amos et al. [21], Chinedu and Amadi [22].

This study has theoretically analyzed, showing the effects of slip, heat source, body acceleration, inclined artery angle and pulsatile pressure on the non-Newtonian unsteady blood flow through a stenotic artery. The artery walls is porous and permeable with the analysis done by solving the problem of the governing equation using the Frobenius power series method to obtain the velocity of the blood flow, blood acceleration, wall shear stress and volumetric flow rate solutions with a graph illustrating the behavior of the effect of slip, heat source, body acceleration, magnetic field, pulsatile pressure gradient and inclined artery on the blood flow velocity, blood acceleration, shear stress and volumetric flow rate.

2. Formulation of the problem

The axisymmetric flow of blood has the coordinate (r', θ', z') , where the blood flows horizontally in the axial direction of z' . The blood flow assumed to be one dimensional flows through a rigid stenotic artery that is cylindrical with permeability at the porous wall of the artery. The blood is assumed to be non-Newtonian, electrically conducting, incompressible and viscous fluid influenced by a magnetic field applied in the radial direction perpendicular to the axial direction of the blood flow. The constriction at the artery wall is affected by the stenosis position and height.

Figure 1.1 Flow geometry of the stenotic artery

The geometry of the one dimensional blood flow through the segmented stenotic artery, symmetrical in shape was proposed by Eldesoky [23] and Kumar et al. [24] as,

$$R(z') = \{d'(z) - \delta/2[1 + \cos 2\pi l_0 \{z' - d' - l_0/2\}]\} d'(z), d' \leq z' \leq d' + l_0 \quad (1)$$

The greatest stenosis height (R) happens at the center, Nadeem et al. [25].

$$z = d + L \cos(1s-1) \text{ For } s \geq 2 \text{ and } l_1 = d'R_0'$$

3. Governing equation

There is a force that is created when the magnetic field acts on the blood which conducts electricity called the electromagnetic force F^{\rightarrow} .

$$F^{\rightarrow} = q(E^{\rightarrow} + V^{\rightarrow} \times B^{\rightarrow}) \quad (1)$$

$J^{\rightarrow} = \sigma(E^{\rightarrow} + V^{\rightarrow} \times B^{\rightarrow})$ (2) The overall intensity of the magnetic field intensity $B = B_0 + B_1$. A Lorentz force is produced or formed when the electric force combines with the magnetic force on the flow of blood where the intensity of the electric field vector E^{\rightarrow} is negligible.

$$\vec{j} = \sigma(\vec{V} \times \vec{B}) \quad (3)$$

$$\vec{j} \times \vec{B} = -\sigma B_0 \vec{u} \quad (4)$$

$|B_0| = B_0$, F acts in the axial direction, $\vec{u} = (0, 0, u)$ is the distribution of the velocity vector, $\vec{B} = (0, B_0, 0)$ is the distribution of the magnetic field vector.

The concentration of the blood and velocity of blood flow is steady and pulsatile flowing through the stenosed artery that is inclined with the magnetic field applied radially to the axial direction is of the blood flow through the artery.

$$\rho \partial u \partial t = -\partial p \partial z + \rho G(t) + \mu r \partial \partial r (r \partial u \partial r) - \sigma c B_0 u + g \sin \phi - \mu k p u + \rho g B c (C' - C_0) \quad (5)$$

$$\partial C \partial t = D' [\partial^2 C \partial r^2 + 1 r \partial C \partial r] - E' (C' - C_0) \quad (6)$$

Dimensional form of the pressure gradient is expressed as

$$-\partial p \partial z = P_s' + P_p' \cos(\omega h t); t \geq 0 \quad (7)$$

$$\omega h = 2\pi f h \text{ and } \omega b = 2\pi f b$$

$$G(t) = G_b' \cos(\omega b t + \phi); t \geq 0 \quad (8)$$

The dimensionless flow geometry with stenosis, Eldesoky [23] and Kumar et al. [24].

$$R(z) = \{ (1 + \xi z) - \delta [1 + \cos 2\pi l_0 \{z - l_1 - l_0\}] \} (1 + \xi z), l_1 \leq z \leq l_1 + l_0 \quad (9)$$

The dimensionless body acceleration and Pressure gradient

$$G(t) = G_0 \cos(\omega t + \phi); t \geq 0 \quad (10)$$

$$-\partial p \partial z = P_0 + P_1 \cos(\omega_p t); t \geq 0 \quad (11)$$

The momentum equation in dimensionless form is written as for first consideration:

$$Re \partial u \partial t = P_0 + P_1 \cos t + G_0 \cos(\omega t + \phi) + (\partial^2 u \partial r^2 + 1 r \partial u \partial r) - (M_2 + 1K)u + \sin \phi Fr + G_c C \quad (12)$$

$$Sc Re \partial C \partial t = \partial^2 C \partial r^2 + 1 r \partial C \partial r - Kr C \quad (13)$$

Dimensional initial and boundary slip conditions are $\{ \partial u \partial r = -h' u', C' = C'_a \text{ at } r' = R'(z) \partial u \partial r = 0, \partial C \partial r = 0 \text{ at } r' = 0 \}$ (14)

Dimensionless initial and boundary slip conditions are

$$\{ \partial u \partial r = -hu, C = C_a \text{ at } r = R(z) \partial u \partial r = 0, \partial C \partial r = 0 \text{ at } r = 0 \} \quad (15)$$

η depends on the porous material

$$a = R(z) R_0 + \xi z; \xi = \tan \phi, h = -\eta R_0 \sqrt{K}$$

Non dimensional parameters in the governing equations and boundary conditions are transformed to dimensionless form.

$$u = u' u_0; \delta = \delta' R_0; d(z) = R_0 + \xi z'; r = r' R_0; Z = z' R_0; b = \omega b \omega h; t = \omega t'; R(z) = R'(z) R_0; P = R_0' p' u_0 \mu; Re = \rho \omega R_0'^2 \mu; C = C' - C_\infty C_w' - C_\infty; C_a = C_a' - C_\infty C_w' - C_\infty; \delta = \delta' R_0'; M_2 = \sigma R_0'^2 B_0 \mu; Sc = \rho D'; Kr = E' R_0'^2 \theta; G_c =$$

$$g\rho R_0^2 \beta c(C_w - C_0) u_0 \mu; P_p = P_p' R_0^2 u_0 \mu; P_s = P_s' R_0^2 u_0 \mu; \quad G_b = \rho G_b' R_0^2 u_0 \mu; f_r = u_0 \mu g R_0^2; D = D' D_0; k = k_p' R_0^2; \quad (16)$$

4. Method of Solution

The Frobenius method is used to solve the differential equation analytically with the solutions for the governing partial differential equation of the steady and pulsatile blood velocity and blood concentration expressed as function of time

$$u(r,t) = u_0(r) + u_p(r) \varepsilon e^{i\omega t} \quad (17)$$

$$C(r,t) = C_0(r) + C_p(r) \varepsilon e^{i\omega t} \quad (18)$$

5. Solution to the Governing equation

The concentration for the steady and pulsatile state is expressed below as

$$\partial^2 C_0 / \partial r^2 + 1/r \partial C_0 / \partial r - Kr C_0 = 0 \quad (19)$$

$$\partial^2 C_p / \partial r^2 + 1/r \partial C_p / \partial r - \alpha C_p = 0 \quad (20)$$

Where $\alpha = Kr - i\omega Pe$

The expression of the steady and pulsatile state blood flow velocity is given below as

$$\partial^2 u_0 / \partial r^2 + 1/r \partial u_0 / \partial r - \beta u_0 = -G - Gr C_0 \quad (21)$$

$$\partial^2 u_p / \partial r^2 + 1/r \partial u_p / \partial r - \gamma u_p = -L - Gr C_p \quad (22)$$

$$\beta = M_2 + 1K; G = P_0 + \sin \theta Fr; \gamma = M_2 + 1K + Re i \omega \text{ and } L = P_p \cos t + G_b \cos(bt + \varphi)$$

Applying the Funch's theorem, called the Frobenius series on equation (19) – (22) expressed as

$$C_0(r) = \sum x_n r^{n+k} \quad \text{Where } x_n, k \in A_1 \quad (23)$$

$$C_p(r) = \sum y_m r^{m+k} \quad \text{Where } y_m, k \in A_2 \quad (24)$$

$$u_0 = \sum p_n r^{n+k} \quad \text{Where } p_n, k \in A_3 \quad (25)$$

$$u_p = \sum q_m r^{m+k} \quad \text{Where } q_m, k \in A_4 \quad (26)$$

Applying the boundary condition from equation (15) into equation (19) the concentration in steady state is expressed as

$$C_0 = A_1 [1 + Kr^2 + Kr^4 + Kr^6 + Kr^8 + \dots] \quad (27)$$

$$A_1 = CR [1 + Kr^2 + Kr^4 + Kr^6 + Kr^8 + \dots] \quad (28)$$

Applying the boundary condition from equation (15) into equation (20) the concentration in pulsatile state is expressed as

$$C_p = A_2 [1 + \alpha r^2 + \alpha^2 r^4 + \alpha^3 r^6 + \alpha^4 r^8 + \dots] \quad (29)$$

$$A_2 = CR [1 + \alpha r^2 + \alpha^2 r^4 + \alpha^3 r^6 + \alpha^4 r^8 + \dots] \quad (30)$$

The concentration solution from equation (18) is obtained when equation (27) and (29) are combined and then expressed as

$$C(r,t) = A_1[1 + K_1 r^{222} + K_2 r^{42242} + K_3 r^{6224262} + K_4 r^{822426282} + \dots] + (A_2[1 + \alpha_1 r^{222} + \alpha_2 r^{42242} + \alpha_3 r^{6224262} + \alpha_4 r^{822426282} + \dots]) \epsilon e^{i\omega t} \quad (31)$$

Applying the boundary condition in equation (15) to equation (21) the complementary solution for the steady state blood velocity is expressed as

$$u_{0c} = A_3[1 + \beta_1 r^{222} + \beta_2 r^{42242} + \beta_3 r^{6224262} + \beta_4 r^{822426282} + \dots] \quad (32)$$

The particular solution for the steady state blood velocity in equation (21) is expressed as

$$u_{0p} = P_0 + P_1 r^2 + P_2 r^4 + P_3 r^6 + P_4 r^8 \quad (33)$$

The blood velocity solution in equation (17) is the combination of equation (32) and (33).

$$u_0 = A_3[1 + \beta_1 r^{222} + \beta_2 r^{42242} + \beta_3 r^{6224262} + \beta_4 r^{822426282} + \dots] + P_0 + P_1 r^2 + P_2 r^4 + P_3 r^6 + P_4 r^8 \quad (34)$$

Where $A_3 = -$

$$\frac{[h(P_0 + P_1 R^2 + P_2 R^4 + P_3 R^6 + P_4 R^8) + 2P_1 R + 4P_2 R^3 + 6P_3 R^5 + 8P_4 R^7][\beta_1 R^{22} + \beta_2 R^{3224} + \beta_3 R^{522426} + \beta_4 R^{72242628} + \dots] + h[1 + \beta_1 R^{222} + \beta_2 R^{42242} + \beta_3 R^{6224262} + \beta_4 R^{822426282} + \dots]}$$

Applying the boundary condition in equation (15) to equation (22) the complementary solution for the pulsatile state blood velocity is expressed as

$$u_{pc} = A_4[1 + \gamma_1 r^{222} + \gamma_2 r^{42242} + \gamma_3 r^{6224262} + \gamma_4 r^{822426282} + \dots] \quad (35)$$

The particular solution for the pulsatile state blood velocity in equation (22) is expressed as

$$u_{pp} = Q_0 + Q_1 r^2 + Q_2 r^4 + Q_3 r^6 + Q_4 r^8 \quad (36)$$

The blood velocity solution in equation (17) is the combination of equation (35) and (36).

$$u_p = A_4[1 + \gamma_1 r^{222} + \gamma_2 r^{42242} + \gamma_3 r^{6224262} + \gamma_4 r^{822426282} + \dots] + Q_0 + Q_1 r^2 + Q_2 r^4 + Q_3 r^6 + Q_4 r^8 \quad (37)$$

Where $A_4 = -$

$$\frac{[h(Q_0 + Q_1 R^2 + Q_2 R^4 + Q_3 R^6 + Q_4 R^8) + 2L_1 R + 4L_2 R^3 + 6L_3 R^5 + 8L_4 R^7][\beta_2 R^{22} + \beta_{22} R^{3224} + \beta_{23} R^{522426} + \beta_{24} R^{72242628} + \dots] + h[1 + \beta_2 R^{222} + \beta_{22} R^{42242} + \beta_{23} R^{6224262} + \beta_{24} R^{822426282} + \dots]}$$

The blood velocity solution from equation (12) is obtained by substituting equation (34) and (37) into equation (17) which is expressed as

$$u(r,t) = A_3[1 + \beta r^{222} + \beta_2 r^{42242} + \beta_3 r^{6224262} + \beta_4 r^{822426282} + \dots] + P_0 + P_1 r^2 + P_2 r^4 + P_3 r^6 + P_4 r^8 + (A_4[1 + \gamma r^{222} + \gamma_2 r^{42242} + \gamma_3 r^{6224262} + \gamma_4 r^{822426282} + \dots] + Q_0 + Q_1 r^2 + Q_2 r^4 + Q_3 r^6 + Q_4 r^8) \epsilon e^{i\omega t} \quad (38)$$

The Solution for the Fluid Acceleration equation

$$F(r,t) = \frac{dudt}{dt} = i\omega \epsilon e^{i\omega t} (A_4[1 + \gamma r^{222} + \gamma_2 r^{42242} + \gamma_3 r^{6224262} + \gamma_4 r^{822426282} + \dots] + 4Q_1 r + GrA_2 \gamma + Q_1 r^2 + Q_2 r^4 + Q_3 r^6 + Q_4 r^8) + \epsilon e^{i\omega t} P_{py} (i\omega \cos t - \sin t) + \epsilon e^{i\omega t} G_{by} (i\omega \cos (bt + \varphi) - b \sin (bt + \varphi)) \quad (39)$$

The Solution for the Wall Shear Stress equation

$$\frac{dudr}{dr} = A_3[\beta r^2 + \beta_2 r^{3224} + \beta_3 r^{522426} + \beta_4 r^{72242628} + \dots] + 2P_1 r + 4P_2 r^3 + 6P_3 r^5 + 8P_4 r^7 + (A_4[\beta r^{22} + \beta_2 r^{3224} + \beta_3 r^{522426} + \beta_4 r^{72242628} + \dots] + 2Q_1 r + 4Q_2 r^3 + 6Q_3 r^5 + 8Q_4 r^7) \epsilon e^{i\omega t} \quad (40)$$

The Solution for the Volumetric Flow Rate equation

$$Q(r,t) = 2\pi \int r a_0 u(r,t) dr = 2\pi \{ A_3 [a_{22} + \beta a_{4224} + \beta_2 a_{622426} + \beta_3 a_{82242628} + \beta_4 a_{1022426282} + \dots] + P_0 a_{22} + P_1 a_{44} + P_2 a_{66} + P_3 a_{88} + P_4 a_{1010} + (A_4 [a_{22} + \beta a_{4224} + \beta_2 a_{622426} + \beta_3 a_{82242628} + \beta_4 a_{1022426282} + \dots] + Q_0 a_{22} + Q_1 a_{44} + Q_2 a_{66} + Q_3 a_{88} + Q_4 a_{1010}) \epsilon e^{i\omega t} \} \quad (41)$$

6. Graphical Results and Discussion.

From Figure 2.0, it was noticed that increased chemical reaction Kr from $0.5 \leq Kr \leq 2$, caused a decrease in the blood velocity. This occurred because chemical reaction increases the internal viscosity of the blood resulting to a decrease in the blood flow. The blood flow decrease causes a decrease in the blood acceleration and volumetric flow rate in figure 3.0 and figure 4.0 but increases the wall shear stress in figure 5.0.

From figure 6.0, an increase in magnetic field M causes a decrease in the blood velocity due to an increase in Lorentz force which inhibits blood flow. This further results to a decrease in the blood acceleration, wall shear stress and volumetric flow rate from figure 7.0 to figure 9.0.

From figure 10.0, an increase in slip causes a decrease in the blood velocity. This is as a result of the relative motion between the surfaces of the blood and the stenosis wall of the artery which inhibits the blood flow. This reduces the blood

acceleration and the volumetric flow rate in figure 11.0 and figure 13.0 but increases the wall shear stress in figure 12.0. From figure 14.0, the increase in the radius of stenosis increases the blood velocity. When the radius of the stenosis was reduced the blood velocity in the artery was reduced due to stenotic arterial blockage. Furthermore, an increase in the radius of stenosis causes an increase in the blood acceleration and volumetric flow rate in figure 15.0 and figure 17.0 but a decrease in the wall shear stress in figure 16.0.

Finally, from figure 18.0 to figure 20.0, increasing values of Schmidt number, chemical reaction and magnetic field reduces the concentration of the blood due to a reduction in the internal viscosity of the blood.

$Kr=0.5,1,1.5,2$

Figure 2.0 Graph for the velocity of Blood flow with increasing values of chemical reaction Kr

when $Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=300, \beta=300, k=0.1, \alpha=1, h=1, R=0.55, M=1.5, \xi=0.1, \omega=1, t=1.$

$Kr=0.5,1,1.5,2$

Figure 3.0 Graph for the Blood acceleration with increasing values of chemical reaction Kr when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=300, \beta=300, k=0.1, \alpha=1, h=1, R=0.55, M=1.5, \xi=0.1, \omega=1, t=1.$

$Kr=0.5,1,1.5,2$

Figure 4.0 Graph for the shear stress at the wall with increasing values of chemical reaction Kr when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=300, \beta=300, k=0.1, \alpha=1, h=1, R=0.55, M=1.5, \alpha=1, \xi=0.1, \omega=1, t=1.$

$Kr=0.5,1,1.5,2$

Figure 5.0 Graph for the Volumetric Flow rate with increasing values of chemical reaction Kr when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=30^\circ, \beta=30^\circ, k=0.1, \alpha=1, h=1, R=0.55, M=1.5, \xi=0.1, \omega=1, t=1.$

$M=0.75,1,1.25,1.5$

Figure 6.0 Blood flow velocity distribution for increase in the Magnetic field M when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=45^\circ, \beta=30^\circ, k=0.1, \alpha=1, h=1, R=0.55, \xi=0.1, \omega=1, t=1.$

$M=0.75,1,1.25,1.5$

Figure 7.0 Blood acceleration profile for increase in the Magnetic field M when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \beta=30^\circ, k=0.1, \alpha=1, h=1, R=0.55, \xi=0.1, \omega=1, t=1.$

$M=0.75,1,1.25,1.5,$

Figure 8.0 Wall shear stress profile for increase in the Magnetic field M when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=45^\circ, \beta=30^\circ, k=0.1, \alpha=1, h=1, R=0.55, \alpha=1, \xi=0.1, \omega=1, t=1.$

$M=0.75,1,1.25,1.5$

Figure 9.0 Volumetric flow rate profile for increase in the Magnetic field M when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=45^\circ, \beta=30^\circ, k=0.1, \alpha=1, h=1, R=0.55, a=1, \xi=0.1, \omega=1, t=1.$
 $h=0.5,1,1.5,2$

Figure 10.0 Blood flow velocity distribution for increase in the Slip h when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=45^\circ, \beta=30^\circ, k=0.1, \alpha=1, R=0.55, M=1.5, \xi=0.1, \omega=1, t=1.$
 $h=0.5,1,1.5,2$

Figure 11.0 Blood acceleration profile for increase in the Slip h when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \beta=30^\circ, k=0.1, \alpha=1, R=0.55, M=1.5, \xi=0.1, \omega=1, t=1.$
 $h=0.5,1,1.5,2$

Figure 12.0 Wall shear stress profile for increase in the Slip h when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=45^\circ, \beta=30^\circ, k=0.1, \alpha=1, R=0.55, M=1.5, a=1, \xi=0.1, \omega=1, t=1.$

$h=0.5,1,1.5,2$

Figure 13.0 Volumetric flow rate profile for increase in the Slip h when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=45^\circ, \beta=30^\circ, k=0.1, \alpha=1, R=0.55, M=1.5, a=1, \xi=0.1, \omega=1, t=1.$
 $R=0.2,0.3,0.5,0.7$

Figure 14.0 Graph for the velocity of Blood flow with increasing values of Radius of stenosis R when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, Fr=0.05, b=2, \phi=30^\circ, \beta=30^\circ, k=0.1, \alpha=1, h=1, M=1.5, \xi=0.1, \omega=1, t=1.$
 $R=0.2,0.3,0.5,0.7$

Figure 15.0 Graph for the Blood acceleration with increasing values of Radius of stenosis R when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \beta=30^\circ, k=0.1, \alpha=1, h=1, M=1.5, \xi=0.1, \omega=1, t=1.$
 $R=0.2,0.3,0.5,0.7$

Figure 16.0 Graph for the shear stress at the wall with increasing values of Radius of stenosis R when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=30^\circ, \beta=30^\circ, k=0.1, \alpha=1, h=1, M=1.5, a=1, \xi=0.1, \omega=1, t=1.$

$R=0.2,0.3,0.5,0.7$

Figure 17.0 Graph for the Volumetric Flow rate with increasing values of Radius of stenosis R when

$Gc=2, Kr=0.5, Sc=1, Ps=2, Pp=4, Gb=3, Fr=0.05, b=2, \phi=30^\circ, \beta=30^\circ, k=0.1, \alpha=1, h=1, M=1.5, a=1, \xi=0.1, \omega=1, t=1.$

$Sc=1.5,2,3,4$

Figure 18.0 Graph for the Concentration with increasing values of Schmidt Number Sc when

$Kr=0.5, Sc=1, a=1, M=1.5, \xi=0.1, \omega=1, t=1.$

$Kr=0.5,1,1.5,2.0$

Figure 19.0 Graph for the Concentration with increasing values of Chemical Reaction Kr when

$Sc=1, a=2, M=1.5, b=1, \xi=0.1, \omega=1, t=1.$

$M=1,1.5,2,2.5$

Figure 20.0 Graph for the Concentration with increasing values of Magnetic Field M when

$Kr=0.5, Sc=1, M=1.5, a=1, \xi=0.1, \omega=1, t=1.$

7.0 Conclusion

This study shows the theoretical analysis of treatment effect which include chemical reaction, slip and magnetic field on MHD blood flow through a stenotic artery. The result summary from the theoretical study showed that,

(i) The increase in the Chemical reaction increases the blood viscosity whereby decreasing the blood velocity, acceleration and shear stress at the wall but increases the volumetric flow rate of the blood.

(ii) Increased magnetic field M causes a decrease in blood velocity, acceleration, shear stress at the wall and volumetric flow rate. Health practitioners could adopt this in treatment of patients with hypertension where the flow of blood to the body muscles from the heart is reduced.

(iii) Increased slip h at the wall with stenosis decreases the blood velocity, acceleration and

volumetric flow rate but causes an increase in the wall shear stress. This could treat tumor growth when the slip is introduced at the stenotic wall causing a starvation in blood supply to the stenotic growth at the artery wall. This cleanses the arteries, heart valves and cavities causing the increase of blood velocity, acceleration and volumetric flow rate but a decrease in the shear stress at the wall.

(iv) Increased radius of stenosis R at the wall with increases the blood velocity, acceleration and volumetric flow rate but causes a decrease in the wall shear stress. This could treat tumor growth and hypertension. This cleanses the arteries, heart valves and cavities hence improving the blood circulation.

(v) Increase in the values of Schmidt number, chemical reaction and magnetic field reduces the concentration of the blood due to a reduction in the internal viscosity of the blood.

References

- [1] Rabby, M. G., Razzak, A. and Molla, M. M. (2013). Pulsatile non-Newtonian blood flow through a model of arterial stenosis. *Procedia Engineering*, volume 56, number 5, page 225-231.
- [2] Ellahi, R., Rahman, S. U. and Nadeen, S. (2014). Blood flow of Jeffery fluid in a catherized tapered artery with the suspension of nanoparticles. *Physics Letters A*, volume 378, number 40, page 2973-2980.
- [3] Pralhad, R. N. and Schultz, D. H. (2004). Modelling of arterial stenosis and its application to blood disease, *mathematical Biosciences*, volume 190, number 2, page 203 – 220.

- [4] Ellahi, R., Rahman, S. U., Gulzar, M. M., Nadeem, S. and Vafai, K. (2014). A mathematical study of non-Newtonian micro-polar fluid in arterial blood flow through composite stenosis. *Applied Mathematics and Information Science*, volume 8, number 4, page 1567-1573.
- [5] Haik, Y., Pai, V. and Chen, C. J. [1999]. Development of magnetic device for cell separation. *Physics of fluids* [1994-present], vol.17, No.7, 077103-077118.
- [6] Abdullah, I., Amin, N. & Hayat, T. (2010). Magneto-hydrodynamic effects on blood flow through an irregular stenosis. *International Journal*

for numerical method in fluids, 67, 1624-1636, DOI:10.1002/flid.2436.

- [7] Prakash, O., Singh, S. P., Devendara, K. & Dwivedi, Y. K. (2011). A Study of the Effects of Heat Source on MHD Blood Flow through Bifurcated Arteries. *AIP Advances I*, 042128.
- [8] Srivastava, N. (2014). Analysis of Flow Characteristics of the Blood Flowing through an Inclined Tapered Porous Artery with Mild Stenosis under the Influence of an Inclined Magnetic Field. *Journal of Biophysics*, doi.org/10.1155/2014/797142.
- [9] Eldesoky, M. I. (2012). Mathematical Analysis of Unsteady MHD Blood Flow through Parallel Plate Channel with Heat Source. *World Journal of Mechanics*, 2, 131, 131 – 137.
- [10] Saddiqui, S. U., Shah, S. R. and Geeta (2014). Effect of body acceleration and slip velocity on the pulsatile flow through a casson fluid through stenosed artery, *Adv. Appl. Sci. Res.* Vol. 5, No. 3, pp. 213-225.
- [11] Sinha, A., Shit, G. C. & Kundu, P. K. (2013). Slip Effect on Pulsatile Flow of Blood through a Stenosed Arterial Segment under Periodic Body Acceleration. *ISRN Biomedical Engineering*, doi.org/10.1155/2013/925876.
- [12] Sinha, A., Misra, J. C. & Shit, G. C. (2016). Effect of heat transfer on unsteady MHD flow of blood in a permeable vessel in the presence of non-uniform heat source. *Alexandria Engineering Journal* 55, 2023-2033, www.sciencedirect.com
- [13] Tripathi, B. & Sharma, B. K. (2018). Effect of haet transfer on MHD blood flow through an inclined stenosed porous artery with variable viscosity and heat source. *Romanian Journal of Biophysics*, 28(3), 89 – 102.
- [14] Karthikeyan, D. & Jeevitha, G. (2019). Heat and Mass Transfer on MHD Two Phase Blood Flow through a Stenosed Artery with Permeable Wall. *International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, 8(7), ISSN: 2278-3075.
- [15] Abubakar, J. U. & Adeoye, A. D. (2020). Effects of Radiative Heat and Magnetic Field on Blood Flow in an Inclined Tapered Stenosed Porous Artery. *Journal of Taibah University for Science*, 14:1, 77 – 86, DOI: 10.1080/16583655, 2019, 1701397.
- [16] Amos, E. & Ogulu, A. (2003). Magnetic Effect on Pulsatile Flow in a Constricted Axis-symmetric Tube. *Indian Journal Pure and Applied Mathematics*, 34 (9): 1315-1326, September.
- [17] Bunonyo, W. K. & Amos, E. (2020). Blood flow through an inclined arterial channel with magnetic field. *Mathematical Modelling and Application*, 5(3), 129 – 137.
- [18] Omamoke, E. & Amos, E. (2022). Slip and Pulsatory MHD Blood Flow through an Inclined Stenosed Artery with Body Acceleration and Heat Source Effect. *IOSR Journal of Mathematics* 18(1) 1-23.
- [19] Amos, E., Omamoke, E. & Chinedu, N. (2022). Chemical Reaction, Heat Source and Slip Effects on MHD Pulsatory Blood Flow Past an Inclined Stenosed Artery Influenced by Body Acceleration. *International Journal of Mathematics Trends and Technology*, 68(1) 1-23.

- [20] Amos, E., Omamoke, E. & Chinedu, N. (2022). MHD Pulsatile Blood Flow through an Inclined Stenosed Artery with Body Acceleration and Slip Effects. *International Journal of Theoretical and Applied Mathematics*, 8(1), 1-3.
- [21] Omamoke, E., Amos, E. & Jatari, E. (2020). Impact of Thermal Radiation and Heat Source on MHD Blood Flow with an Inclined Magnetic Field in Treating Tumor and Low Blood Pressure. *Asian Research Journal of Mathematics*, 16(9) 77-78.
- [22] Chinedu, N. & Amadi, I. U. (2021). Analytical Solutions of a Non-isothermal flow in Cylindrical Geometry. *Asian Research Journal of Mathematics*, 17(3), 55-76.
- [23] Eldesoky, M. I. (2012). Slip Effects on Unsteady MHD Pulsatile Blood Flow through Porous Medium in an Artery under the Effect of

Body Acceleration. *International Journal of Mathematics and Mathematical Sciences*, Volume 2012, ID 860239, doi:10.1155/2012/860239.

[24] Kumar, A., Chandel, R. S., Shrivastava, R., Shrivastava, K. & Kumar, S. (2016). Mathematical Modelling of blood flow in an inclined tapered artery under MHD effect through porous medium. *International Journal of Pure and Applied Mathematical Science*, 9(1), 75 – 88, ISSN 0972 – 9828, www.ripublication.com.

[25] Nadeem, S., Noreen, S. A., Hayat, T. & Awatif, A. H. (2012). Influence of Heat and Mass Transfer on Newtonian Bio magnetic Fluid of Blood Flow through a Tapered Porous Artery with Stenosis. *Transport in Porous Medium*, 91(1):81-100.

APPENDIX

$$P_4 = GcA_2\alpha_4\gamma_22426282; P_3 = 1\gamma(64P_4 - GcA_2\alpha_3224262);$$

$$P_2 = 1\gamma(36P_3 + GcA_2\alpha_22242); P_1 = 1\gamma(16P_2 - GcA_2\alpha_22);$$

$$P_0 = 1\gamma(4P_1 + L + GcA_2);$$

$$Q_4 = GcA_1Kr_8\beta_22426282; Q_3 = 1\beta(64Q_4 - GcA_1Kr_6224262); Q_2 = 1\beta(36Q_3 + GcA_1Kr_42242);$$

$$Q_1 = 1\beta(16Q_2 - GcA_1Kr_222); Q_0 = 1\beta(4Q_1 + G + GcA_1)$$