

# IMPACT OF LAND CAPABILITY CLASSES AND LAND USE ON PROPERTIES AND ERODIBILITY BEHAVIOUR OF SOIL OF GHATAMPUR WATERSHED

## Abstract

The study was carried out in Ghatampur Watershed district Kanpur under National Watershed Development Project Area . The soils of Ghatampur watershed region are erodible in nature. Soil erodibility increased from land use capability class II to VI in the project area . Fallow land is most erodible followed by Rangeland, woodlots, cultivated land while orchard & grooves lands are least erodible on the basis of water stable aggregates, dispersion and erosion ratio as principal indices of erodibility, soil under various land use capability classes may be arranged in the order of class VI > class V > class III > class II . The erodibility of soil under different present land use was found in the order Fallow land > Rangeland > Wood lots > Cultivated land > Orchard & grooves land, Erosion ratio was significantly and negatively correlated with clay ( $r = -0.920^{***}$ ) moisture equivalent ( $r = -0.669$ ) , water holding capacity ( $r = -0.685^{**}$ ), water stable aggregate ( $r = -0.834^{***}$ ) , organic carbon ( $r = -0.780^{***}$ ) and clay/moisture equivalent ratio ( $r = -0.660^{***}$ ) but a positive correlation was recorded with sand ( $r = 0.777^{***}$ ), Bulk density ( $r = 0.709^{**}$ ), easily dispersible silt+clay ( $r = 0.888^{***}$ ) , clay ratio ( $r = 0.745^{***}$ ), dispersion ratio ( $r = 0.908^{***}$ ), Erosion index ( $r = 0.432^{**}$ ), the correlation between erosion ratio and silt ( $r = -0.432^{**}$ ) was recorded to be negative but significant. Among various land use capability classes, soil erodibility decreased substantially with increasing clay content but increased with increasing advancing capability class and fallow land use. Soil of Ghatampur watershed area is erodible in nature and requires warrant and prompt attention for implementing intensive soil conservation measures in the entire watershed in order to subside the havoc of soil erosion within safe limits because adapted soil conservation measures are variably effective to control the erosion.

**Key words :** Erodibility indices, Aggregation indices, PH, E.C, Correlation indices, Land Use Capability Classes

## Introduction

Soil and water are most essential finite resources which need to be conserved . Being exhaustible , they are liable to be short of demand if used improperly . Without soil there would be short of demand if used improperly . Without soil there would be no plants , without plants there would be no food and without food no living being would survive . Thus soil is the very beginning of the soil plant-animal food chain. The susceptibility of soil to erosion is known

as soil erodibility is apparently is due to the differences in there physical and chemical properties. It is dependant on soil properties ,vegetation, climate, topography besides, human factors influencing the present land use. The present land use alters the soil properties making it either resistant or susceptible to soil erosion. Soil erodibility is the vulnerability or inherent susceptibility of the soil to erosion and is a function of soil properties ; vegetation , climate, and topography , besides present land use and their management. The study was conducted with the following objectives : (i) To study the pattern of physical, properties erodibility indices of soils of Ghatampur watershed , and (ii) The erodibility indices and aggregation indices in relation to various soil properties.

The Ghatampur watershed is situated in Kanpur Nagar central part of uttar Pradesh . The watershed lies between  $26^{\circ} 30'$  N to  $27^{\circ}$  N latitude and  $79^{\circ} 30'$  to  $80^{\circ}$  E longitude with mean sea level of the villages : Samuhi , Aswarmau, Lahurimau , Bagariya , Sindhol, Sirsa, Bandh , Anupur and Rampur of Ghatampur Block of district Kanpur Nagar . The study was conducted to accomplish the physical properties as well as erodibility of soils of Ghatampur watershed. The geographical area of watershed was 5084 ha and area not available for cultivation was 84 ha . The project area suffers from the threat of heavy sheet and rill erosion through small to medium size gullies are also being formed. The whole watershed area lies in the catchment of the Jawahar nala of river Yamuna . Area under land capability classes (LCC) varies from class II to VI and whole area was treated with different soil and water conservation measures like : Land leveling, contour bunding, field bunding , field bunding+ vegetative barrier , contour farming , filter strip, gully plugging, sunken structure, agroforestry & rainfed horticulture etc.

### **Materials and Methods**

The present investigation entitled “ Impact of land capability classes and land use on properties and erodibility behavior of soil of Ghatampur watershed in district Kanpur under National watershed Development Project for Rainfed Area. The district Kanpur is located in the central part of the state lies in lower part of Ganga Yamuna doab. Watershed lies between  $26^{\circ} 30'$  N to  $27^{\circ} 30'$  E longitude with mean sea level of 120.9 km around the village : Samuhi, Aswarmau, Lahurimau, Bagariya, Sindhaul,sirsa, bandh, Anupur and Rampur of ghatampur Block of distict Kanpur . It comprises of districts of Hamirpur, fatehpur and Banda . the soil of this track are entirely different from those of the remaining part of the state.

Sixty soil sample, thirty each from disturbed and undisturbed state among different land use and capability classes from surface (0-15 cm ) and sub surface ( 15-30 cm) were collected from the project area. The mechanical analysis of air dried sample was carried out International Pipette method ( Pipper, 1950 ), bulk density as outline in U.S.D.A. Hand book

sixteen ,water stable aggregate more ( > 0.25mm) were determined by following modified wet sieving techniques of Yodder (1936), suspension percentage was determined to Middelton (1930), suction method by pipper (1950). Soil properties viz. PH, E.C., organic carbon and water holding capacity were determined by using standard method analysis Pipper (1950), suspension percentage and dispersion ratio, clay and colloid/ moisture equivalent were compared as suggested by Middelton (1930) substituting colloids with clay in colloid/ moisture equivalent ratio. Erosion index was calculated by dividing the dispersion ratio by clay/ water holding capacity while erosion ratio is obtained by dividing by clay moisture equivalent.

### **Result and Discussion**

The result of some important physical properties of the soil have been presented in ( Table-1) sand fraction was found to be more in class V land which may be because of washing away of finer particles in much greater proportion the coarse soil particles in these eroded soil. Wilson and Schubert (1949) have also reported that the finer soil particles were washed in a much greater proportion than coarse soil particles during water erosion . Present land use sand fraction was found lowest in orchard & grooves land and there was more clay fraction of in the soil. Orchards provide sufficient amount of canopy to the soil which reduce the runoff and beating action of rain drops leading to reduced power of raindrops, detach soil particles and thus minimizing the loss of finer fractions. The water holding capacity, moisture equivalent, water stable aggregates ( >0.25mm) was highest recorded in class II land and lowest in class VI land as in compare to under capability class following order II > III > IV >V >VI . These values are highest in nearly level and decreased with increasing slope, and degree of erosion and finer fraction of organic matter various land use capability classes. The present land use fallow land and range land were found to be more erodible by these under orchard & grooves land wood lots and cultivated lands . These results are conformity with findings of Talukdar and Das (1981), Bhatia and Vardani ( 1982 ), Kumar et al (2000)and Munendra et al (2014)

### **Physico- chemical and chemical properties**

The project one was presented by under land use capability class II , III and orchard & grooves land having lowest PH, E.C., B.D. and easily dispersible ( silt+ clay %) in comparison to

land use capability classes IV, V, VI and present land use classes as cultivated land, wood lots, range land and fallow land (Table 1a,b and 2a, b ).

### **Erodibility indices**

Erosion indices with clay ratio, dispersion ratio, erosion ratio and erosion index of soils of Ghatampur watershed and values of correlation coefficient of erosion ratio with soil properties have been depicted in (Table 1a, b ). The higher value of clay ratio, dispersion ratio, erosion ratio, erosion index wear observed recorded in class VI, and lower value of class II land . According to criteria of Middleton (1930), soil having dispersion ratio and erosion greater than 15 and 10, respectively are erosive in nature and thus, all the land use capability classes of the Ghatampur watershed are erodible. Similar findings also observed by Bhatia and Vardani (1982),Kumar et al (2000), kumar et al (2004) and Munendra et al (2014 ),Based on various erodibility indices,various land use capability class may be ranked in order of erodibility.

Class VI > V > IV > III > II

Similarly, among various present land uses adopted in the project area of Ghatampur watershed erodibility varied in the order

Fallow land > Range land > Wood lots > Cultivated land > Orchard & grooves land

### **Conclusion**

It is concluded that the soils of Ghatampur watershed region are erodible in nature. Soil erodibility increased under land use capability class II to VI in the project area. However, fallow land is most erodible ( ER = 62.14%) followed by rangeland (ER = 56.06%) ,woodlots ( ER= 37.52% ), cultivated land ( ER= 34.35 %) while orchard & grooves land are least erodible ( ER= 17.22%). Dispersion ratio and erosion index values substantiate foresaid results. Warrant prompt attention for taking simple to intensive soil conservation measures in the entire watershed in order to keep down the havoc of soil erosion within safe limit

### **References**

Agnihotri R.C, Yadav and Promod Jha . Erodibility characteristics of entisol soils of the Yamuna river in Agra .*J. Indian J. Soil Cons.*2007; 35 (3): 226-229.

Bhatia K.S, and Vardani. Physico-chemical and erosional behavior of red and black soil in Bundelkhand region of Uttar Pradesh. *Journal of the Indian Society of Soil Science* .1982; 30 (4) : 523-527

Kumar kaushal, Tripathi S.K and Bhatia K.S. Water stable aggregates in relation to physio-chemical properties of soil of Rendhar watershed Bundelkhand region.*Indian Journal of Soil Conservation*.2000; 28(3) : 216-220

Kumar K, Gangwar M and Chaudhary H.P. Effect of land use capability class and present land use on erosional behavior of Rendhar watershed Bundelkhand of U.P. *International Journal of Ecology and Environmental Science* .2004; 30 (3): 317-323

Middleton H.E. Properties of soil which influence soil erosion. *Tech. Bull. U.S.D.A.* 1930;178: 1-16

Pal M, Kumar K and Gangwar M.(2014). Impact of land use capability classes and present land use on soils properties and erodibility behavior of sheetalpur watershed in district Hamirpur of Bundelkhand region (U.P.) India. *Plant Archives*.2014; 14(1): 241-248

Piper C.S. Soil and Plant Analysis. Academic Press ; 1950 .

Talukdar M.C and Das S.K. Studies on the physic-chemical properties in relation to their erodibility under shifting cultivation in N.C. Hills of Assam. *Journal of Indian Society of soil Science* .1981; 63-69

Yoder R.E. A direct method of Aggregate analysis of soil and study of physical nature of erosion losses. *Journal American Society of Agronomy* 1936; (9) 337-351

Table-1 a Pattern of Physical properties and erosion indices of the soils of Ghatampur Watershed

Sl.No.	Land capability unit	Particle size distribution			Easily dispersible silt+clay %	Moisture equivalent %	Water holding capability	Water stable Aggregates (>0.25 mm)	Clay ratio	Clay/moisture equivalent ratio	D.R %	E.R %	Erosion index
		Sand % (0.05 - 0.002 mm)	Silt % (0.05 - 0.002 mm)	Clay % (< 0.002 mm)									
<b>Land use capability classes</b>													
1	II Wl	20.9	40.3	38.8	15.30	30.34	52.54	36.45	2.03	1.27	19.34	15.23	13.16
2		20.0	40.6	40.4	17.46	28.95	43.85	34.15	2.00	1.39	21.56	15.51	11.17
3		18.1	33.5	48.4	14.67	33.19	57.36	41.75	1.69	1.45	17.91	12.26	10.66
<b>Mean</b>		<b>19.3</b>	<b>38.1</b>	<b>42.5</b>	<b>15.81</b>	<b>30.82</b>	<b>51.25</b>	<b>37.45</b>	<b>1.89</b>	<b>1.37</b>	<b>19.61</b>	<b>14.21</b>	<b>11.88</b>
4	III el	31.8	40.4	27.8	27.60	18.20	38.80	21.40	2.45	1.52	40.46	26.62	28.29
5		24.2	36.3	39.5	21.58	25.23	47.13	33.10	1.91	1.56	28.46	18.24	16.94
6		19.1	38.6	42.3	23.73	22.46	44.85	31.45	1.92	1.87	29.33	15.60	15.60
<b>Mean</b>		<b>25.0</b>	<b>38.4</b>	<b>35.5</b>	<b>24.30</b>	<b>21.96</b>	<b>43.59</b>	<b>28.65</b>	<b>2.08</b>	<b>1.61</b>	<b>32.79</b>	<b>20.24</b>	<b>20.24</b>
7	V ewl	34.7	44.0	21.3	33.72	21.45	42.07	26.76	3.06	0.99	51.63	52.15	51.12
8		28.5	47.5	24.0	40.74	23.85	42.15	23.89	2.97	1.01	56.97	56.97	50.42
9		24.2	43.6	32.4	28.96	24.40	44.97	29.55	2.34	1.34	38.10	28.43	26.45
<b>Mean</b>		<b>29.1</b>	<b>45.0</b>	<b>25.9</b>	<b>34.47</b>	<b>23.13</b>	<b>43.06</b>	<b>26.73</b>	<b>2.73</b>	<b>1.12</b>	<b>48.62</b>	<b>43.80</b>	<b>40.52</b>
10	V el	28.7	35.1	16.2	38.76	13.40	30.60	15.81	3.16	1.21	75.55	62.96	71.27
11		36.3	35.5	28.5	26.35	20.04	38.45	27.49	1.60	1.42	57.78	40.69	39.04
12		48.6	31.8	19.6	33.18	18.55	35.80	21.84	2.62	1.05	64.55	61.47	59.22

<b>Mean</b>		<b>45.5</b>	<b>34.1</b>	<b>21.4</b>	<b>32.76</b>	<b>17.33</b>	<b>34.95</b>	<b>21.71</b>	<b>2.59</b>	<b>1.23</b>	<b>59.03</b>	<b>47.99</b>	<b>48.38</b>
13	V1 es2	53.6	43.0	12.4	35.10	13.45	25.89	12.36	3.74	0.92	75.65	82.23	79.63
14		41.6	39.9	18.5	36.12	14.35	26.30	13.90	3.15	1.28	61.85	48.32	44.18
15		43.2	33.7	21.1	33.36	19.55	31.40	15.30	2.59	1.07	60.88	56.89	45.43
<b>Mean</b>		<b>46.1</b>	<b>35.8</b>	<b>17.3</b>	<b>34.86</b>	<b>15.78</b>	<b>27.86</b>	<b>13.85</b>	<b>3.06</b>	<b>1.09</b>	<b>65.65</b>	<b>60.22</b>	<b>52.94</b>

**Table-1 b**

Sl.No.	Land capability unit	Particle size distribution			Easily dispersible silt+clay %	Moisture equivalent %	Water holding capability	Water stable Aggregates (>0.25 mm)	Clay ratio	Clay/moisture equivalent ratio	D.R %	E.R %	Erosion index
		Sand % (0.05-0.002 mm)	Silt % (0.05-0.002 mm)	Clay % (< 0.002 mm)									
<b>Present Land Use</b>													
16	Fallow land	53.6	32.0	14.4	36.46	14.26	25.89	13.80	3.22	1.00	75.58	78.58	70.79
17		46.9	35.2	17.9	33.65	16.85	31.64	19.25	2.97	1.06	63.37	59.78	56.08
18		40.5	38.3	21.2	29.50	21.40	36.70	19.35	2.81	0.99	49.58	50.00	42.74
<b>Mean</b>		<b>47.0</b>	<b>35.1</b>	<b>17.8</b>	<b>33.20</b>	<b>17.50</b>	<b>31.41</b>	<b>17.46</b>	<b>2.97</b>	<b>1.02</b>	<b>62.76</b>	<b>62.14</b>	<b>54.99</b>
19	Range land	42.8	36.2	21.0	32.68	22.12	37.25	20.48	2.67	0.95	58.15	61.86	51.46
20		52.2	29.4	18.4	35.25	13.28	33.48	14.58	1.89	1.39	101.29	73.40	92.08
21		38.6	42.6	18.4	30.48	18.47	24.78	18.23	3.32	1.00	50.49	51.00	33.89
<b>Mean</b>		<b>44.5</b>	<b>36.0</b>	<b>19.2</b>	<b>32.80</b>	<b>17.95</b>	<b>31.83</b>	<b>17.76</b>	<b>2.88</b>	<b>1.07</b>	<b>59.42</b>	<b>56.06</b>	<b>49.52</b>
22	Wood Lots	36.6	32.7	30.7	36.26	15.25	23.58	19.62	2.07	2.01	57.19	28.45	21.10
7523		41.3	34.8	23.9	29.18	19.78	32.34	17.72	2.45	1.21	49.71	41.43	33.59
24		34.2	39.3	26.5	32.02	23.13	42.10	24.10	2.48	1.15	48.66	42.68	38.62
<b>Mean</b>		<b>37.4</b>	<b>35.6</b>	<b>27.0</b>	<b>32.48</b>	<b>19.38</b>	<b>32.67</b>	<b>20.48</b>	<b>2.32</b>	<b>1.39</b>	<b>51.88</b>	<b>37.32</b>	<b>31.44</b>
25	Cultivated land	40.3	34.8	24.9	34.16	13.76	29.80	21.20	2.40	1.81	57.22	31.79	34.26
26		37.3	36.2	28.5	31.25	26.10	33.60	23.30	2.34	1.09	46.78	42.92	27.52
27		33.1	36.2	30.6	28.46	18.92	36.20	25.78	2.19	1.62	42.54	26.42	25.17
<b>Mean</b>		<b>36.9</b>	<b>35.7</b>	<b>28.0</b>	<b>31.29</b>	<b>19.59</b>	<b>33.20</b>	<b>23.76</b>	<b>2.28</b>	<b>1.42</b>	<b>49.12</b>	<b>34.35</b>	<b>29.06</b>
28	Orchard & grooves land	18.1	32.5	48.4	14.67	35.19	51.36	41.75	1.17	1.38	18.13	13.23	9.64
29		24.2	39.6	36.2	16.80	25.65	48.20	33.70	2.09	1.41	22.16	15.72	14.77
30		29.2	38.1	32.7	25.10	20.53	38.70	26.45	2.17	1.27	35.45	22.30	20.98
<b>Mean</b>		<b>23.8</b>	<b>36.7</b>	<b>39.1</b>	<b>18.80</b>	<b>27.12</b>	<b>46.08</b>	<b>33.96</b>	<b>1.93</b>	<b>1.44</b>	<b>24.8</b>	<b>17.22</b>	<b>12.40</b>
Correlation of erosion ratio with soil properties and erosion indices													
		***	_*	_*	***	***	***	***	***	***	***	***	***
		0.777	0.432	0.920	0.808	-0.669	-0.685	-0.834	0.745	-0.660	0.908		0.946

## Pattern of Physico-chemical and chemical properties of the soils of Ghatampur watershed

Table-2(a)

Sl. No.	Land Capability Units	PH(1:2.5)	E.C.(1:2.5)	Organic Carbon%
<b>Land Use Capability Classes</b>				
1	II w I	7.39	0.31	0.53
2	II w I	8.10	0.47	0.41
3	II w I	7.31	0.51	0.61
<b>Mean</b>		<b>7.60</b>	<b>0.43</b>	<b>0.52</b>
4	III e I	8.17	0.33	0.37
5	III e I	7.90	0.30	0.38
6	III e I	8.06	0.42	0.45
<b>Mean</b>		<b>8.04</b>	<b>0.35</b>	<b>0.40</b>
7	IV e w I	8.65	0.51	0.26
8	IV e w I	8.21	0.46	0.29
9	IV e W I	8.45	0.49	0.32
<b>Mean</b>		<b>8.43</b>	<b>0.48</b>	<b>0.29</b>
10	V e I	8.70	0.23	0.29
11	V e I	8.55	0.54	0.30
12	V e I	8.14	0.48	0.27
<b>Mean</b>		<b>8.46</b>	<b>0.42</b>	<b>0.29</b>
13	VI e s2	8.95	0.76	0.23
14	VI e s2	9.05	0.68	0.21
15	VI E s2	7.80	0.61	0.24
<b>Mean</b>		<b>8.60</b>	<b>0.68</b>	<b>0.23</b>

Table-2(b)

Sl. No.	Land Capability Units	PH(1:2.5)	E.C.(1:2.5)	Organic Carbon%
<b>Land Use Capability Classes</b>				
16	Fallow Land	9.1	0.65	0.19
17		8.7	0.54	0.23
18		8.5	0.43	0.26
<b>Mean</b>		<b>8.7</b>	<b>0.80</b>	<b>0.23</b>
19	Range Land	8.4	0.42	0.34
20		9.2	0.62	0.22
21		7.8	0.58	0.18
<b>Mean</b>		<b>8.4</b>	<b>0.54</b>	<b>0.24</b>
22	Wood Lots	7.9	0.38	0.20
23		8.8	0.43	0.39
24		8.2	0.39	0.36
<b>Mean</b>		<b>8.3</b>	<b>0.40</b>	<b>0.31</b>
25	Cultivated Land	8.3	0.41	0.35
26		8.5	0.39	0.38
27		7.8	0.36	0.41
<b>Mean</b>		<b>8.2</b>	<b>0.38</b>	<b>0.38</b>
28	Orchard & Grooves Land	7.6	0.31	0.68
29		7.9	0.38	0.54
30		8.1	0.43	0.49
<b>Mean</b>		<b>7.8</b>	<b>0.37</b>	<b>0.57</b>

**Table - 3( a ) Correlation between erosion ratio and soil properties**

<b>Sl. No.</b>	<b>Correlation between Soil properties X</b>	<b>Erosion ratio Y</b>	<b>Correlation coefficient</b>	<b>Regression equation</b>
1	Sand %	-do-	$r=0.777^{***}$	$Y= -13.796+1.481X$
2	Silt %	-do-	$r=-0.432^{**}$	$Y= 84.443- 1.169X$
3	Clay %	-do-	$r=-0.920^{***}$	$Y= 94.797-1.953 X$
4	Easily dispersible % Silt+clay	-do-	$r=0.808^{***}$	$Y= - 24.981+2.272 X$
5	Bulk density g/cc	-do-	$r=0.709^{***}$	$Y= - 154+141.579 X$
6	Moisture equivalent %	-do-	$r=0.669^{***}$	$Y= 91.611-2.394 X$
7	Water holding capacity	-do-	$r=-0.685^{***}$	$Y= 101.511-1.629 X$
8	Water stable aggregate (>0.25mm)	-do-	$r=-0.834^{***}$	$Y= 92.854-2.140 X$
9	PH	-do-	$r=0.698^{***}$	$Y= -197.605+28.884 X$
10	E.C ( dsm-1)	-do-	$r=0.591^{***}$	$Y= -5.117+100.336 X$
11	Organic carbon	-do-	$r=-0.780^{***}$	$Y= 85.105-127.665 X$
<b>Correlation between erosion ratio and erosion indices</b>				
	Clay ratio	-do-	$r=0.745^{***}$	$Y= 24.400+26.747 X$

1				
2	Clay/ moisture equivalent	-do-	$r=-0.660^{***}$	$Y= 103.386-48.93 X$
3	Dispersion ratio	-do-	$r=0.908^{***}$	$Y= -5.492+0.945 X$
4	Erosion index	-do-	$r=0.946^{***}$	$Y = 6.883 +0.909 X$

**Table – 3 (b) Correlation between water stable aggregates and soil properties**

SI. No.	Correlation between Soil properties	W.S.A (>0.25mm)	Correlation Coefficient	Regression equation
1	Sand %	-do-	$r =-0.718^{***}$	$Y = 43.750-0.534 X$
2	Silt %	-do-	$r=0.407^{**}$	$Y = 9.110+0.406 X$
3	Clay %	-do-	$r=0.933^{***}$	$Y = 2.960+ 0.772 X$
4	Easily dispersible Silt+ clay %	-do-	$r=0.870^{***}$	$Y = 51.948-0.955 X$
5	Bulk density g/cc	-do-	$r=0.796^{***}$	$Y= 109.709-62.005 X$
6	Moisture equivalent %	-do-	$r=0.890^{***}$	$Y = -2.017+1.242 X$
7	Water holding capacity %	-do-	$r=0.914^{***}$	$Y = -7.740+0.847 X$
8	PH	-do-	$r=-0.684^{***}$	$Y= 115.209-11.014 X$
9	E.C,(dsm-1)	-do-	$r=-0.489^{***}$	$Y= 39.079+32.335 X$
10	Organic carbon	-do-	$r=0.858^{***}$	$Y= 5.308+54.764 X$
<b>Correlation between water stable aggregates and erosion indices</b>				
1	Clay ratio	-do-	$r=-0.742^{***}$	$Y= 49.583-10.371 X$

2	Clay/ moisture equivalent	-do-	$r=0.363^{***}$	$Y= 10826+10.357 X$
3	Dispersion ratio	-do-	$r=-0.877^{***}$	$Y= 41.722-0.356 X$
4	Erosion ratio	-do-	$r=-0.791^{***}$	$Y= 35.336-0.296 X$

\*\*\* Significant at 0.1 %

\*\* Significant at 1 %

UNDER PEER REVIEW