

## Review Form 1.7

Journal Name:	<a href="#">Journal of Engineering Research and Reports</a>
Manuscript Number:	Ms_JERR_96716
Title of the Manuscript:	COMPARISON OF THE STRENGTH OF BLOCKS MADE FROM SHARP SAND CEMENT, LATERITE CEMENT AND RED EARTH CEMENT
Type of the Article	Original Research Article

### General guideline for Peer Review process:

This journal's peer review policy states that **NO** manuscript should be rejected only on the basis of '**lack of Novelty**', provided the manuscript is scientifically robust and technically sound. To know the complete guideline for Peer Review process, reviewers are requested to visit this link:

(<https://www.journaljerr.com/index.php/JERR/editorial-policy> )

### PART 1: Review Comments

	Reviewer's comment	Author's comment (if agreed with reviewer, correct the manuscript and highlight that part in the manuscript. It is mandatory that authors should write his/her feedback here)
<b>Compulsory</b> REVISION comments  <b>1. Is the manuscript important for scientific community?</b> (Please write few sentences on this manuscript)  <b>2. Is the title of the article suitable?</b> (If not please suggest an alternative title)  <b>3. Is the abstract of the article comprehensive?</b>  <b>4. Are subsections and structure of the manuscript appropriate?</b>  <b>5. Do you think the manuscript is scientifically correct?</b>  <b>6. Are the references sufficient and recent? If you have suggestion of additional references, please mention in the review form.</b> <b>(Apart from above mentioned 6 points, reviewers are free to provide additional suggestions/comments)</b>	Yes but need to re-conclude "On crushing the blocks, it was discovered that the compressive strength of all did not meet up to the minimum recommended standard of 3.45N/mm <sup>2</sup> for individual blocks as recommended by the Nigerian Industrial Standard (NIS 87: 2000). The overall average strength for the block made with cement and sharp sand (sand Crete) ranged from 4.83 N/mm <sup>2</sup> to 9.97 N/mm <sup>2</sup> , for those made with laterite it ranged from 3.27 N/mm <sup>2</sup> to 5.16 N/mm <sup>2</sup> while those made with red earth had compressive strength that ranged from 2.02 N/mm <sup>2</sup> to 3.16 N/mm <sup>2</sup> .  Yes  Yes  Yes  Yes	
<b>Minor</b> REVISION comments <b>1. Is language/English quality of the article suitable for scholarly communications?</b>		
<b>Optional/General</b> comments		

### PART 2:

	Reviewer's comment	Author's comment (if agreed with reviewer, correct the manuscript and highlight that part in the manuscript. It is mandatory that authors should write his/her feedback here)
<b>Are there ethical issues in this manuscript?</b>	<i>(If yes, Kindly please write down the ethical issues here in details)</i>	

### Reviewer Details:

Name:	Burachat Chatveera
Department, University & Country	Thammasat University, Thailand