

Application of SWAT in Hydrological Simulation of Rapti River Basin

ABSTRACT

Study Region: Rapti River Basin (RRB), Nepal and India

Study Focus: This study aimed at to calibrate and validate SWAT model for rapti river basin which originates from Nepal and then it comes in India. SWAT (Soil and Water Assessment Tool) is a comprehensive, semi-distributed river basin model that requires a large number of input parameters, which complicates model parameterization and calibration. The RRB was discretised into 4 sub-basins and 630 hydrological response units (HRUs) and calibration and validation was carried out at Bagasoti using monthly flow data of 11 years, respectively. We first calibrate the model in SWAT-CUP which is a decision-making framework that incorporates a semi-automated approach (SUFI2) using both automated and manual calibration and incorporating sensitivity and uncertainty analysis. Parameter sensitivity analysis helps focus the calibration and uncertainty analysis and is used to provide statistics for goodness-of-fit. In this paper Manual Calibration has been done between simulated and observed discharge data (1974-1985) for 50 simulations with 6 parameters i.e. Curve number (CN2 = 0.945), Groundwater delay (GW_DELAY = 50), Baseflow alpha factor (ALPHA_BF = 0.58), Manning's "n" value for the main channel (CH_N2 = 0.15), Effective hydraulic conductivity in main channel alluvium (CH_K2 = 10.20) and Available water capacity of the soil layer (SOL_AWC = 0.28) and the result were analysed with remaining observational data. The model performance evaluation also showed acceptable ranges of values (e.g., Nash Sutcliff was 0.75 and R2 was 0.71). After model calibration, in order to predict water balance, the model was validated by using this best parameter.

Keywords: Manual calibration, Hydrologic model, SWAT, Validation, Water balance.

1. INTRODUCTION

Understanding hydrological processes is crucial for managing water movement and its impact on quantity and quality. Basin-focused studies are vital for grasping the mechanisms regulating water flow and predicting their effects on water resources. This knowledge is essential for efficient planning and management, enabling the quantitative assessment of parameters like rainfall and river flow, considering their spatial and temporal variations in river basins [1] these processes are shaped by diverse factors such as weather, topography, geology, land use, and human activities. Water movement on land, both on the surface and beneath, affects unsaturated and saturated zones [2]. A rising surface runoff volume can lead to issues like sedimentation, erosion, and agricultural pollutants, posing significant threats to water resources. Hence, a precise understanding of hydrological behavior is crucial for effective planning and management.

Hydrological models are pivotal for comprehending and forecasting the impact of both natural and human-induced disturbances on water systems. These models integrate mathematical

representations of key components in the water cycle, such as rivers, lakes, groundwater, soil, and snow, facilitating the analysis of fluxes in elements like runoff, evapotranspiration, groundwater recharge, and soil moisture. These hydrological models are applicable across a range of scales, from local to global, with their complexity tailored to the specific design scale.

Physically based hydrological models are frequently used to estimate surface runoff, sediment yield, and nutrient losses in watersheds under different management scenarios. Within these models, simulation models replicate processes to explore various scenarios, while optimization models adjust parameters to meet specific objectives. However, a limitation exists in the capability of many water resource models to effectively analyze and display spatial information. A significant number of these models address spatial aspects by simplifying assumptions and parameterization, as highlighted by [3].

The Soil and Water Assessment Tools (SWAT) model, operating on a daily time step, is designed to predict the impact of management on runoff, sediment, and agricultural chemical yields in large ungauged basins. Over the last two decades, the versatility of the SWAT model has garnered attention for its ability to address a diverse range of watershed problems at desired spatial and temporal scales. Researchers have extensively examined the SWAT model's performance on daily, monthly, or annual bases in predicting runoff and sediment yield. Its simplicity and applicability have been emphasized in numerous studies conducted by researchers such as [4], [5], [6], [7], [8], [9],[10], [11], [12], [13], [14], [15], [16], [17],[18], [19], and [20].

This study aimed at to calibrate and validate SWAT model for rapti river basin which originates from Nepal and then it comes in India. The Rapti River, a significant left bank tributary of the Ghaghra River, originates south of a notable east-west ridgeline situated midway between the western Dhaulagiri Himalaya and the Mahabharat Range in Nepal, at an elevation of approximately 3048 meters. The Dundwa range, a subrange of the Shiwaliks in Western Nepal, diverts the Rapti about 100 kilometers westward before it resumes its southward course towards the Ganga. Upon traversing Nepal, the river enters Eastern Uttar Pradesh in Chanda Pargana, east of the Kundwa village in Bahraich district. The floodwaters of the Rapti River are regulated by the Rapti Barrage, located upstream of the Bhinga site in Shravasti district, and maintained by the State government. The Rapti River Basin is a part of the middle Ganga plain, receiving contributions from numerous tributaries and affluents that descend steeply into the Rapti from the Shiwalik and its foothills.

2. MATERIAL AND METHODS

2.1 The study area

2.1.1 Location of the study area

The Rapti Zone is situated between East longitudes 81°35' and 83°52' and North latitudes 26°18' and 28°35' in both Uttar Pradesh and Nepal, covering a total area of 23,237.51 square kilometers. With an elevation of 3,500 meters (11,500 feet), the zone includes the Ghaghara River (located at 26°17'20"N and 83°40'08"E) with a basin size of 23,900 square kilometers (9,200 square miles) and an average discharge of 136 cubic meters per second (4,800 cubic feet per second). The origin of the Rapti River

is in the Mahabharat range of the lesser Himalayas, near Rukumkot in Nepal. Starting at an elevation of 3,050 meters within Nepal's Mahabharat range, the Rapti River basin exhibits diverse physiography, encompassing lofty mountains, inner and outer Terai, and undulating plains. Originating as a small river draining the Chitwan (Inner Terai) valley in Nepal, the Rapti flows westward to converge with the Narayani (Gandaki) River to the north. The Rapti zone, situated in Nepal's Middle Hills between the Karnali and Gandaki Basins, continues its course westward through the Mahabharat range and then southeast across the Indo-Gangetic plains before joining the Sharda (Ghaghara) River. As a significant tributary, the Rapti River plays a vital role in the Ghaghara River system. The river experiences two distinct climatic regions based on altitude differences: the mountainous region has a temperate climate, while the plain region features a subtropical climate. The Himalayan climate is characterized by temperate conditions, with hot summers and cold winters. In the subtropical plain region, a typical monsoon climate prevails, marked by a dry winter season and extremely hot summer




Figure 1: Location of the study area

2.2 SWAT model Inputs

In addition to topographic, soil, and land use/land cover (LULC) information, SWAT necessitates spatially detailed datasets of climatic data at daily or sub-daily intervals. Key input data for SWAT encompass Digital Elevation Model (DEM), land use/land cover, soil properties, and daily weather data (encompassing precipitation, maximum and minimum air temperatures, relative humidity, wind speed, and solar radiation).

2.2.1 Digital Elevation Model (DEM)

The Digital Elevation Model (DEM) holds significance as it serves as a crucial dataset from which all topographic characteristics of the catchment, sub-catchment, and Hydrologic Response Units (HRUs) are derived. These attributes encompass area, slope, slope length, channel length, channel slope, channel width, and channel depth. In this investigation, a 30-meter spatial resolution DEM from the Shuttle Radar Topography Mission (SRTM) was obtained from the USGS website (link: https://lpdaac.usgs.gov/data_access/data_pool) and utilized as an input dataset.

2.2.2 Land use/land cover data (LULC)

The study area-specific, cloud-free digital LANDSAT data was obtained from the Global Land Cover Facility site. The land use/cover map for the study watershed was generated using satellite data captured during the autumn of 2000, 2010, and 2020, sourced from USGS Earth Explorer. The sensor associated with this data provided a spatial resolution of 10 meters. Various land use or cover types, including agricultural land, wetland, barren land, forest, water bodies, and habitat, were identified. Figure 3 illustrates the distribution of each land use type within each sub-watershed.

2.2.3 Soil type and characteristics

The soil map of the basin underwent a detailed process, starting with meticulous outlining, scanning, and subsequent uploading into ArcGIS. Map-to-map registration was conducted using registered topographic maps to ensure accuracy. To facilitate precise identification, individual soils were carefully delineated, and the corresponding polygons were filled with different colors to represent distinct soil types. Figure 4 visually depicts the spatial distribution of the various soil types within the designated areas.




Fig 2.DEM Map of Rapti River Basin




Fig 3: Land-use map of Rapti River Basin




Fig 4: Soil map of Rapti River Basin

2.2.4 Climatic data

The SWAT2012 model necessitates daily data for variables such as precipitation, temperature, relative humidity, solar energy, and wind speed. The SWAT software incorporates a weather generator tool, which proves helpful in filling in missing data during specific time periods within the simulation duration. Moreover, this tool allows the generation of relative humidity, solar energy, and wind speed, provided that a long-term daily precipitation rate and maximum and minimum temperatures are supplied.

2.3 Model setup and configuration

This study utilized the Soil and Water Assessment Tool (SWAT) model to estimate all components of the water balance within the study catchment. The initial step in the simulation process was the delineation of the catchment. The GIS interface of SWAT2012 was employed for this purpose, utilizing a 30-meter spatial resolution SRTM DEM (digital elevation model) downloaded from earth explorer, a data distribution center of USGS (accessible at the link: https://lpdaac.usgs.gov/data_access/data_pool). The procedural details can be found in [21] and [22]. Upon completion of the catchment delineation, the definition of Hydrologic Response Units (HRUs) ensued. The SWAT2012 interface was used for HRU definition, incorporating three essential spatial datasets: slope, land use/land cover, and soil maps. HRUs are essentially lands with similar characteristics in terms of topography, land use/land cover, and soil types. The assumption is that similar HRUs exhibit comparable hydrologic characteristics. This approach allows for the determination of all components of the soil water balance on an HRU basis, as outlined in studies by [21], [22] and [23]. Subsequently, the model was supplied with all the necessary climatic variables, including rainfall, minimum and maximum temperature, relative humidity, average wind speed, and solar radiation data. In cases where station data were unavailable, the weather generator tool within the ArcSWAT interface was utilized to fill in the gaps. This tool also allowed for the generation of relative humidity, solar energy, and wind speed based on long-term daily precipitation and maximum and minimum temperature data, as outlined by [21]. The rainfall-runoff process was configured to be estimated using the curve number (CN-method), potential evapotranspiration was determined using the Penman-Monteith equation, and channel water routing was simulated through the Variable Storage Routing method. Upon completion of these processes, the SWAT simulation was initiated, incorporating a three-year warming-up period. Including this warm-up period, the total simulation duration, spanning from 1974 to 1985, was established. Consequently, a 11 year period of hydrologic variables was simulated for the study catchment, excluding the warm-up periods. The key steps in the simulation process are summarized in Figure 5.




Fig 5: framework of swat model

2.4 Water balance equation used by the SWAT model

The SWAT model is a continuous, process-based, and spatially-distributed model specifically designed to replicate the water balance in a defined geographical area. It takes into account diverse hydrological processes such as rainfall; evapotranspiration, surface and subsurface runoff, and deep aquifer recharge [24], [25]. The model functions according to the water balance equation;

$$SW_t = SW + \sum_{t-1}^t (R - Q - ET - P - QR)$$

Where,

SW_t = final soil water content (mm),

SW = initial soil water content (mm),

t = time (days),

R = amount of precipitation (mm),

Q = amount of surface runoff (mm),

ET = amount of evapotranspiration (mm),

P = percolation (mm) and

QR = amount of return flow (mm).

2.5 SWAT-CUP Model

SWAT-CUP is a comprehensive tool that integrates a calibration and uncertainty program with the SWAT hydrological model, providing a range of algorithms including Sequential Uncertainty Fitting (SUFI-2), Particle Swarm Optimization (PSO), Generalized Likelihood Uncertainty Estimation (GLUE), and Markov Chain Monte Carlo (MCMC) [26], [27]. These algorithms empower users to conduct uncertainty and sensitivity analyses. The process of parameter optimization and calibration, involving an inverse problem, inherently introduces uncertainty as it begins with observed results and subsequently identifies parameter values responsible for producing those results.

In this research, the SUFI-2 [28], [29], [30], [31], [32] was utilized for the purposes of calibration, validation, and sensitivity analysis. SUFI-2 is recognized for its efficiency in handling large-scale, time-consuming models [33], [34], [35] and for accurately constraining most measured data within a narrow uncertainty band. The algorithm iteratively maps all uncertainties, ensuring that 95% of the measured data falls within the 95% prediction uncertainty (95PPU) of the model.

Two pivotal factors, namely the p-factor and r-factor, play a crucial role in assessing the results. The p-factor quantifies simulation uncertainty, while the r-factor gauges the strength of the calibration and uncertainty analyses. The r-factor is calculated as the average thickness of the 95PPU band divided by the standard deviation of the measured data. The goodness of fit is evaluated using the R² and Nash-Sutcliffe coefficient (NSE) between observed data and the best simulation, where an R-factor of 1 and P-factor of 100% indicate a perfect simulation. The P-factor ranges between 0 and 100%, while the R-factor ranges between 0 and infinity.

The first step involves identifying the most critical factors for the selected watershed, a decision that the user makes based on expertise or through the process of sensitivity analysis. Sensitivity analysis, which examines the influence of adjusting various variables on model output, can take the form of either local (changing parameters one at a time) or global (allowing changes in all parameters) analyses. Both types of analyses provide valuable insights.

Subsequently, the calibration process is undertaken to improve the model's fit to local conditions by selecting input parameter values within their uncertainty ranges and comparing the model output to observed data. During calibration, the goal is to fine-tune the model to achieve an optimal match with observed data.

Following calibration, the validation process assesses the model's performance for a specific output variable, such as streamflow or sediment yield, using the parameters determined during calibration. This evaluation involves comparing model predictions to unused observed data. Model validation ensures that the model produces accurate simulations aligned with the project goals [36], [37] and [38]

3. RESULT AND DISCUSSION

3.1 Model Calibration

The accuracy of a hydrological model hinges on the precision of its calibration process [39], [40] and [41]. In this study, auto-calibration using SWAT_CUP was performed for the Rapti river basin, specifically utilizing observed monthly runoff data measured at the outlet during the period 1985–1995. The initial four years of the modeling period, from 1981 to 1984, were allocated for model

'warm-up' to enable the model to establish the states of its internal hydrological components realistically.

The input parameters employed for model calibration included SCS curve number (CN2), Groundwater delay time (GW_DELAY), Baseflow recession constant (ALPHA_BF), Manning's "n" value for the main channel (CH_N2), Effective hydraulic conductivity in main channel alluvium (CH_K2) and Available water capacity of the soil layer (SOL_AWC).

The calibration values of NSE and R2 were 0.75 and 0.71, respectively, indicating a further enhancement in the model's predictive performance. The results suggest that the overall prediction of monthly surface runoff during the calibration period was very good, making it acceptable for further analysis. The model evaluation summary for both the calibration and validation periods is presented in Table 1

Table 1: Selected parameters for calibration

Parameter	SWAT range		Full Name	Values after Calibration
	Min	Max		
CN2	35	98	SCS runoff curve number	6% increase
GW_DELAY	0	500	Groundwater delay	50
ALPHA_BF	0	1	Base flow alpha factor	0.58
CH_N2	0.01	0.3	Manning's "n" value for the main channel	0.15
CH_K2	0.01	500	Effective hydraulic conductivity in main channel alluvium	10.20
SOL_AWC	0	1	Available water capacity of the soil layer	0.28

3.2 Model Validation

During the validation phase, the model was operated with the input parameters established during the calibration process, and no further adjustments were made. The results were then compared with the remaining observational data. Model validation utilized an independent dataset covering the period from 1996 to 2009, comprising observed discharge data from the gauging site. The findings illustrated that the model estimates closely aligned with the observed runoff. With an NSE value of 0.83 and an R2 value of 0.84, the validation level was deemed very well. These results indicate that the model was effectively validated for predicting monthly discharges. Consequently, the SWAT model demonstrates successful performance and can be reliably utilized for the Rapti river basin. Figure 6, 7 illustrates the best simulated discharge for the validation period.




Fig 6 Line graph for observed and calibrated discharge




Fig 7: Scatter graph for observed and calibrated discharge

4. SUMMARY AND CONCLUSION

Ensuring the accuracy of predictions, particularly in estimating variables like discharge, relies on a thorough calibration of a hydrological model.

- This study focused on calibrating and validating the Rapti River Basin using the SWAT model.
- The evaluation of the SWAT model's performance involved a meticulous calibration and validation process. The SUFI-2 technique, chosen for model calibration, proved to be highly convenient and iterative, involving a substantial number of simulations.

- The results obtained from the SWAT model were highly satisfactory, indicating a successful calibration process. Consequently, the calibrated parameter values derived from this study can be confidently used for subsequent hydrological simulations of the watershed.
- The study observed a high correlation between observed and simulated discharge on a monthly time scale, validating the accuracy of the SWAT model.
- The findings and conclusions drawn from this study are of significant value for hydrologists and water resource management professionals, offering valuable insights for the effective management and understanding of the Rapti River basin.

CONSENT

All authors declare that 'written informed consent was obtained from the patient (or other approved parties) for publication of this case report and accompanying images. A copy of the written consent is available for review by the Editorial office/Chief Editor/Editorial Board members of this journal.

REFERENCES

- [1] Arai, F.K., Pereira, S.B. and Gonçalves, G.G., 2012. Characterization of water availability in a hydrographic basin. *Engenharia agrícola*, 32, pp.591-601.
- [2] Singh, V.P. and Frevert, D.K., 2006. Watershed models. In *Environmental and Water Resources History* (pp. 156-167).
- [3] Walsh, M.R., 1993. Toward spatial decision support systems in water resources. *Journal of Water Resources Planning and Management*, 119(2), pp.158-169.
- [4] Srinivasan, R., Arnold, J. G., Rosenthal, W. and Muttiah, R. S. (1993). Hydrologic modeling of Texas Gulf Basin using GIS, In: *Proceedings of 2nd International GIS and Environmental Modeling*, Breckinridge, Colorado, pp.213-217.
- [5] Srinivasan, R., Ramanarayanan, T.S., Arnold, J.G. and Bednarz, S.T., 1998. Large area hydrologic modeling and assessment part II: model application 1. *JAWRA Journal of the American Water Resources Association*, 34(1), pp.91-101.
- [6] Srinivasan, R. and Arnold, J.G., 1994. INTEGRATION OF A BASIN-SCALE WATER QUALITY MODEL WITH GIS 1. *JAWRA Journal of the American Water Resources Association*, 30(3), pp.453-462.
- [7] Cho, S. M., Jennings, G. D., Stallings, C. and Devine, H. A. (1995). GIS-based water quality model calibration in the Delaware river basin, *Transactions of American Society of Agricultural Engineering*, Microfiche No. 952404, ASAE, St. Joseph, Michigan.
- [8] Rosenthal, W.D., Srinivasan, R. and Arnold, J.G. (1995). Alternative river management using a linked GIS- hydrology model, *Transactions of the American Society of Agricultural Engineering*, 38(3): 783-790.

- [9] Bingner, R. L., Garbrecht, J., Arnold, J. G. and Srinivasan, R. (1997). Effect of watershed division on simulation of runoff and fine sediment yield, *Transactions of American Society of Agricultural Engineering*, 40(5): 1329-1335.
- [10] Peterson, J. R. and Hamlett, J. M. (1998). Hydrological calibration of the SWAT model in a watershed containing fragipan soils, *J. American Water Resources Association*, 34(3): 531-544.
- [11] Arnold, J.G., Srinivasan, R., Ramanarayanan, T.S. and Diluzio, M. (1999). Water resources of the Texas gulf basin, *Water Science and Technology*, 39(3):121-133.
- [12] Chaplot, V. (2005). Impact of DEM mesh size and soil map scale on SWAT runoff, sediment, and NO₃-N loads predictions, *J. Hydrology*, 312:207–222.
- [13] Setegn, S.G., Srinivasan R. and Dargahi B. (2008). Hydrological modeling in lake Tana Basin, Ethiopia, using SWAT model, *The Open Hydrology Journal*, 2, 49-62.
- [14] Neitsch, S.L., Arnold, J.G., Kiniry, J.R. and Williams, J.R., 2009. Soil and water assessment tool theoretical documentation version 2009. 2011. Texas Water Resources Institute.
- [15] Srinivasan, R., Zhang, X. and Arnold, J. (2010). SWAT unguaged: Hydrological budget and crop yield prediction in the upper Mississippi river basin, *American Society of Agricultural and Biological Engineers*, 53 (5): 1533-1546.
- [16] Betrie, G. D., Mohamed, Y.A., Van, G. A. and Srinivasan, R. (2011). Sediment management modeling in the Blue Nile basin using SWAT model, *Hydrology and Earth System Sciences*, 15:807-818.
- [17] Qiu, L.J., Zheng, F.L. and Yin, R.S., 2012. SWAT-based runoff and sediment simulation in a small watershed, the loessial hilly-gullied region of China: capabilities and challenges. *International Journal of Sediment Research*, 27(2), pp.226-234.
- [18] Himanshu, S.K., Pandey, A. and Shrestha, P., 2017. Application of SWAT in an Indian river basin for modeling runoff, sediment and water balance. *Environmental Earth Sciences*, 76, pp.1-18.
- [19] Chilagane, N.A., Kashaigili, J.J., Mutayoba, E., Lyimo, P., Munishi, P., Tam, C. and Burgess, N., 2021. Impact of land use and land cover changes on surface runoff and sediment yield in the Little Ruaha River Catchment. *Open Journal of Modern Hydrology*, 11(3), pp.54-74.
- [20] Zeiger, S. J., Owen, M. R., & Pavlowsky, R. T. (2021). Simulating nonpoint source pollutant loading in a karst basin: A SWAT modeling application. *Science of the Total Environment*, 785, 147295.
- [21] Neitsch, S.L., Arnold, J.G., Kiniry, J.R. and Williams, J.R., 2011. *Soil and water assessment tool theoretical documentation version 2009*. Texas Water Resources Institute.
- [22] Arnold, J.G., Moriasi, D.N., Gassman, P.W., Abbaspour, K.C., White, M.J., Srinivasan, R., Santhi, C., Harmel, R.D., Van Griensven, A., Van Liew, M.W. and Kannan, N., 2012. SWAT: Model use, calibration, and validation. *Transactions of the ASABE*, 55(4), pp.1491-1508.
- [23] Winchell, M.F., Peranginangin, N., Srinivasan, R. and Chen, W., 2018. Soil and Water Assessment Tool model predictions of annual maximum pesticide concentrations in high

vulnerability watersheds. *Integrated Environmental Assessment and Management*, 14(3), pp.358-368.

- [24] Arnold, J. G., Srinivasan R., Muttiah, R. S. and Williams, J. R. (1998). Large area hydrologic modeling and assessment Part I: Model development. *J. of the Am. Water Resour. Asso.*, AWRA, Vol. 34(1): 73-89.
- [25] Ha, L.T., Bastiaanssen, W.G., Van Griensven, A., Van Dijk, A.I. and Senay, G.B., 2018. Calibration of spatially distributed hydrological processes and model parameters in SWAT using remote sensing data and an auto-calibration procedure: A case study in a Vietnamese river basin. *Water*, 10(2), p.212.
- [26] Abbaspour, K.C., Yang, J., Maximov, I., Siber, R., Bogner, K., Mieleitner, J., Zobrist, J. and Srinivasan, R., 2007. Modelling hydrology and water quality in the pre-alpine/alpine Thur watershed using SWAT. *Journal of hydrology*, 333(2-4), pp.413-430.
- [27] Samadi, S., Tufford, D.L. and Carbone, G.J., 2017. Assessing Parameter Uncertainty of a Semi-Distributed Hydrology Model for a Shallow Aquifer Dominated Environmental System. *JAWRA Journal of the American Water Resources Association*, 53(6), pp.1368-1389.
- [28] Abbaspour, K.C. and Calibration, S.W.A.T., 2008. Uncertainty Programs-A User Manual. Department of Systems Analysis. *Integrated Assessment and Modeling (SIAM)*, Eawag, Swiss Federal Institute of Aquatic Science and Technology, Duebendorf, Switzerland, 95pp.
- [29] Wu, H. and Chen, B., 2015. Evaluating uncertainty estimates in distributed hydrological modeling for the Wenjing River watershed in China by GLUE, SUFI-2, and ParaSol methods. *Ecological engineering*, 76, pp.110-121.
- [30] Narsimlu, B., Gosain, A.K., Chahar, B.R., Singh, S.K. and Srivastava, P.K., 2015. SWAT model calibration and uncertainty analysis for streamflow prediction in the Kunwari River Basin, India, using sequential uncertainty fitting. *Environmental Processes*, 2, pp.79-95.
- [31] Kumar, N., Singh, S.K., Srivastava, P.K. and Narsimlu, B., 2017. SWAT Model calibration and uncertainty analysis for streamflow prediction of the Tons River Basin, India, using Sequential Uncertainty Fitting (SUFI-2) algorithm. *Modeling Earth Systems and Environment*, 3, pp.1-13.
- [32] Tejaswini, V. and Sathian, K.K., 2018. Calibration and validation of swat model for Kunthipuzha basin using SUFI-2 algorithm. *Int J Curr Microbiol Appl Sci*, 7(1), pp.2162-72.
- [33] Yang, J., Reichert, P., Abbaspour, K.C., Xia, J. and Yang, H., 2008. Comparing uncertainty analysis techniques for a SWAT application to the Chaohe Basin in China. *Journal of hydrology*, 358(1-2), pp.1-23.
- [34] Ficklin, D.L., Luo, Y. and Zhang, M., 2013. Watershed modelling of hydrology and water quality in the Sacramento River watershed, California. *Hydrological processes*, 27(2), pp.236-250.
- [35] Kamali, B., Abbaspour, K.C., Lehmann, A., Wehrli, B. and Yang, H., 2018. Uncertainty-based auto-calibration for crop yield—the EPIC+ procedure for a case study in Sub-Saharan Africa. *European journal of agronomy*, 93, pp.57-72.
- [36] Refsgaard, J.C., 1997. Parameterisation, calibration and validation of distributed hydrological models. *Journal of hydrology*, 198(1-4), pp.69-97.

- [37] Moriasi, D.N., Arnold, J.G., Van Liew, M.W., Bingner, R.L., Harmel, R.D. and Veith, T.L., 2007. Model evaluation guidelines for systematic quantification of accuracy in watershed simulations. *Transactions of the ASABE*, 50(3), pp.885-900.
- [38] Henriksen, H.J., Trolborg, L., Nyegaard, P., Sonnenborg, T.O., Refsgaard, J.C. and Madsen, B., 2003. Methodology for construction, calibration and validation of a national hydrological model for Denmark. *Journal of Hydrology*, 280(1-4), pp.52-71.
- [39] Gupta, H.V., Sorooshian, S. and Yapo, P.O., 1999. Status of automatic calibration for hydrologic models: Comparison with multilevel expert calibration. *Journal of hydrologic engineering*, 4(2), pp.135-143.
- [40] Thyer, M., Renard, B., Kavetski, D., Kuczera, G., Franks, S.W. and Srikanthan, S., 2009. Critical evaluation of parameter consistency and predictive uncertainty in hydrological modeling: A case study using Bayesian total error analysis. *Water Resources Research*, 45(12).
- [41] Johnston, R. and Smakhtin, V., 2014. Hydrological modeling of large river basins: how much is enough? *Water resources management*, 28, pp.2695-2730.