

Rainfall Analysis and groundwater studies for soil and water conservation in Kodihalli sub - watershed of Haveri district, Karnataka

ABSTRACT

The Kodihalli sub-watershed (4D4D2f) is lies between 14°28'23.68" – 14°34'20.103" North latitudes and 75°26'49.224"– 75°31'44.208" East longitudes and covers an area of about 4398.83 ha. with an average annual rainfall of 783.0 mm (2014-2021). The maximum rainfall of 439.0 mm is received from June to September, 226.0 mm from October to early December and the remaining 118.0 mm is received during the rest of the year. The number of rainy days (>2.5 mm) varied from 13-24 days per year. On an average, the number of rainy-day events likely to produce runoff (20 to 30 mm) are about 2 to 8 rainy days per year with moderate variation across the years. The Actual Evapotranspiration (AET) over the years 2014 - 2021 in the Kodihalli sub-watershed varied from 383.0 to 770.0 mm. During 2014 - 2021, the average annual AET (621.0 mm) was less than the average rainfall (783.0 mm). The average AET/P ratio between 2014-2021 was about 0.79 which is less than the sustainable limit of about 0.80. The soils of watershed viz., sandy clay loam (IR 10 mm/hr) and sandy clay (IR 14 mm/hr) resulted in more infiltration rate than clay (2 mm/hr) and clay loam soils (7 mm/hr). For effective soil and water conservation, maximum area of about 3769 ha (85.7%) requires graded bunding and 267 ha (6.06%) area requires contour bunding

Keywords: Rainfall, Watershed, Evapotranspiration, Groundwater, Kriging and Soil conservation measures

1. INTRODUCTION

The backbone of the Indian economy is agriculture and allied fields which mostly depend upon an abundance of natural resources like rainfall, water resources, soil and forest vegetation. As these resources are limited and depleted yearly, there is an utmost need to stabilize and conserve these resources. Global population growth, climate change, competition from other uses, and increased regulation of agricultural water use are causing water to become increasingly scarce [1, 2]. So, there is an urgent need of advanced technologies are required to optimize water use in agriculture. Sustainable management of land and water resources is essential for food security, maintenance of environment and general well-being of the people. The most important basic natural resources like soil and water that determines the ultimate sustainability of any agricultural system.

Watershed is the geographical area which is drained by the network of streams to the common outlet. A watershed is a complex and dynamic biophysical system which is identified as planning and management unit. A watershed is also a hydrological rejoinder unit and a multifaceted ecological unit in terms of the resources (materials), energy and information present. The watershed not only is a useful unit for physical analyses, it can also be an appropriate socio-economic-political component for the execution of management strategies. In essence, a watershed is a basic organizing unit to manage resources [3].

The planning and management of the watershed are done to accomplish the tasks related to the overall development of the watershed, which may be with respect of water quality and quantity improvement, management of ecosystem, enrichment of the socio-economic status of the watershed inhabitants, enhancing the employment opportunity for the people and selection of most appropriate cropping pattern etc., [4].

Watershed management is the balanced exploitation of terrestrial and aquatic resources for the acquisition of optimal production with petite vulnerability to natural assets. It adopts the rehearsal of soil and water conservational strategies in the watershed, for example, appropriate exploitation of the land, defensive measures of land against anthropogenic pressures, enhancement and management of soil fertility, water conservation for irrigational practices, proper supervision of local water supplies for drainage, protection against flash floods and reduction in runoff and soil erosion, and also escalating the production from all the existing land use patterns. Watershed-level hydrological studies are essential to soil and water resources evaluation, improvement and management. At the field scale, hydrologic studies are engaged in devising and designing of soil conservation practices [5], management of irrigation water, water quality evaluation and water supply availability etc, [5]. Hydrological studies are important tools for comprehending the hydrological behaviour of the watersheds. Karnataka State in India ranks second, next to Rajasthan in drought condition [6]. Rainwater gained its importance with the emerging need and to meet the demands of water resources. Keeping these in view, hydrological studies have been taken up at the Kodihalli sub-watershed (4d5e3b), which is located in the Hirekerur taluk of Haveri district, Karnataka.

2. METHODOLOGY

2.1 Location and Extent

The Kodihalli watershed is located in Hirekerur Taluk, Haveri District of Karnataka, covering villages of Yalavadhalli, Aladageri, Lingdevarakoppa, Kunchur and Mavinathopa. It lies between 14°28'23.68" – 14°34'20.103" North latitudes and 75°26'49.224"– 75°31'44.208" East longitudes and covers an area of about 4398.83 ha. with its elevation ranging from 480 to 638 above man sea level (Fig.1).




Fig. 1. Location map of Kodihalli Sub-watershed of Haveri district, Karnataka

2.2 Geology, Physiography and Drainage of Haveri District

Kodihalli sub-watershed is underlain by formations of Dharwad schist belt called as Dharwars (supergroup of Archean Eon). The major part of the area is underlain by shale and greywacke. The trend of foliation in the schistose formation is NNW-SSE with dip ranging from 45 to 75 degree to the northeast direction. The weathered thickness of the shale is 60 to 75 m and that of greywacke including different types of schists is about 5 to 20 m. Physiographically, the area has been identified as schistose landscape. The sub-watershed area has been further divided into mounds/ridges, summits, side slopes and moderately sloping, gently sloping and very gently sloping uplands and nearly level plains based on slope and its relief features. The elevation ranges from 636-645 m MSL in the moderately sloping uplands.

Haveri district is drained by TungaBhadra River. The TungaBhadra River flowing on the eastern border of the district is the only perennial river in the district. The Varada and Kumudvati rivers are major tributaries of Tungabhadra and river Dharma a major tributary of Varada drains the district. All the rivers in the district together with their tributaries exhibit dendritic drainage pattern and they form part of Krishna main basin.

2.3 Rainfall and Ground Water Measurement

Groundwater recharge is an important and required necessary activity in managing and developing water resources of a watershed. The seasonal water-level fluctuations in the Kodihalli watershed have been analyzed. The borewell in Koda (Well Code: 90606) representing Kodihalli sub watershed groundwater status. Based on available data obtained from Directorate of ground water, Govt of Karnataka, Bengaluru, characteristics of the groundwater pattern, such as average depth, water

level and variability trend in the study area were analysed.

Rainfall is the major source of groundwater recharge. The infiltration of water is mainly governed by lithology, land use practice and elevation of the terrain. Spatial maps were prepared using ArcGIS 10.8. Rainfall data is one of the important data sets in the spatial domain, controlling the water resources budget of the region. Rainfall data for the last eight years were collected from Karnataka State Natural Disaster Monitoring Centre, Govt of Karnataka.

2.4 Point Interpolation: Kriging

Kriging is a geostatistical method for estimating values in unknown areas by considering both the distance and variation between known data points. It involves creating an estimated surface from scattered points with z-values by fitting a mathematical function to nearby points. The process includes statistical analysis, variogram modelling, surface creation, and variance exploration. Predicted values are calculated using a weighted average technique based on the relationship between samples. The search radius can be fixed or variable and generated cell values may exceed the sample range [7].

$$Z(S_0) = \sum_{i=1}^N \lambda_i Z(S_i)$$

Where, $Z(S_i)$ = the measured value at the i^{th} location

λ_i = an unknown weight for the measured value at the i^{th} location

S_0 = the prediction location

N = the number of measured values

The Kriging method is an interpolation method based on principles of zero bias and minimum mean square error. It determines values for a process over an entire domain, finite-volume block or specific point using a linear combination of data values. The summation may be over an entire area or restricted region centered at the estimation point [8].

3. RESULTS AND DISCUSSION

3.1 Weather and Rainfall Analysis

To develop the rainfall indices of the Kodihalli sub-watershed, data from the Aladagri rain gauge station in Hirekerur taluk of Haveri district was taken into account. The district falls under hot semi-arid tract of the state and is categorized as drought-prone with an average annual rainfall of 782.5 mm received in last 8 years (Table 1). The maximum of 439.0 mm precipitation is received during south-west monsoon period from June to September, north-east monsoon contributes about 218.9 mm and prevails from October to early December and the remaining 124.7 mm is received during the rest of the year. The monthly precipitation amounts vary considerably from year to year. During the year 2015, 2016, 2017 and 2018 annual rainfall was deficient by 11%, 45%, 11%, and 10.7%, respectively, during 2019 and 2021 the annual rainfall was excess by 33% and 38.6 %, respectively as compared to average annual rainfall (Fig.2).

During April and May, the temperatures reach up to 36.5°C and in December and January, the temperatures will go down to 16°C. The average monthly Potential Evapotranspiration (PET) is 119.8 mm and varies from a low of 99.8 mm in January to 175.5 mm in the month of March. The PET is higher than precipitation in all the months except end of July to end of October. Generally, length of growing period in Kodihalli sub-watershed ranged from 190 to 200 days (Fig. 3). The length of growing period begins at 19th week (which is May 2nd week) and ends at 47th week (which is November 3rd week). Based on the observation, farmers can schedule sowing and other agronomic practices for short duration and long duration crops.

Table 1. Mean monthly rainfall, PET, 0.5 PET at Hirekerur Taluk, Belagavi District

Month	Rainfall (mm)	Temp Max (°C)	Temp Min (°C)	Max. RH (%)	Min. RH (%)	PET (mm)	0.5 PET (mm)
January	7.0	31.0	16.6	85.7	32.6	99.8	49.9
February	3.9	33.0	17.2	84.3	25.0	119.1	59.6
March	6.2	35.5	20.1	91.0	25.1	175.5	87.8
April	34.3	36.6	22.4	92.2	29.9	147.3	73.7
May	73.3	34.5	22.6	91.6	46.0	141.8	70.9
June	87.3	30.2	22.2	94.0	61.7	114.3	57.2
July	124.1	27.9	21.7	93.0	70.0	115.3	57.7
August	122.5	27.9	21.3	94.1	73.3	117.1	58.6
September	105.2	29.7	21.4	91.9	62.2	100.4	50.2
October	173.3	30.8	20.8	96.1	57.6	119.6	59.8
November	40.5	30.9	19.0	92.5	46.6	93.0	46.5
December	5.1	31.0	17.3	92.1	42.6	94.5	47.3
Total	782.5					1437.7	718.9

3.2 Rainfall Distribution

The number of rainy days (>2.5 mm) varied from 13 to 29 days per year. On an average the number of rainy-day events likely to produce runoff (20 to 30 mm) are about 2 to 8 rainy days per year with moderate variation across the years (Fig. 4). The extremely high rainfall peak event days (>30mm) 8 day per year observed in the year 2019 which may cause flood. Which helps in designing conservation and harvesting structure in a watershed. Extreme precipitation is characterized by high spatial variability, the detection of trends induced by changing climate conditions is highly dependent on the quality and quantity of observed rainfall data [9]. In Karnataka different watershed areas clearly indicate that rainfed farming in the region is highly vulnerable to rainfall variability and continues to be risk prone for drought [10].

Fig. 2. Average annual rainfall at Hirekerur Taluk, Haveri District, Karnataka

Fig.3. Mean weekly rainfall, PET and 0.5 PET₅ of Hirekerur Taluk, Haveri District, Karnataka

Fig.4. Distribution of Rainfall in different rainfall events

3.3 Spatial and Temporal Estimation of Actual Evapotranspiration

The Actual Evapotranspiration (AET) over the years 2014-2021 in the Kodihalli sub-watershed varied from 383 to 770 mm (Fig. 5). During 2014-2021, the average annual AET (621.0 mm) was less than the average rainfall (782.5 mm). AET was higher than rainfall during the months of January to April, November and December, which forced groundwater withdrawal during these months to meet crop water needs (Fig.6).

In the sub-watersheds, the mean annual AET is lower than the mean annual rainfall. This means at the annual time scale of water budget demand side is lower than the supply side. During *kharif season* (June-September), the mean rainfall is higher than the mean AET which means there is surplus water budget in this season for investing in useful water storage. During *Rabi season* (October-January), the mean AET is higher than mean rainfall. During the *summer season* (February-May), the mean AET is close to the mean rainfall.

The spatial maps of reference and actual evapotranspiration describe that the difference between ET_{ref} and ET_a is less over upper, middle and lower ridges of the watershed (Fig.7). The ridge-wise analysis in annual actual evapotranspiration shows that the extremely low (565-583 mm) values observed over upper and lower ridge of the watershed and high (721-725 mm) amount of ET_a observed over middle ridge of the watershed. Spatial variability in of actual evapotranspiration was due to soil moisture, vegetation cover and cropping systems adopted in the watershed [11]. To understand the reason for the variability in ET_a , the seasonal trends are calculated for the major evapotranspiration components including transpiration, bare soil evaporation, interception loss, and open water evaporation during the study period [12]. The transpiration and interception loss from the vegetation has shown a tremendous change in the evapotranspiration [13].

AET can be more efficiently retrieved at the farm scale using remote sensing techniques that are spatially consistent and temporally continuous. This methodology has the advantage of providing estimates across the entire territory, capturing minor spatial variations between pixels that allow one to assess water use, irrigation, and groundwater recharge efficiency [14, 15].

Fig.5. Actual evapotranspiration (AET) and rainfall over different years (Temporal)

Fig.6. Month wise Actual evapotranspiration (AET) and rainfall (Temporal)




Fig. 7. Spatial Map of the Annual Actual Evapotranspiration of Kodihalli sub-watershed.

3.4 Evapotranspiration Index

Budyko curve is the relationship between the ratio of the actual evaporation amount to the annual precipitation (AET/P) and the ratio of the potential evaporation amount to the annual precipitation (PET/P), called the dryness index or aridity index) based on data obtained from watersheds [16]. The watershed water balance is in normal condition. For sustainability, the limit of AET/P should be below the Budyko curve for sustainable watersheds from hydrological considerations. This suggests that the cropping choices and irrigation choices have to be altered to reduce the total ET (Fig.8.). The average AET/P ratio between 2014-2021 was about 0.79 which is less than the sustainable limit of about 0.80 (Fig. 9). During 2014 and 2015, AET/P ratio were 1.47 and 1.11 respectively, which indicates receipt of less rainfall in the years and also possibility of ground water being augmented to maintain crop water requirement.

To build on this and link the Budyko's hypothesis to the complementary relationship between actual evaporation and potential evaporation [17]. The Budyko curve analytically by modelling total evaporation using simple models of interception and transpiration in combination with measurable parameters related to rainfall dynamics and storage availability obtained from remotely sensed data sources [18].

The Budyko curve has also been interpreted at a higher physical level as a possible outcome of thermodynamic optimality through the invocation of the maximum entropy production principle [19]. Budyko curve parameter could facilitate and easily utilized by policymakers for watershed quality assessment and hydrological system identification [20]. The Budyko curve is different for each watershed, and the point on the curve moves due to climate change. Therefore, it is possible to predict when climate changes. It has the advantage of quantitatively evaluating the effect of improving the hydrological system by watershed management [16].

Fig. 8. Seasonal Budyko curve of Kodihalli sub-watershed of Karnataka (2014-21)

Fig .9. AET/P Ratio of Kodihalli sub-watershed of Karanataka

3.5 Soil Texture and Infiltration Rate

Texture is an expression to indicate the coarseness or fineness of the soil as determined by the relative proportion of primary particles of sand, silt and clay. It has a direct bearing on the structure, porosity, water infiltration, adhesion and consistence. The textural classes used for LRI were used to classify and a surface soil texture map was generated. The area extent and their geographical distribution in the sub-watershed is shown in Fig 10. An area of about 551 ha (12.5%) has a clay texture at the surface. The most productive lands concerning surface soil texture are clayey soils (12.5%) with an infiltration rate of 2mm/hr that have a high potential for retention and availability of water and nutrients but, have more problems with drainage, infiltration, workability and other physical problems. The sandy clay loam (1654 ha), clay loam (1811 ha) and sandy clay (20 ha) texture classes occupied the majority of the sub-watershed area. The soils of watershed viz., sandy clay loam (10 mm/hr) and sandy clay (14 mm/hr) resulted in more infiltration rate than clay (2 mm/hr) and clay loam soils (7 mm/hr). The surface soil textural class provides a guide to understanding soil-water retention and availability, nutrient holding capacity, infiltration, workability, drainage, physical and chemical behavior, microbial activity and crop suitability [21,22,23]. Soil textural classes are pivotal in determining the volume of water that can infiltrate into subsurface formations, thereby influencing groundwater recharge. When evaluating infiltration rates, soil texture and hydraulic properties are important considerations.




Fig. 10. Surface soil texture and infiltration rate map of Kodihalli sub-watershed

3.6 Groundwater Depth Measurement and Kriging

The groundwater level data is an important variable in the hydrological budget for estimation of recharge from rainfall or other sources in sub watersheds. Time series data of groundwater level is also useful in understanding the usage patterns of groundwater for irrigation. The data is also useful in assessing the role of managed aquifer recharge or watershed practices in the catchments [24]. Groundwater levels fluctuate naturally in response to a sequence of climatic events and to constraints imposed by hydrogeologic and topographic characteristics. The groundwater level is influenced by borewell recharge, discharge, topography of land, soil texture etc. Trend analysis of water table depths indicates marked spatial variations of groundwater levels in the Kodihalli sub-watershed of the study area. The mean depth of groundwater observed from ground level during pre and post-monsoon. During pre and post monsoon the average ground water depth highest of 19.0 mbgl and lowest of 4-5 mbgl (Fig.11 and 12). These data indicate marked spatial variability in the distribution of wells with distinct rates of change across the different geomorphic units

visible [25]. The groundwater resource of a region is one of the building blocks for the balanced economic development of the area. The water table represents the groundwater reservoir, and changes in its level represent the changes in groundwater storage [26].

The highest groundwater elevation occurred in the west to the western part of the study area and the lowest groundwater elevation was obtained in the northeastern part of the study area (Fig.11 and 12). The groundwater elevation gradients are higher in the northern part and gradually decrease towards the southern parts and the general flow occurs from north to south [27]. The groundwater table is deep on the upstream side and shallow on the mid and valley sides. This is possibly due to the flux that the water drains downslope to bring the soil moisture to the field capacity [28].




Fig. 11. Pre-monsoon Ground water depth of Kodihalli sub-watershed of Karnataka




Fig. 12. Post-monsoon Groundwater depth of Kodihalli sub-watershed of Karnataka

The ground water level data have been monitored from the representative wells for pre and post-monsoon seasons for the years 2014 to 2023 has given in figure 13. The borewell in Koda (Well Code: 90606) representing Kodihalli sub-watershed groundwater status. Based on available data obtained from Directorate of ground water, Govt of Karnataka, Bengaluru, there was falling trend of depth to water table (25-37 mbgl) in the watershed during 2016 to 2019, as these years were lower rainfall years and indicates utilization of groundwater to buffer the lower rainfall years. The long-term data of depth to Water level is analysed to interpret the behaviour of groundwater over period of time. The groundwater level is observed to show an increasing trend [29]. Which directly means that, the availability of groundwater is enhanced over the last decade. The pre-monsoon period as well as post-monsoon

period shows the increasing trend of groundwater level.

Fig.13. Ground water status of Kodihalli sub watershed over different years

3.7 Soil and water conservation treatment plan

There are always strong links between measures for soil conservation and measures for water conservation, and this applies equally in semi-arid areas. For preparing the soil and water conservation treatment plan for the Kodihalli sub-watershed, the land resource inventory database was generated and transformed as information through a series of interpretative (Thematic) maps using a soil phase map as a base. A map showing soil and water conservation plan with different kinds of structures recommended has been generated which shows the spatial distribution and extent of area. A maximum area of about 3769 ha (85.7%) requires graded bunding, 267 ha (6.06%) area requires contour bunding and 51 ha (1.16%) requires graded trenching (Fig.14.). The size distributions of the particles (Soil texture) were significantly affected by conservation measures and between conservation types [30].




Fig.14. Soil and Water Conservation Plan map of Kodihalli sub-watershed

CONCLUSION

The total geographical area of the Kodihalli sub watershed is 4398.83 ha. and the sub watershed is primarily composed of loamy sand followed by sandy clay loam, sandy loam and clay. The infiltration rates within the sub watershed varied based on the type of soil and ranged from 3 to 14 mm/hr. In sub watershed the mean annual ET is lower than the mean annual rainfall. This means at the annual time scale of water budget demand side is lower than the supply side. There was falling trend of depth to water table (25-37 mbgl) in the watershed during 2016 to 2019, as these years were lower rainfall years and indicates utilization of groundwater to buffer the lower rainfall years. The groundwater map shows the natural topography and prevailing conditions in the watershed are favorable for declining water table. The point recharge

and farm ponds may be constructed in the lower most corner of the agricultural fields to increase the natural recharge of rain water during the monsoon period.

REFERENCES:

- Boretti A, Rosa L. Reassessing the projections of the world water development report. *Nature Partner journal of Clean Water*, 2019; 2: 1–6.
- Kisekka I, Peddinti SR, Kustas WP, McElrone AJ, Bambach-Ortiz N, McKee L, Bastiaanssen W. Spatial–temporal modeling of root zone soil moisture dynamics in a vineyard using machine learning and remote sensing. *Irrigation Science*, 2022;1:1–17
- Sadeghi SHR. Watershed Management in the 21st Century. In: Yousuf, A. and Singh, MJ. (eds.) *Watershed Hydrology, Management and Modelling*. CRC Press, Taylor and Francis, Boca Raton, 2020: 152-162.
- Anonymous. *A Source Book for Soil and Water Conservation Measures*. Foundation for Ecological Security, Anand, Gujarat, 2018: pp 1-239.
- Wurbs, R. Dissemination of generalized water resources models in the United States. *Water International*, 1998; 23:190-198.
- Jayasree V, Venkatesh B. Analysis of Rainfall in Assessing the Drought in Semi-arid Region of Karnataka State, India. *Water Resource Management*, 2015; 29: 5613–5630
- Mustafaa JS, Mawlood DK. Mapping groundwater levels in Erbil Basin, *American Academic Scientific Research Journal for Engineering, Technology and Sciences*. 2023; 93 (1): 21-38.
- Varouchakis EA, Hristopulos DT, Karatzas GP. Improving kriging of groundwater level data using nonlinear normalizing transformations - a field application, *Hydrological Sciences Journal*.2012; 57(7):1404-1419.
- Tamm O, Egle Saaremaa, Kristiina Rahkema, Jaak Jaagus, Toomas Tamm. The intensification of short-duration rainfall extremes due to climate change – Need for a frequent update of intensity–duration–frequency curves, *Climate Services*, 2023;20: 100349-100354.
- Raizada A, Adhikari RN, Kumar S, Patil SL, Ramajayam D, Prabhavathi M, Loganandhan N, Mondal, Muralidhar W. Impact assessment of watershed interventions under low rainfall situations in semi-arid Karnataka, 2018; 46:1-10.
- Alexander Samuel, Atkilt Girma, Amanuel Zenebe, Tesfaalem G. Spatio-temporal variability of evapotranspiration and crop water requirement from space, *Journal of Hydrology*, 2018; 567: 732-742.
- Melloulia HJ, Van Wesemael B, Poesenc J, Hartmann R. Evaporation losses from

bare soils as influenced by cultivation techniques in semi-arid regions, *Agricultural Water Management*, 2000; 42:355-369.

- Raghavendra Prasad K, Kantha Rao B, Patra GK, Himesh S, Sheshakumar G. Annual and seasonal trends in actual evapotranspiration over different meteorological subdivisions in India using satellitebased data, *Theoretical and Applied Climatology*.2023; 52:999–1017.
- Khan MS, Baik J, Choi M. Inter-comparison of evapotranspiration datasets over heterogeneous landscapes across Australia. *Advances in Space Research*, 2023; 66(3): 533-545.
- Tridiv Ghosh, Bappa Das, Vinay K S, Debasish Roy, Joydeep Mukherjee, Rajkumar Dhakar, Koushik Bag, Debashis Chakraborty. Estimation of actual evapotranspiration using the simplified-surface energy balance index model over an irrigated agricultural farm, *Journal of Agrometeorology*, 2023; 25(3): 365-374.
- Dey P, Mishra A. Separating the impacts of climate change and human activities on streamflow: A review of methodologies and critical assumptions, *Journal of Hydrology*, 2017; 548:278–290.
- Yang D, Sun F, Liu Z, Cong Z, Lei Z. Interpreting the complementary relationship in non-humid environments based on the Budyko and Penman hypotheses, *Geophysical Research Letters*. 2006; 33:1-5.
- Kyeung Kim, Hakkwan Kim, Hyunji Lee, Sang-Min Jun, Soonho Hwang, Jung-Hun Song and Moon-Seong Kang. Development and Assessment of Watershed Management Indicators Using the Budyko Frame work Parameter, *Sustainability*, 2021; 13: 1-15.
- Gerrits AMJ, Savenije HHG, Veling EJM, Pfister L. Analytical derivation of the Budyko curve based on rainfall characteristics and a simple evaporation model. *Water Resources Research*. 2009;45: 1-15.
- Zhao J, Wang D, Yang H, Sivapalan M. Unifying catchment water balance models for different time scales through the maximum entropy production principle. *Water Resources Research*. 2016; 52 :7503–7512.
- Christelle Basset, Majdi Abou Najm, Teamrat G, Xiaoxiao Hao, Andr´e D. How does soil structure affect water infiltration? A meta-data systematic review, *Soil and Tillage Research*. 2023; 226:1-15.
- Nawaz MF, Bourri´e G, Trolard F. Soil compaction impact and modelling. a review. *Agron. Sustain. Dev.* 2013; 33 (2) :291–309.
- Huang J, Hartemink AE. Soil and environmental issues in sandy soils. *Earth Sci. Rev.* 2020; 208;103295.

- Rajashekhar DB, Chandrakantha G. Groundwater and hydrological studies in Ajjampur sub-watershed, Plant Archives, 2020;20(1): 2001-2004.
- Suneel Kumar Joshi, Sanjeev Gupta, Rajiv Sinha, Alexander LD, Shive Prakash R, Shashank S, Philippa JM, Van Dijk WM. Strongly heterogeneous patterns of groundwater depletion in Northwestern India, Journal of Hydrology.2021; 598: 126-492.
- Raghavendra G. Groundwater fluctuation and the flow pattern in the Kamarwadi sub-basin of Bhima River. Res Rev J Eng Technol. 2013; 73: 101-108.
- Nikroo L, Zare MK, Sepaskhah AR, Shamsi SRF. Groundwater depth and elevation interpolation by kriging methods in Mohr Basin of Fars province in Iran. Environmental Monitoring and Assessment. 2010; 166: 387-407.
- Addisie MB. Groundwater recharge estimation using water table fluctuation and empirical methods. H₂Open Journal.2022; 5(3):457-468.
- Manjunatha MV, Manjunatha SB, Nagaraj Malappanavar, Manjunatha Hebbara, Kuligod VB, Shirahatti MS, Chidanand Pujeri, Jyoti Hiremath, Hydrological Studies of Artal Sub-watershed of Belagavi District, Karnataka, India. Journal of Experimental Agriculture International, 2024; 46 (10):36-48.
- Yonas A, Temesgen K, Alemayehu M, Toyiba S. Evaluation of the effectiveness of soil and water conservation practices on improving selected soil properties in Wonago district, Southern Ethiopia. Journal of Soil Science and Environment Management. 2017; 8: 70–79.