

POUR POINT DEPRESSION OF WAXY CRUDE OIL USING UNMODIFIED AFRICAN PEAR (*DACRYODES EDULIS*) SEED OIL

Abstract

The pour point depression of a Nigeria waxy crude oil was investigated using unmodified African pear seed oil. Crude oil sample collected from a marginal field in Delta state was analyzed for its physiochemical parameters such as; specific gravity, API, kinematic viscosity, pour point and wax content. African pear seeds sourced from choba Port Harcourt were extracted of their oil content and the oil was analyzed for some oil quality parameters such as; free fatty acid (FFA), acid value, saponification value and iodine value. The results showed a crude oil of high wax content and extracted oil of low FFA and high saponification and iodine values. The waxy crude oil was dosed with the unmodified African pear seed oil of concentrations 0.1ml, 0.2ml and 0.3 ml. The result showed no reduction in the pour point of the crude oil at all concentrations. Therefore the African pear seed oil cannot be used as a pour point depressant in its pure state.

Key words: Pour point; waxy crude oil; depressant; unmodified; African pear; oil

Introduction

The oil industry's midstream sector is largely reliant on the steady flow of crude oil from upstream to downstream. Crude oil is made up of a complex and diverse set of hydrocarbon components (Litvinets et al., 2016). When the temperature falls below the Wax Appearance Temperature (WAT), paraffin waxes separate from crude oil and build up on the inner surface of transfer pipelines (Al-Sabagh et al., 2016). Wax accumulation is a key difficulty in crude oil extraction, separation, transportation, and refining. Because crude oil is susceptible to pressure and temperature changes as it leaves the reservoir and travels down the pipeline, the development of wax crystals in the fluid accelerates (Oseghale and Akpabio, 2012). As a result, viscosity increases as temperature drops, resulting in a decrease in fluidity (Al-Sabagh et al., 2012).

In extreme situations, this might bring crude oil production to a halt. As a result, controlling wax precipitation and wax gelation in flow assurance is a significant challenge. To address this issue,

several flow-improvement techniques are used to reduce wax crystal accumulation. To overcome higher pressure drops while transporting waxy crude oil through a pipeline at a temperature below the pour point, extra energy is required.

There are several approaches for improving crude oil fluidity at low temperatures. Heavy oil dilution is a frequently used traditional approach for improving fluidity, whereas heating is employed to prevent low temperatures. Pigging is a method of cleaning and removing wax deposits from pipelines.

The use of chemicals known as pour point depressants as a flow improver is a new, simple, and cost-effective technology (Litvinets et al., 2016). There are several chemicals that have been used for the purpose of Pour point depression of Crude oil. Insistence on the low toxicity and greenings of these depressants has driven researchers to the use of modified and unmodified natural products. This work is one of such attempts at using green substances as Pour Point depressants.

Wax formation and deposition during crude oil production is one of the long-standing problems in petroleum industry. At low temperatures, the crystals of wax easily form impermeable cake. This leads to stoppage of production and sometimes a complete shutdown of facilities and process resulting in loss of revenue for the industries due to reduced output and increased maintenance cost. Hence, there is need to find a solution to the problem posed by wax formation and deposition.

Safou (French), ube (Igbo), elemi (Yoruba), eben (Efik), and orumu (Benin) are all names for *Dacryodes Edulis* (African pear), which belongs to the *Burseraceae* family. They thrive in a wide range of climates and soil types, and they're found all over Africa. Cabinda, Cameroon, Congo (Brazzaville and Kinshasa), Gabon, Ghana, Equatorial Guinea, Nigeria, and Sao Tome are among the countries where they can be found. The trees are grown near homesteads in south-east Nigeria, and blossoming occurs from January to April. Between May and October is the main fruiting season. The fruits are boiled or roasted and eaten with corn in both rural and urban parts of Nigeria (Onuegbu et al., 2011).

Methodology

Sample Collection and Preparation

The crude oil sample used for this study was collected from a Marginal field in Delta State Nigeria. The seed of *Dacryodes Edulis* (African pear) was obtained from Choba Area in Obio-

Akpor Local Government of Rivers State. Seed of *Dacryodes Edulis* 4kg were sundried and pulverized to fine texture using an industrial blender.

Characterization of the Crude Oil Sample

The physicochemical characterization of Crude oil was carried out by means of some standard test methods as follows:

Determination of Density, Calculation of Specific Gravity and Api Gravity of Crude Oil Samples.

An Empty density bottle was measured using physical balance, the density bottle was filled to the volume mark with the oil. The weight of the density bottle with the oil was measured and recorded

$$\text{Density} = \frac{\text{mass}}{\text{volume}} = \frac{m_2 - m_1}{v} = \dots\dots\dots\text{eqn1}$$

Where;

M1 = mass of empty density bottle

M2 = mass of density point with crude oil

V = volume of the oil

Calculation of Specific Gravity

Empty density bottle was measured using physical balance, the density bottle was filled to the volume mark with distilled water. The weight of the density bottle with the distilled water was measured and recorded. Same was repeated using the oil. And recorded

The specific gravity = density of crude oil sample/density of water.....Eqn2

Calculation of Api Gravity.

API gravity was calculated using the value of specific gravity obtained from eqn. 2 above. API gravity can be calculated using the following expression

$$= \frac{141.5}{\text{Specific gravity}} - 131.5$$

API Gravity

Determination of Viscosity

Viscosity is a measure of resistance to flow of an oil due to internal friction offered by the fluid

Procedure (ASTM D445)

The viscometer bath is set at 40⁰ C and a thermometer was inserted on the bath to take temperature of the bath fluid as a feedback reading. The sample was poured into a suitable viscometer Oswald viscometer to the marked Level. The time taken for the sample to flow to the second marked of the viscometer was recorded.

Kinematic Viscosity (V) = ct (unit is centistoke Cst or mm² / s²)

Where c = viscosity constant of the U-tube in mm² /S²

Determination of Pour Point

Pour point is the minimum temperature at which no oil movement is observed. The ASTM D97 test method was used in pour point determination

Procedure

The sample was placed in a heated water bath for liquefaction and transferred to the test jar up to mark. The test jar was tightly closed by the cork and the thermometer position adjusted so that the thermometer bulb was completely immersed. The test jar was rapidly cooled at a temperature of 8-10⁰ C, which was above the expected pour point temperature intervals of 3⁰C. This was continued until the sample placed in the test jar showed no movement when aligned horizontally for exactly 5 seconds. The temperature reading on the thermometer was reported by adding 3⁰C to the recorded value as the pour point temperature.

Extraction of *Dacryodes Edulis* (African Pear) Seed Oil

3kg (3000g) of ground African pear (*Dacryodes edulis*) seed was measured using an analytical weighing balance into a container and soaked with 3.5 litres of n-hexane for 2 days. The container was covered and made air tight to avoid evaporation of n-hexane. Decantation was carried out followed by filtration. Distillation of the filtrate to recover the n-hexane was done at a temperature of 65⁰C using Soxhlet (Atta, 2015). The percentage yield of the oil was calculated as thus:

$$\% \text{ yield} = \frac{\text{weight of extracted}}{\text{weight of sample used}} \times 100 \dots\dots\dots \text{eqn 3}$$

Determination of Oil Quality Parameters of the Extracted Oil

Saponification Value

0.5g of the oil sample was weighed into a conical flask. 50mls of 0.5N ethanolic solution of potassium hydroxide was added and the solution was refluxed to ensure perfect dissolution. The solution was allowed to cool. 3 drops of phenolphthalein were added. The solution was titrated with 0.5N HCl until the pink color of indicator disappeared (V1). A blank (V2) was carried out as well.

Thus, saponification value was calculated using this equation 4

$$\text{Saponification Value} = \frac{56.1 \times (V2 - V1) \times 0.5}{\text{weight of sample}} \dots\dots\dots \text{eqn. 4}$$

Iodine Value

0.5g of the oil sample was weighed into a conical flask. 15ml of chloroform was added after which 25ml of Wiji solution (mixture of iodine, acetic acid and chloroform) was added and covered slightly using a foil and masking tape. The resulting solution was placed in the dark for 30 minutes. 20ml of potassium iodide was added followed by 150ml of distilled water. The solution turned red. 5ml of 1% starch indicator was added which turned the solution blue black. The whole solution was titrated with 0.1N sodium thiosulphate till the end point is achieved (V1). A blank (V2) was carried out too starting with 15ml of chloroform. Solution turned to blue black precipitate and then to colourless. Iodine value was calculated using equation 5

$$\text{Iodine Value} = \frac{12.69 \times (V2 - V1) \times \text{Normality of the titrant}}{\text{weight of sample}} \dots\dots\dots \text{eqn 5}$$

Free Fatty Acid (FFA)

0.5g of the sample was weighed into a dry beaker and 20ml of ethanol added to it. 3 drops of phenolphthalein indicator were added and shook. The solution was titrated with 0.1N sodium hydroxide until a pink colouration was observed.

$$\% \text{ FFA} = \frac{\text{titre value} \times 0.0282 \times 10}{\text{weight of sample used}} \dots \dots \dots \text{eqn. 6}$$

Acid Value

2 g of the sample was weighed into a dry beaker, 25 ml of chloroform and 25 ml of ethanol was added and mixed. 2 drops of phenolphthalein were added to the resulting mixture. The mixture was titrated with 0.1N NaOH to the end point of which a dark pink color was observed.

$$\text{Acid value} = \frac{\text{titre value} \times \text{normality of the base} \times 56.1}{\text{weight of sample used}} \dots \dots \dots \text{eqn 7}$$

Application of the Unmodified African Pear (*Dacryodes Edulis*) Seed Oil on the Waxy Crude Oil

The African pear (*Dacryodes Edulis*) seed oil was added to the waxy crude oil in different concentration using a micro-syringe. The concentration range from 0.1 ml to 0.3 ml to 20 ml of the waxy crude oil. The mixture was allowed to stand for one hour and collected for physiochemical analysis.

Results and Discussion

Table 1 Characterization of Crude Oil

S.NO.	Parameters	Unit	Value
1	specific gravity		0.883
2	API	°	28.7
3	kinematic viscosity	Cst	2.09
4	pour point	°C	21
5	wax content	%	29.5

Table 1 shows the physicochemical properties of crude oil sample. Specific gravity gives an idea about the presence of light and high molecular weight hydrocarbons. The lesser the value of specific gravity, the higher the amount of hydrocarbons in the Petroleum (Kumar et al., 2017)

The crude oil samples from Marginal field in Delta State Nigeria have specific gravity of 0.883 indicating a composition of lower and higher molecular weight hydrocarbon. API gravity is reverse of specific gravity and describes the nature of crude oils, i.e., light or heavy. The API of the crude oil is 28.7⁰ which indicate medium oil. Pour point is an import parameter used to measure the wax content of crude oils. The pour point measures the temperature at which a crude oil no longer flows, and for paraffinic crude oils, pour points are usually between 12 °C and 15 °C, and are determined by operation of the dewaxing unit. The pour points of crude oil sample is 21 °C. These crude oil samples are within the paraffinic base oils. Values greater than 15 °C indicate that the crude oil samples have high wax content as an indication of a high wax content value of 29.5.

The kinematic viscosity at 2.09 Cst is high. According to Davidson et al. (2004) crude oil is heavy, dense and viscous due to the high ratio of aromatics and naphthenes to parafins and high amounts of nitrogen, sulphur, oxygen and heavy metals. the kinematic viscosities have particular role in assessing the producibility of a reservoir (rate and amount of oil production from a reservoir) as well as determining the amount of diluent that will permit pipeline transportation of the crude oil i.e., it is used in calculating the flow of liquids through nozzles, orifices and pipelines. The kinematic viscosity of petroleum products is important for flow of fuel through pipelines, injection nozzles and lubricants for bearings, gears, compressor cylinders and hydraulic equipment. Also, for designing proper temperature ranges for the proper operation of the fuel in burners. The lower the viscosity of a fluid, the more easily it flows.

Table 2 Characterization of *Dacryodes Edulis* Seed Oil (modified and unmodified)

S.No.	Parameters	Unit	Unmodified oil
1	% FFA	%	2.5
2	acid value	mgKOH/g	5.4
3	saponification value	mgKOH/g	94.3
4	iodine value	g/iodine/100g	30.65
5	yield	%	67

Table 2 shows the oil quality parameters of *Dacryodes Edulis* seed oil. The iodine, saponification levels were comparable to those found in other vegetable oils. Free fatty acid, and acid value, on the other hand, were all fairly high. This may be due to the oil's unrefined nature as evidenced by a study by Mohamed *et al.*, (2017), which showed that unrefined soybean and cotton seed oils had higher acid value and FFA concentrations than refined oils. The saponification value of oils is a measurement of their capacity to make soap. Saponification readings above a certain threshold indicate a high soap-forming ability and vice versa. *Dacryodes Edulis* seed oil saponification value (SV) was found to be 94.3 mg KOH/g. This figure was lower than the Codex Alimentarius Commission's recommendations of 230-254 mg KOH/g for palm kernel oil and 248-265 mg KOH/g for coconut oil. *Dacryodes Edulis* seed oil's strong saponification suggests that it has a high soap-forming ability, implying that it could be effective in soap manufacturing (Singhal *et al.*, 1991).

Prior to the degradation reactions, the levels of free fatty acid (FFA) and also the acid value (AV) affect the rate of rancidification in oil owing to oxidative degradation. According to Mohamed *et al.*, (2017) oil's free fatty acid content is directly proportional to its acid value, therefore the higher the acid value of a vegetable oil, the higher the percentage free fatty acid. In oxidative degradation events, free fatty acids act as pro-oxidants, resulting in an unpleasant flavour in oils (Ghazani *et al.*, 2013). As a result, *Dacryodes Edulis* seed oil's fairly high free fatty acid content (2.5%) and acid value (5.4 mg KOH/g) indicate that it may have poor storage stability. Deodorization methods could be utilized to reduce FFA levels in *Dacryodes Edulis* seed oil and increase its storability (Onuegbu & Igwe, 2011). The degree of unsaturation of fats and oils is measured by the iodine value *Dacryodes Edulis* seed oil has an iodine value of 30.65g/iodine/100g. The existence of fewer unsaturated C=C bonds in *D. gDacryodes Edulis* seed oil is indicated by its lower iodine value.

Table 3 Effect of Unmodified *Dacryodes Edulis* (African pear) seed oil on the pour point of a waxy crude oil sample

Concentration of additives in ml	Pour point of waxy crude oil
0.1	21 ⁰ C
0.2	21 ⁰ C
0.3	21 ⁰ C

The pour point of the crude with pour point depressant at different concentration is presented in table 3. The performance of the *Dacryodes Edulis* (African pear) seed oil as crude oil pour point depressant showed no significant reduction in pour point and this could be due to the high acid

value and a medium percentage of free fatty acid as shown in table 2 which is above the permissible limit of 3.0 of acid value. This is a clear indication that it couldn't inhibit the wax deposition of the crude oil and shows no effect on the pour point of the crude oil at all the concentrations dosed.

Conclusion

The unmodified African Pear seed oil did not exhibit any significant pour point depression effect on the waxy crude oil even at varying concentrations. This suggests that the natural composition of African pear seed oil may not be sufficient to alter the crystallization behaviour of the wax in the crude oil.

Further modification or processing of the African pear seed oil may be necessary to enhance its pour point depression properties. Other biomaterials or renewable resources can also be used investigated as pour point depressants.

References

- Al-Sabagh, A.M., Khali, T.M., Sabaa, M.W., Khidr, T.T., Saad, G.R., (2012). Poly (n-alkyl itaconate-co-vinyl acetate) as pour point depressants for lube oil in relation to rheological flow properties. *Journal of dispersion science and technology*, 33, 1649–1660.
- Al-Sabagh, A.M., Khidr, T.T., Moustafa, H.Y., Mishrif, M.R., AI-Damasy, M.H., (2016). Synergistic effect between surfactants and polyacrylate-maleic anhydride copolymers to improve the flow properties of waxy crude oil. *Journal of dispersion science and technology*, 38, 1055–1062
- Atta, A. M., El-Ghazawy, R. A., Morsy, F. A., Hebishy, A., &Elmorsy, A. (2015). Adsorption of polymeric additives based on vinyl acetate copolymers as wax dispersant and its relevance to polymer crystallization mechanisms. *Journal of Chemistry*, 2015, 1-8.
- Davidson, M. R., Nguyen, Q. D., Chang, C., &Rønningsen, H. P. (2004). A model for restart of a pipeline with compressible gelled waxy crude oil. *Journal of non-newtonian fluid mechanics*, 123(2-3), 269-280.

- Kumar, R., Banerjee, S., Mandal, A., & Naiya, T. K. (2017). Flow improvement of heavy crude oil through pipelines using surfactant extracted from soapnuts. *Journal of Petroleum Science and Engineering*, 152, 353–360.
- Litvinets, I. V., Prozorova, I. V., Yudina, N. V., Kazantsev, O. A., & Sivokhin, A. P. (2016). Effect of ammonium-containing polyalkyl acrylate on the rheological properties of crude oils with different ratio of resins and waxes. *Journal of Petroleum Science and Engineering*, 146, 96-102.
- Mohamed, N. H., Soliman, F. S., El Maghraby, H., & Moustfa, Y. M. (2017). Thermal conductivity enhancement of treated petroleum waxes, as phase change material, by α nano alumina: Energy storage. *Renewable and Sustainable Energy Reviews*, 70, 1052–1058.
- Onuegbu, G. C., & Igwe, I. O. (2011). The effects of filler contents and particle sizes on the mechanical and end-use properties of snail shell powder filled polypropylene. *Materials Sciences and Applications*, 2(07), 810.
- Oseghale, C. I., & Akpabio, E. J. (2012). Managing paraffin wax deposition in oil wells–related problems in Nigerian oil fields. *In Nigeria Annual International Conference and Exhibition*. OnePetro.
- Singhal, H. K., Sahai, G. C., Pundeer, G. S., & Chandra, K. (1991). Designing and selecting wax crystal modifier for optimum field performance based on crude oil composition. *In SPE Annual Technical Conference and Exhibition*. OnePetro.