

Energy Assessment Methodology and Analysis in Post Harvest Food System and Opportunities for Use of Renewable Energy Sources: A review

ABSTRACT:

A significant part of agricultural production goes through some degree of transformation between harvesting and consumption to make food edible and digestible. Energy is required to preserve food, reduce post-harvest losses and extend the availability of food over a longer period. This paper describes the stepwise methodology to assess the energy consumption in unit operations performed in the post-harvest food system. The parameters and equations used in accounting for the energy consumption for unit operations and the energy audit have been described. The analysis base is percent plant capacity utilization, production, energy use and energy intensity. The standard representation of different energy sources for the unit operations has also been discussed in the paper. The implementation of these opportunities and renewable energy technologies can provide PHF with a more sustainable, cost-effective, and environmentally friendly approach to processing operations. The systematic approach for estimation of energy in industry helps to identify the energy intensive operation and type of energy used.

Keyword: Energy, energy consumption, energy audit, post-harvest food

Introduction

IMPORTANCE AND SCARCITY OF ENERGY IN POST HARVEST FOOD (PHF) SYSTEM

A significant part of agricultural production goes through some degree of transformation between harvesting and consumption to make food edible and digestible. Energy is required to preserve food, reduce post-harvest losses and to extend the availability of food over a longer period. The energy consumption as well as employment and value added by the PHF system is several times greater than the farm level activities. The total food system uses around 17 to 20% of total energy use in the economies. Of this, usually around one-fifth to one-quarter only is spent on production on the farm and the remainder goes into post-harvest operations [Mohod *et al.*, 2019, Mohod *et al.*, 2010, Ramachandra *et al.*, 1987, Reddy *et al.*, 2004].

Postharvest handling of agricultural produce is crucial for food security and supporting farmers in developing countries. Postharvest systems deliver sorted, segregated, packaged, and market-appropriate products to consumers in distant locations. These systems consume resources and

internal patterns, delivering outputs such as energy, information, data, wash water, chemicals, packaging materials, and skilled people. Outputs include prepared products, information, worker pay packets, waste water, and packaging waste, all of which are open systems, Fig 1 [Bekele *et al.*, 2021].

The components of the PHF system are: food processing, transportation, storage and cooking. The post-harvest-food system requires 2 to 4 times more energy than the energy on farms. Commercial energy is often used for food processing, such as milling, crushing, forwards transport, and to some extent for cooking. The share of commercial energy in total energy used in the PHF system ranges between 22% in Africa to 80% in Near East (Ramachandra *et al.*, 1987, Ramachandra *et al.*, 1988). The PHF system's energy consumption is influenced by income, urbanization, availability of fossil fuels or forests, and various parameters like cropping, dietary patterns, food export or import, and urban location. This information is discussed for four world regions and 90 developing countries, with country-specific insights provided graphically due to limited space for individual data reporting. [Parikh *et al.*, 1986].

Limited energy access is a significant challenge for small- and medium-sized enterprises in rural areas. Food losses in developing countries are primarily during harvest and storage, making post-harvest activities a priority for increasing farmers' income. This includes inadequate energy access for post-harvest operations, transportation, and distribution. Additionally, managing industrial by-products, residues, and wastes in an environmentally sound manner is crucial for the agrifood industry's development. [Kanji *et al.*, 2003, Ramachandra *et al.*, 2003]. One management option is to use industrial wastes to produce energy. In addition, rising energy prices affect the competitiveness of existing food processing enterprises and highlight the need for the food-processing sector to reduce energy consumption. Profit is generally one of the most common and accepted criteria determining the success of an economic activity. Integrated food-energy systems must be profitable in the long term for its practices to be adopted by all the stakeholders [Balasubramanian *et al.*, 2007, Bamgboye *et al.*, 2015, Banks *et al.*, 2022, Baruah *et al.*, 1996].

Lack of linkages between industry, government and institution, lack of technology and advanced technique in food processing, and lack of linkage between farmers and processing unit, are most significant factors responsible for scarcity of energy in PHF system. In Post-harvest loss can be defined as the degradation in both quantity and quality of a food production from harvest to consumption. Quality losses are intrinsic in nature leading to internal and external biochemical changes leading to changes in colour, flavour, nutritive value of food, calorific value etc. without

significant change in weight /volume. Quantitative loss is more serious in nature leading to value loss to the actors in the supply chain. It is mainly caused due to poor post-harvest management practices such as loss in weight due to moisture loss, physical damage, insect pest infestation, spoilage or rotting due to senescence and bacterial/ fungal infections etc [Jain *et al.*, 2004].

ENERGIES IN PHF SYSTEM

The food industry is heavily dependent on fossil fuels and significantly contributes to GHG emissions. The global population is also growing and food demand is expected to increase a 60% by 2050. To combat environmental pollution and create a more sustainable food sector, energy use during manufacturing needs to be reduced [Mohod *et al.*, 2011].

Energy is a crucial parameter in agri-food industries, accounting for profit and operating expenses like material, labor, and water. It plays a fundamental role in food systems, consumed in primary production and secondary activities like drying, cooling, storage, transport, and distribution [Taghizadeh *et al.*, 2019]. Agri-food systems account for 30% of the world's total energy consumption, requiring energy at all stages of the chain, including production, processing, transport, and manufacturing of fertilizers, agro-chemicals, and machinery [Jain *et al.*, 2006]. Electrical energy is the most convenient for PHF systems due to its ease of transportation, control, and conversion into other energy forms, with a 100% efficiency rate. Agro-industries have both direct and indirect energy sources. [Mohod *et al.*, 2019, Mohod *et al.*, 2010].

The direct energy includes electricity, mechanical power, solid, liquid and gaseous fuels. Indirect energy, on the other hand, refers to the energy required to manufacture inputs such as machinery, farm equipment, fertilizers and pesticides. The type of energy we use in the agrifood chain and how we use it, will in large part determine whether our food systems will be able to meet future food security goals and support broader development objectives in an environmentally sustainable manner. The agrifood systems not only require energy, they can also produce energy. For this reason, agrifood systems have a unique role to play in alleviating 'energy poverty' Fig. 2, [Jain *et al.*, 2006].

Indirect sources of energy:

Indirect sources of energy include seeds, manures, chemicals, fertilizers, and machinery, which release energy through conversion processes rather than directly, such as in farm yards and poultry [Mohod *et al.*, 2019]. Energy can be classified as commercial or non-commercial based on economic value. Non-commercial energy sources include human labor, animal sources, fuel wood,

twigs, leaves, agro-wastes, solar, wind, and animal dung. In developing countries, cooking is a primary energy use, with around one-third of the world's population relying on biomass for domestic needs [Jekayinfa *et al.*, 2008]. Large amounts of commercial energy can be obtained from renewable fuel crops and organic wastes. Such energy sources can be economically competitive and environmentally benign. Many practical technologies already exist, and promising new approaches are being subjected to further research. [Gene *et al.*, 2002].

The direct/Indirect energy may be further classified as renewable and non-renewable sources of energy depending upon their replenishment.

Renewable sources of energy

Renewable energy sources include human beings, animals, solar and wind energy, fuel wood, and agricultural wastes. Seed and manure are renewable indirect sources of energy. Sustainable energy technologies are being developed due to increasing energy demand. Energy-efficient buildings and industrial applications are crucial due to the negative effects of fossil fuels. To increase energy efficiency in the food industry, specific energy consumption reduction is needed. Models based on renewable energy, waste heat management, solar energy, efficient heat pumps, ice storage heat pumps, thermal energy storage heat pumps, drying with heat recovery, and dehumidification are being developed for wide utilization [Tuncer *et al.*, 2019].

Non-Renewable sources of energy

Coal and fossil fuels are non-renewable direct energy sources, while chemicals, fertilizers, and machinery manufacturing are non-renewable indirect sources of energy [Sarwer *et al.*, 2022].

Benchmarking energy consumption internally and externally is crucial for performance assessment and improvement. Historical data helps identify energy consumption and cost trends, while trend analysis helps understand the effects of capacity utilization on energy use efficiency and costs. External benchmarking compares inter-units across similar units, but it's essential to verify similarities to avoid misleading findings. Both methods help understand the effects of capacity utilization on energy use efficiency and costs on a broader scale. [Dienst *et al.*, 2011]. Few comparative factors, which need to be looked into while energy benchmarking externally is: • Scale of operation, • Vintage of technology • Raw material specifications and quality and • Product specifications and quality.

ENERGY ASSESSMENT/ACCOUNTING IN POST- HARVEST INDUSTRIES

The fundamental goal of energy management in processing industry is to produce value added goods and provides services with the least cost and least environmental effect. It is defined as *“The strategy of adjusting and optimizing energy, using systems and procedures so as to reduce energy requirements per unit of output while holding constant or reducing total costs of producing the output from these system [Dienst et al., 2011, Ramachandra et al., 1998, Ullah et al., 2021]*

The objective of Energy Management is to achieve and maintain optimum energy procurement and utilization, throughout the organization and:

1. To minimize energy costs / waste without affecting production & quality
2. To minimize environmental effects.

Energy Audit is the key to a systematic approach for decision-making in the area of energy management. It is an effective tool to:

- *Explore relationship between energy and production*
 - *Identify pattern, type, level and efficiency of energy use*
 - *Provide base line information for energy consumption*
 - *Help to identify energy conservation opportunity*
 - *Help to identify measures for efficiency improvement*
 - *Help to reduce disparities among similar process and provide ecological perspective*
- [Kulkarni et al., 2000].

Energy use assessment is a crucial tool for estimating energy requirements in processes before conservation, enabling the use of renewable energy technologies. This method helps alleviate energy constraints and reduce costs by identifying energy use patterns, energy loss sources, and excess energy use points. Variations in energy use may depend on machine parameters, material properties, plant layout, capacity, and processing methods. The main purpose of energy use assessment is to judge energy use patterns, energy loss sources, and excess energy use points [Mohod et al., 2011, Mohod et al., 2010, Morais et al., 2019, Kulkarni et al., 2000].

Gene et al., (2002), It stated that the study examines the energy consumption patterns in small cashew nut processing industries in Panruti taluk, Cuddalore district, Tamil Nadu, India. It compares energy utilization, specific energy consumption, and intensity of processing raw cashew nuts. The energy input for drying, steaming, cooling, tempering, cutting, separation, drying, kernel cooling, peeling, and grading and packing were quantified using standard equations. The total energy

consumption for processing 1000 kg of raw cashew nuts was 5866.2 MJ, 5911.69 MJ, and 6897.36 MJ for electrical drying, steam drying, and biomass drying industries, respectively. Cashew kernel drying, raw cashew nut drying, and steaming consume 95% of the energy. Cashew processing's energy intensity varied from 1.5 MJ/kg to 3 MJ/kg.

The study estimates energy consumption in eight small scale cashew nut processing operations in India, with drying, steaming, and kernel drying being the most energy-intensive processes. These operations consume 90% of the total energy. The study suggests the use of renewable energy technologies like solar tunnel dryers and forced convection solar cabinet dryers for energy conservation. The fuel analysis of cashew nut shells suggests gasification technology for heat generation [Mohod *et al.*, 2011].

The energy analysis of baby boiler for steaming of cashew nut seeds. solar energy, electricity and fuel are the major source of energy consumed for cashew nut processing. Finally, the results showed that while using electricity in the baby boiler for the steaming operation, for 60, 30 and 15 kg batch capacity industries, their corresponding total energy was estimated at 5321.43, 5540.14 and 6061.34 MJ [Mohod *et al.*, 2010].

The energy audit of cashew nut processing industries in Karnataka revealed significant disparities in energy consumption for producing similar products. 60% of units had a percentage production capacity utilization below 50%, with higher specific energy consumption and energy intensity. The energy intensity varied from 4.43 to 8.66 kg per kernel, suggesting potential for energy conservation of 30 to 48%. The relationship between specific energy consumption and production showed improvement with increased production, indicating optimal utilization of installed capacity [Reddy *et al.*, 2004].

The bakery and pastry sector's energy consumption and technologies are crucial for global competitiveness. The agri-food sector must ensure a strong, innovative industrial base at all stages of the value chain, capable of international competition and product and service quality differentiation [Morais *et al.*, 2019]. The characteristics of confectionery plants are influenced by raw material type, production technology, equipment structure, and automation. These factors influence energy consumption. This article provides technical and technological factors for analysing energy efficiency in the confectionery industry, aiding in selecting optimal techniques and creating a database tracking these characteristics. [Wojdalski *et al.*, 2015].

Preliminary studies on energy conservation in canned mango pulp processing found that A10 cans can be filled with hot mango pulp at 85-90°C, sealed, sterilized, and cooled, reducing steam consumption and increasing production without affecting the quality of the canned mango pulp. This method can be applied at both laboratory and factory levels [Radhakrishnaiah *et al.*, 1983].

The energy audit in a tea manufacturing industry in North Bengal, India, reveals concerns about rising energy bills and environmental impacts. The audit helps identify opportunities to reduce energy bills while maintaining production quality and conserving the environment. The focus is on a medium-scale tea manufacturing industry with a garden in Jalpaiguri, North Bengal. The audit determines energy usage by machines and production processes, and suggests recommendations to reduce overall energy use.[Morais *et al.*, 2019].

The tea industry's garden and factory sectors were analysed for energy use patterns. A tea garden required 18408 MJ ha⁻¹ of human energy in the first year, while a tea factory required 5.56-13.48 MJ kg⁻¹ of electrical energy. Fuel energy varied from 14.9 to 63.62 MJ kg⁻¹. The study also estimated energy consumption of eight-unit operations in small scale cashew nut processing in India. Three energy-intensive operations, cashew nut drying, steaming, and drying of cashew kernels, consumed 90% of the total energy consumption. The study suggests energy conservation and utilization of renewable energy technologies [Chhinnan *et al.*,1980].

The study surveyed 25 tea estates in Assam to assess the energy consumption for processing green tea leaves. Data was collected through questionnaires and personal interviews. The data pertaining to energy input per tone of made tea for various operations were converted into equivalent energy units, human labour = 1.96 MJ h⁻¹, coal =32.8 MJ kg⁻¹, electricity= 11.93 MJ kWh⁻¹ and oil = 41.3 MJ l⁻¹. The total energy input for processing tea leaves, on small, medium and large estates were 53600, 40718 and 38026 MJ per tone, respectively [Yadav *et al.*, 2019].

The study examined the energy consumption of various operations in converting paddy into rice in raw and parboiled rice mills. Results showed that the polisher consumes a significant amount of energy, with a minimum EEC of 0.5 kWh and a maximum SEC of 5.07 kWh/t. The total energy consumption was 36.29 kWh/t, with a 70% recovery of polished rice. The study also revealed that the total energy consumption was 923.97 kWh/t, with an 80% recovery of the final product. [Chhinnan *et al.*,1980]

A study on a vegetable oil refinery in Nigeria evaluated its energy and exergy efficiency. The plant's four main operations were neutralizer, bleacher, filter, and deodourizer. The energy intensity

for processing 100 tonnes of palm kernel oil into edible oil was 487.04 MJ/tonne, with electrical energy accounting for 4.65%, thermal energy at 95.23%, and manual energy at 0.12%. The deodourizer was the most energy-intensive operation, accounting for 56.26% of the net energy input, Sulaiman *et al.*, 2012.

The dairy industry faces a significant energy crisis due to depleting conventional sources and growing industrial and domestic loads. To address this, it is crucial to explore energy-generating and conservation methods. The dairy industry uses electrical and thermal energy, and identifying potential energy savings is crucial for a competitive advantage. Energy consumption and savings are assessed based on equipment and functional purpose. [Vinutha *et al.*, 2016].

The pulp and paper manufacturing process requires steam for pulping and papermaking, while electricity is used for pumping and rollers. To reduce energy bills, several energy-saving measures can be implemented, including steam optimization, replacing inefficient pumps, and installing high-tensile motors. The proposed energy conservation measures can reduce the total annual cumulative bill by 18%, resulting in an annual savings of around Rs. 446.53 Lakhs. [Irena *et al.*, 2021].

The energy audit of condiment industries found that electric motors and boilers consume the most energy. Despite the absence of variable speed drives, motors run under loaded conditions. Variable speed drives can save up to 60% of electrical energy by reducing motor speed by 20%, 40%, and 60%, respectively. This could save about 276 MWh, 551 MWh, and 827 MWh electrical energy. [Ullah *et al.*, 2021].

A Nigerian wheat processing plant conducted an energy study to determine the energy consumption pattern for flour production. The study used a process analysis method to evaluate energy requirements for eight-unit operations. The energy used was electrical and manual, with an average intensity of 0.101 MJ/Kg. The milling unit was the most energy-intensive, with an intensity of 0.073 MJ/kg (72.20%). Optimizing the milling process is suggested to make the system more energy-efficient [Olaoye *et al.*, 2014].

The energy audit in flour mill plant was studied and revealed that an energy audit of the 2015 production year of Crown Flour Mill Plants and reported that the energy requirement of the process machines and consumption capacities for Mills A and B was a total of 14.1GWh/year which is far lesser than the energy generated from the diesel fuel used. Hence, a lot of energy is being wasted in the flour production plants. [Aliu *et al.*, 2018].

Inefficient sugar processing in Gur and Khandsari units in northern India results in significant sugar loss and excess commercial energy consumption. The loss exceeds 1.5 million tons per year, and the commercial energy required to produce raw sugar is higher than refined sugar production. Pathak *et al.*, 2008].

ENERGY ESTIMATION OF UNIT OPERATIONS IN PROCESSING INDUSTRY

The energy estimation in the unit operations of post-harvest food industry required the systematic approach [Kulkarni *et al.*, 2000, Ladha *et al.*, 2019, Mohod *et al.*, 2011, Radhakrishnaiah *et al.*, 1983]. The step-by-step methodology to begin the energy estimation processing unit should be planned as

- Decide an objective of analysis to quantify the energy accounted in unit
- Choose a system boundary of energy utilization
- Draw a flow diagram of process
- Identify all mass and energy input
- Quantify all mass and energy input
- Identify all mass and energy output
- Quantify all mass and energy output
- Analyze the recorded data
- Draw graphical representation of energy use in unit.
- Identify energy intensive operations in the unit
- Explore the possibility of energy conservation
- Retrofitting of existing system with possible renewable energy systems

The commonly used unit operations, energy sources and parameters need to be recorded during the unit operations in various agro processing industries are summarized in Table 1.

The data recorded during the energy audit for unit operations should be averaged over the period of season or on the basis of yearly data to avoid the fluctuations and errors in energy consumption. The following empirical equations could be used to calculate energy consumption using various sources in post-harvest food industries. [Kothari 2000, Kulkarni 2000, Mohod *et al.*, 2019, Mohod *et al.*, 2010, Mohod *et al.*, 2010, Reddy *et al.*, 2004].

The mathematical conversions used for computation of different energies for unit operations are as follows.

$$\text{Electrical energy: } E_p = K.P.t_e (\text{kWh}) - (1)$$

$$\text{Thermal energy: } E_f = C_f \cdot W_f \text{ (J)} \quad \text{-- (2)}$$

$$\text{Manual energy: } E_m = 0.075N \cdot t_m \text{ (kWh)} \quad \text{--(3)}$$

$$\text{Solar energy : } E_s = I_{sc} \cdot A \cdot t_s \text{ (J)} \quad \text{-- (4)}$$

The total energy, E_T for unit operations in processing is computed as

$$E_T = E_P + E_f + E_m + E_s \quad \text{---- (5)}$$

E_T = Total energy requirement for all processing operations (J)

T = Time taken for a particular operation (h)

C= Lower heating value of fuel used for a particular operation (J kg^{-1} or J l^{-1})

I_{sc} = Average solar energy availability ($\text{J s}^{-1} \text{ m}^{-2}$)

W= Quantity of fuel used for a particular operation (l or kg)

P= Electrical power consumed for a particular operation (kW)

N=Number of persons involved in a particular operation

K =Efficiency of the electric motor used for a particular operation

A= Open sun drying area, m^2

The assessment of energy in agro processing operations involves assessing various factors such as machine parameters, material properties, plant layout, capacity, and processing method. This information is crucial for developing energy-efficient units, which can reduce costs and energy loss due to mismatch between prime mover and machine or transmission losses. The main purpose is to determine energy use patterns, sources, and excess points [Mohod *et al.*, 2010].

The study by Kulkarni *et al.* (2000), estimated energy consumption in eight-unit operations of cashew nut processing using data from nine mills. Equations were developed to calculate electricity, fuel, and labor requirements for each operation. Results showed total energy intensity varied between 0.21 and 1.161 MJ kg^{-1} , with electrical energy intensity ranging from 0.0052 to 0.029 MJ kg^{-1} and thermal energy intensity ranging from 0.085 to 1.064 MJ kg^{-1} . These equations were useful for budgeting, forecasting, and planning plant expansion.

The study evaluated energy consumption in nine Nigerian palm-kernel oil (PKO) mills using mathematical expressions and empirical equations. Mathematical expressions were used to evaluate energy requirements for seven-unit operations, while empirical equations were used to relate energy requirements to palm-nut/kernel input. [Kulkarni *et al.*, 2000].

ANALYSIS OF ENERGY DATA AND REPRESENTATION

The recorded data with the help of mathematical expressions in the food industries could be presented in different form to compare with the similar industries [Ladha *et al.*, 2019, Jekayinfa *et al.*, 2008, Jekayinfa *et al.*, 2007]. The energy use patterns and energy use efficiency indicators viz;

- i. Energy intensity (E_I)
- ii. Energy cost per unit product ($E_{C/P}$)
- iii. Energy ratio (E_R)
- iv. Food energy ratio (F_{ER})
- v. Percentage yield by weight.

The analysis of energy consumption and production in industries is crucial to determine disparities in energy consumption for producing the same quantity of product, considering factors like installed capacity, production, and energy intensity. [Ramachandra *et al.*, 1987, Ramachandra *et al.*, 1998, Mohod *et al.*, 2010, Morais *et al.*, 2019].

Installed capacity (P):

The installed capacity of the industry was determined by considering the capacity, number of batches performed per day and average working days in a year.

$$\text{Installed capacity, } P \text{ (kg)} = \text{capacity} \times \text{no. of batches/day} \times \text{working days} \quad \text{-- (6)}$$

Production (P_r):

The industry's production is determined by analyzing the average actual raw material processed per kg yr⁻¹, taking into account the average of the last three years' production data.

Percent production capacity utilization (P_{PCU}):

The percent production capacity utilization of the industry has to be calculated as the ratio of actual production to the total installed capacity of the industry.

$$\text{Percent production capacity utilization } (P_{PCU}), \% = (P_r/P) \times 100 \quad \text{- (7)}$$

Total energy (E_n):

The industry's energy consumption for unit operations and lighting must be estimated using the maxi energy audit method and cross-checked from electrical bills annually, while the quantity and type of biomass used for raw material processing must be measured. All the forms of energy sources were converted in to the common unit of energy i.e MJ Yr⁻¹.

Energy intensity (E_I):

The energy intensity of industry has to be calculated as the ratio of Total energy consumption (E_n) and Production (P_r).

$$\text{Energy intensity } (E_I), \text{ MJ kg}^{-1} = \text{Total energy } (E_n) / \text{Production } (P_r) \quad \text{-- (8)}$$

Another way to represent the flow of input and output energies in the plant is with the help of symbols (Fig 2.). Different symbols for energy accounting of food processing operations are used for development of energy flow diagram Fig.3, Mohod *et al.*, 2010

OPPORTUNITIES AND RENEWABLE ENERGY TECHNOLOGIES FOR PHF SYSTEM

There are several opportunities and renewable energy technologies that the post-harvest food system (PHF) can consider incorporating. These options can provide numerous benefits in terms of sustainability, cost savings, and environmental impact. Here are some opportunities technologies worth exploring: Solar PV power on PHF buildings can reduce energy costs and traditional power reliance. Wind turbines can generate electricity from wind energy, reducing dependence on fossil fuels and carbon emissions. Solar drying reduces moisture content and increases shelf-life of fruits, vegetables, and grains. Biogas production from organic waste serves as a fuel source for cooking and other food industry energy needs. Biomass energy, derived from organic matter, can be used for heating, cooking, and other food industry needs.

Renewable energy resources are being utilized as a replacement for conventional fuel in the post-harvest food system. Solar and biomass technologies are widely adopted as suitable energy replacements, as energy accounting units are energy-intensive operations.

Solar Energy Technologies

The study explores post-harvest operations for turmeric processing, including conventional boiling and drying. A new technology for boiling and drying agricultural produce, specifically turmeric rhizomes, was developed. Results show solar drying is superior to direct sun drying, achieving desired moisture content and essential quality in 42 hours. [Sanchavat *et al.*, 2012].

The techno-economic analysis of typical dryers found that plastic collectors with a 5–10-year lifespan are the cheapest, while conventional collectors have a useful lifetime of over 20 years but are more economical [Sodha *et al.*, 1991].

The economics was assessed of drying timber in the title kiln along with the conventional drying techniques. Compared to air drying, the solar drying was cheaper and cost less than half of the steam kiln [Sattar *et al.*, 1994].

The study evaluated the efficiency of a forced convection solar dryer for drying groundnut, ginger, and garlic compared to an electrically operated tray-type mechanical dryer. Results showed the solar dryer was more cost-effective and efficient, with a benefit cost ratio of 1.56 and 1.18, respectively. [Kanji *et al.*, 2003].

The study evaluated a solar tunnel dryer's techno-economic analysis using net present worth, benefit cost ratio, and payback period. The commercial solar tunnel dryer had a net present worth of Rs 78,74,500, compared to Rs 36,52,500 for a diesel-fired dryer. The benefit cost ratio was 7.08 for the solar tunnel dryer and 2.56 for the diesel-fired dryer. [Sevda *et al.*, 2003].

A solar dryer was developed for drying vegetables and fruit, with a separate collector and drying chamber and two axial flow fans. The drying cost was Rs 17.52 and 41.35 kg⁻¹, respectively. The cumulative present worth of annual savings over 20 years was Rs 31659.00, much higher than the capital cost of Rs 6500.00. The payback period was 3.26 years [Sreekumar *et al.*, 2008].

The study examined the energy requirements of a solar-assisted dryer for drying onion slices. The energy required per unit mass of water removed without air recirculation ranged from 23.548 to 62.117 MJ kg⁻¹, while the energy required per unit mass of water removed was between 12.040 and 38.777 MJ kg⁻¹ [Sarsavadia *et al.*, 2008].

A comparative study on solar cabinet, vacuum assisted solar dryer and open sun drying for drying of tomato slices (4-, 6- and 8-mm thicknesses) was reported. The overall study concluded that good quality dehydrated tomato slices could be produced by using vacuum assisted solar dryer compared to solar cabinet and open sun drying methods [Perumal *et al.*, 2007].

Biomass Energy Technologies

The study evaluated the techno-economic aspects of biomass briquetting in India, analyzing its financial performance using simple cost functions for briquetting machines. It calculated unit costs for different raw materials and units, and analyzed factors affecting briquette production costs [Tripathi *et al.*, 1998].

The study evaluated the financial aspects of biomass gasifier-based institutional cooking, comparing its thermal energy unit cost to LPG and coal-based options. It works out to Rs 0.37MJ⁻¹

for a 29 kW_{th} (25000 kcal h⁻¹) biomass gasifier system while for a 291 kW_{th} (250 000 kcal/h) system it was Rs 0.23 MJ⁻¹. Biomass gasifier-based institutional cooking systems were always financially more attractive than corresponding coal-based systems and are even better than LPG-based systems for capacities over 58 kW_{th} [Tripathi *et al.*, 1999].

The performance of energy efficient biomass cook stove suitable for different fuel wood & briquetted fuel was reported. It was tested with babul wood (*Prosopis juliflora*), groundnut (*Arachis hypogaea*) shell briquettes, sawdust briquettes and cashew nut (*Anacardium occidentale*) shell. The stove was insulated by refractory cement (Insulyte -11U) to minimize heat losses. The stove has exhibited about 35% thermal efficiency [Panwar *et al.*, 2009].

The reliability of power systems is crucial for achieving decarbonisation targets, but challenges and failures often hinder this. The literature rarely discusses these challenges and technological solutions. Future research should focus on developing a solution matrix with renewable technology solutions to address these challenges. The potential of these solutions, particularly cost-effective energy, can help prioritize and reduce specific challenges. The study's categories can help determine specific needs and increase transparency in the renewable energy integration process. [Ashfaq *et al.*, 2016].

Table 2&3: Describe the Matrix of solar energy& biomass energy technologies for post-harvest operations [Mohod *et al.*, 2019]

The implementation of these opportunities and renewable energy technologies can provide PHF with a more sustainable, cost-effective, and environmentally friendly approach to processing operations. It is essential to conduct feasibility studies, evaluate potential returns on investment, and engage relevant stakeholders to ensure successful integration and long-term benefits.

The costs and performance of renewable energy technologies have reached the stage where the number of economical applications in developing countries is increasing, particularly in the grid and off-grid markets for electricity [www.fao.org].

The conclusions are as follows. (a) Competition and regulatory reform in the energy industry, particularly in the electricity sector, can boost investments in renewable energy by reducing subsidies for fossil and hydro resource electricity production.

(b) Key technologies offer potential for further cost reductions, with each generation acting to lower future costs. These benefits should be acknowledged in tax and regulatory policies, as well as in budgetary allocations for R&D and education.

(c) The environmental advantages of renewable energy will become more apparent as developing countries begin to introduce their environmental policies on fossil fuels.

(d) Accelerating the development of renewable energy options would be a more effective and focused policy, reducing uncertainties and costs associated with climate change response.

CONCLUSION

The energy auditing in the post-harvest food (PHF) system, as well as exploring opportunities for using renewable energy sources is the key tool to assess and analyze the energy usage within the PHF system and identify potential areas for implementing renewable energy solutions. It is necessary to standardise reported consumption data across the sector and policy efforts must be devoted to this task urgently to develop efficient strategies to optimise the whole food system, allocate resources more effectively and reduce both waste and fossil fuel dependency.

The systematic approach for estimation of energy in industry helps to identify the energy intensive operation and type of energy used. The wide utilization of commercially available renewable energy technologies for post - harvest operations can provide the profitable solution for energy security and clean environment. Solar drying, biogas production, hydroelectric power, wind power, and biomass energy are just a few examples of the various renewable energy options that can be harnessed in this sector.

References:

1. Aliu, S. A., Onochie, U. P., Itabor, N. A., & Adingwupu, A. C. (2018). Energy audit of a flour mill plant: A case study of Crown Flour Mill PLC. *Nigerian Research Journal of Engineering and Environmental Sciences*, 3(1), 345-358.
2. Amjad, W., Munir, A., Akram, F., Parmar, A., Precoppe, M., Asghar, F., & Mahmood, F. (2023). Decentralized solar-powered cooling systems for fresh fruit and vegetables to reduce post-harvest losses in developing regions: a review. *Clean Energy*, 7(3), 635-653.
3. Anonymous. 2006. Comprehensive Industrial Document and Environmental Standards for Cashew Seed Processing Industries, Central Pollution Control Board, N.Delhi, 2-29.
4. Anonymous. 2009. Statistical Information, Annual Report, Directorate of Cashew and cocoa development, Kochi, India 2006-2007. 23-28.4.b)
5. Ashfaq, S., Ahmad, M., & Munir, A. (2016). Design, development and performance evaluation of a small-scale solar assisted paddy dryer for on farm processing. *Mehran University Research Journal of Engineering & Technology*, 35(2), 217-228.
6. Balasubramanian, D. 2007. Optimization of processing parameters using farm level cashewnut processing. *J. Agril. Engg. Today*. Vol. 32 (2): 35-41.
7. Bamgboye, A. I., & Kosemani, B. S. (2015). Energy input in the production of cassava. *Energy and Environment Research*, 5(1), 42-48.
8. Banks, N. H. (2022). Postharvest systems—some introductory thoughts. In *Postharvest Handling* (pp. 3-16). Academic Press.
9. Baruah, D.C. and Bhattacharyya, P.C. 1996. Energy Utilization pattern in the manufacturing of Black tea. *J.of Agril. mechanization in Asia, Africa and latin America*. Vol.27 (4):65-70.
10. Baruah, D.C. and Bhattacharyya, P.C. 1996. Energy Utilization pattern in the manufacturing of Black tea. *J.of Agril. mechanization in Asia, Africa and latin America* **27** (4):65-70
11. Bekele, D. (2021). Role of postharvest management for food security: A review. *Adv. Crop Sci. Technol*, 9, 1-6.
12. Bureau of Energy Efficiency. <https://beeindia.gov.in/sites/default/files/1Ch3.pdf>

13. Chhinnan, M.S., Singh, R.P., Pederson, L.D., Carroad, P.A., Rose, W.W. and Jacob, N.L. 1980. Analysis of energy utilization in spinach processing. Transaction of ASAE.0001-2351/80/2302-0503502,503:507
14. Denis Hayes, Biological Sources of Commercial Energy, BioScience, Volume 27, Issue 8, August 1977, Pages 540–546.
15. Dhanushkodi, S., Wilson, V. H., & Sudhakar, K. (2016). Energy analysis of cashew nut processing agro industries: a case study. Bulgarian Journal of Agricultural Science, 22(4), 635-642.
16. Dienst, C., Ortiz, W., Pfaff, J. C., & Vallentin, D. (2011). Food issues: renewable energy for food preparation and processing.
17. Divya, K., Parameshwari, N., Logeswari, K., Pandi, K., Naveena, K., (2018). power utilisation calculation and energy audit. IJARIE-ISSN(O)-2395-4396.
18. Erdiwansyah, Mahidin, Husin, H., Nasaruddin, Zaki, M., & Muhibbuddin. (2021). A critical review of the integration of renewable energy sources with various technologies. Protection and control of modern power systems, 6, 1-18.
19. Gene Owens. 2002. Best practices guide: economic & financial evaluation of renewable energy projects. U.S. Agency for International Development Office of Energy, Environment & Technology, Global Bureau Environment Center, Washington, DC 20523:1810.
20. Goyal, k., Singh, S., Jai, p. (2013). Energy Consumption in Rice Processing using Energy Audit. Advances in energy engineering, Excel India publisher, New delhi.
21. <https://ecoenergies.co.in/pulp-and-paper-energy-audit/>.
22. <https://www.fao.org/3/an913e/an913e01.pdf>.
23. <https://www.mofpi.gov.in/sites/default/files/study-report-of-post-harvest-losses.pdf> .
24. Internatinal energy agency (IEA) (2010). Energy poverty: How to make modern energy access universal.
25. Irena, F. (2021). Renewable Energy and Agri-food Systems: Advancing Energy and Food Security towards Sustainable Development Goals.

26. Jain, A.K.2006. Design parameters for a rice husk throatless gasifier reactor. *Agricultural Engineering International: the CIGR Ejournal*, Manuscript EE 05 012. **VIII**. May, 2006.
27. Jain, N.K., Kothari, S. and Mathur, A.N. 2004. Techno-economic evaluation of a forced convection solar dryer. *Journal of Agricultural Engineering*. 41(3): 6-12.
28. Jekayinfa, S.O. and Bamgboye, A.I. 2008. Energy use analysis of selected palm-kernel oil mills in south western Nigeria. *Energy*. Vol.33(1):81-90.
29. Jekayinfa, S.O. and Bamgboye, A.I. 2006. Estimating energy requirement in cashew (*Anacardium occidentale L.*) nut processing operations. *Energy*. Vol. 31(8-9): 1305-1320.
30. Jekayinfa, S.O. and Bamgboye, A.I. 2007. Development of equations for estimating energy requirements in palm-kernel oil processing operations. *J. Food Engg*. Vol. 79(1): 322-329.
31. Kanji, N. and Vijfhuizen, C. 2003. 'Cracking the Cashew Nut Myths? The Dilemmas and Challenges of Gendered Policy Research in the Cashew Sector in Mozambique', *Repositioning Gender in Development Policy and Practice*, Institute of Development Studies (IDS), University of Sussex 2-4 July 2003.
32. Kothari S. 2000. Greenhouse under composite climate. *Proceeding of National Conference on Commercialization of Renewable Energy Sources*, held at Udaipur : 2-5.
33. Kulkarni, S.D. 2000. Energy use assessment in Agro Processing operations: Factors to be considered for data collection for comparison. *J. Agri. Engg. Today*. Vol. 24(4): 51-61.
34. Ladha-Sabur, A., Bakalis, S., Fryer, P. J., & Lopez-Quiroga, E. (2019). Mapping energy consumption in food manufacturing. *Trends in Food Science & Technology*, 86, 270-280.
35. Mitra, S., & Roy, T. (2016). An energy audit in a tea manufacturing industry at North Bengal, India. *International Journal of Research in Engineering and Technology*, 5(6), 83-89.
36. Mohod, A.G., B. Shirsat and A. A Deogirikar, 2019. Renewable energy for value added agro processing. *International Journal of chemical studies*, 7(4): 3122–3125.
37. Mohod, A.G., S.Jain and A. G Powar, 2010. Energy option for small scale cashew nut processing in India. *Energy Research Journal*, 1(1): 47–50.

38. Mohod, A.G., S.Jain and A. G Powar, 2011. Quantification of energy consumption for cashew nut (*Anacardium occidentale* L.) processing operations. *International Journal of Sustainable Energy*, 30: S11-S23.
39. Mohod, A.G., S. Jain, A. G Powar, N. Rathore and A. K. Kurchania, 2010. Elucidation of Unit operations and energy consumption pattern in small scale cashew nut processing mills. *Journal of Food Engineering*, 99: 184–189.
40. Morais, D., Gaspar, P. D., Silva, P. D., Santos, F. C., Andrade, L. P., & Nunes, J. (2019). Assessment of the energy consumption and technologies in the bakery and pastry sector–The Portuguese case study. *Energy Procedia*, 161, 83-92.
41. Moreno, R., & Rios, R. (2002). Study on sawdust drying techniques in fluidised bed.
42. Njomo, D. 1995. Techno-economic analysis of a plastic cover solar air heater. *Energy Conversion and Management* 36: 1023-1029.
43. Olaoye, O. S., Adefajo, A. A., & Ekundayo, S. O. (2014). Energy analysis of a wheat processing plant in Nigeria. *ARPN Journal of Engineering and Applied Science*, 9(9), 1586-1591.
44. Panwar, N. L., Rathore, N. S. and Kurchania, A. K. 2009. Experimental investigation of open core downdraft biomass gasifier for food processing industry. *Mitigation and Adaptation Strategies for Global Change*.14 (6): 547-556.
45. Parikh, k., Syed, S. 1986. Energy use in the post-harvest food (phf) System of developing countries. International institute for applied systems analysis 2361 Laxenburg, Austria.
46. Pathak, B.S., Amar singh, Didar singh and Varma, R. 1987. Energy economics of sugarcane processing technologies in northern India, *J. of Agril. Engineering*. xxix (1): 91-103.
47. Pathak, B.S., Patel, S.R., Bhave, A.G., Bhoi, P.R., Sharma, A.M. and Shah, N.P. 2008. Performance evaluation of an agricultural residue-based modular throat-type down-draft gasifier for thermal application. *Biomass and Bioenergy*. 32(1): 72-77.
48. Perumal, R. 2007. Comparative Performance of Solar Cabinet, Vacuum Assisted Solar and Open Sun Drying Methods, A M. Sc. (Bioresource Engineering) thesis submitted to McGill University, Montreal, Canada.

49. Pokhrel, B. (2021). Review on post-harvest handling to reduce loss of fruits and vegetables. *International Journal of Horticulture and Food Science*, 2(2), 48-52.
50. Practical action (2007). Evaporative cooling. Technical Brief. War wick shire, Uk.
51. Radhakrishnaiah Setty, G., & Patwardhan, M. V. (1983). Energy conservation in the processing of canned mango pulp. *Indian Food Packer*, 37(1), 91-93.
52. Ramachandra, T.V. and Subramanian, D.K. 1987. Analysis of energy utilization in the grain mill sector in Karnataka. *Energy Policy, State Environment Report of Kamataka*, 1985—86. Centre for Taxonomic Studies, Bangalore, India: 107-121.
53. Ramachandra, T.V. 1998. Energy utilization in rural industries in Karnataka. *International Journal of Ambient Energy*. 19(2): 75-92.
54. Reddy, S., RaghuRam, P., Neelakanta Sastry, T.V. and Bhavani Devi, J. 2004. A textbook of Agricultural Economic. Oxford and IBH publishing. 291-294.
55. Rubab, S. and Kandpal, T.C. 1996. Biofuel mix for cooking in rural areas: Implications for financial viability of improved cookstoves. *J.of Bioresource Technology*, **56** (3):169-178.
56. Sanchavat, H., Kothari, S., Sharma, D., Jain, N. K., & Sharma, G. P. (2012). Performance and economic evaluation of biomass and solar energy system for turmeric processing. *Indian Journal of Hill Farming*, 25(2), 1-5.
57. Sarsavadia, P.N.2007. Development of a solar-assisted dryer and evaluation of energy requirement for the drying of onion. *Renewable Energy*, **32** (15): 2529-2547.
58. Sarwer, A., Hussain, M., Al-Muhtaseb, A. A. H., Inayat, A., Rafiq, S., Khurram, M. S., ... & Jamil, F. (2022). Suitability of biofuels production on commercial scale from various feedstocks: a critical review. *ChemBioEng Reviews*, 9(5), 423-441.
59. Sattar, M. A. 1994. Economics of drying timber in greenhouse-type solar kiln. *Holz als Roh- und Werkstoff* (Journal written in English) **52** :157-161.
60. Sevda M.S., Rathore, N.S. and Singh, Pratap. 2004. Techno-economics of solar tunnel dryer – A case study. *J. of Agricultural Engineering*. 41(3): 13-17.
61. Shanmugam, V. and Natarajana, E. 2006. Experimental investigation of forced convection and desiccant integrated solar dryer. *Renewable Energy*, **31**(8): 1239-1251.

62. Singh, Paul R. 1978. Energy accounting in food process operations. *J. Food Technology*. April 1978: 40-46.
63. Singh, R.N., Jena, U., Patel, J.B. and Sharma, A. M. 2006. Feasibility study of cashew nut shells as an open core gassifier feedstock. *Renewable Energy*. **31**(4): 481-487.
64. Sodha, M. S., Chandra, R., Pathak, K., Singh, N. P. and Bansal, N. K. 1991. Techno-economic analysis of typical dryers. *Energy Conversion and Management* **31**: 509-513.
65. Sreekumar, A., Manikantan, P. E. and Vijayakumar, K. P. (2008). Performance of indirect solar cabinet dryer, *Energy Conversion and Management* **49**(6): 1388-1395.
66. Sulaiman, M. A., Oni, A. O., & Fadare, D. A. (2012). Energy and exergy analysis of a vegetable oil refinery.
67. Taghizadeh-Hesary, F., Rasoulinezhad, E., & Yoshino, N. (2019). Energy and food security: Linkages through price volatility. *Energy policy*, 128, 796-806.
68. Tripathi, A.K., Iyer, PVR and Kandpal, T.C.1998. A techno-economic evaluation of biomass briquetting in India. *J. of Biomass & Bioenergy*.**14**(6):479-488.
69. Tripathi, A.K., Iyer, PVR and Kandpal, T.C.1999. Biomass gasifier based institutional cooking in India: a preliminary financial evaluation. *J. of Biomass & Bioenergy*. **17** (2):165-173.
70. Tuncer, A. D., Mavuş, R., Gökçe, C., Koşan, M., & Aktaş, M. (2019). Efficient Energy Systems Models for Sustainable Food Processing. *Turkish Journal of Agriculture-Food Science and Technology*, 7(8), 1138-1145.
71. Ullah, K. R., Thirugnanasambandam, M., Saidur, R., Rahman, K. A., & Kayser, M. R. (2021). Analysis of energy use and energy savings: a case study of a condiment industry in India. *Energies*, 14(16), 4798.
72. Vinutha, K., Anand, B., Rajan, N. A., & Tejamourthy, M. E. (2016). Exploring Energy Auditing in Dairy Industry. *International Journal of Innovative Research in Electrical, Electronics, Instrument Control Engineering*, 4(2), 91-96.
73. Waheed, M.A., Jekayinfa, S.O., Ojediran, J.O. and Imeokparia, O.E. 2008. Energetic analysis of fruit juice processing operations in Nigeria. *Energy* **33**(1): 35-45.

74. Wojdalski, J., Grochowicz, J., Drozd, B., Bartoszewska, K., Zdanowska, P., Kupczyk, A., & Wojcik, G. (2015). Energy efficiency of a confectionery plant—Case study. *Journal of Food Engineering*, 146, 182-1.
75. Yadav, L. S., & Srivastava, A. P. (1998). Energy requirement for processing green tea leaves. *Agricultural Engineering Today*, 22(3and4), 28-34.

UNDER PEER REVIEW